

The new range of industrial vacuums for food, pharma, packaging and OEMs

Nilfisk-CFM presents four new models designed to meet the market and customer requirements: innovative solutions in terms of safety and design, ease of use and reliability. Who else knows your application better, worldwide? Hygiene, safety, reliability, silentness are the main features of this new line.



FIXED VACUUM ON PROCESSING MACHINE



CLEANING OF COMPRESSING MACHINE



FIXED VACUUM ON MEDICINES PACKAGING MACHINES



CLEANING OF DRIERS

When Design and Hygiene meet performance







- Innovative with smooth surface DESIGN
- CONFORMS WITHGMPs.
- Low noise level
- ABSOLUTE FILTRATION FOR FINE AND TOXIC DUST
- SAFE REPLACEMENT OF THE ABSOLUTE FILTER
- ATEX certified
- L, M, H CERTIFIED
- PullClean, innovative filter cleaning system

| Master Description | VHW310 | VHW311 | VHW320 LC | VHW321 LC |
|--|----------------------|----------------------|------------------------------|------------------------------|
| Part No. | 4041100304 | 4041100308 | 4041200372 | 4041200383 |
| Voltage (V) | 400 | 400 | 400 | 400 |
| Frequency (Hz) | 50 | 50 | 50 | 50 |
| Ip Protection Class | 55 | 55 | 55 | 55 |
| Insulation Class | I | ı | I | ı |
| Rated Power (kW) | 1,5 | 1,5 | 1,5 | 1,5 |
| Airflow Without Hose (L/Sec) | 58 | 58 | 53 | 53 |
| Vacuum Max (Kpa) | 24 | 24 | 17 | 17 |
| Sound Pressure Level At 1.5 M (Db(A)Iso 3744) | 61 | 60 | 60 | 60 |
| Container Capacity (L) | 5 | 5 | 25 | 25 |
| Main Filter Type | L Class Polyester | L Class Polyester | M Class Cartridges Filter | M Class Cartridges Filter |
| Main Filter Area (cm²) | 4250 | 4250 | 10000 | 10000 |
| Inlet (mm) | 50 | 50 | 50 | 50 |
| Length X Width X Height (cm) | 71x42x90,5 | 71x42x90,5 | 76,5x42x117 | 75x42x117 |
| Weight (Kg) | 49 | 61 | 73 | 78 |

Innovative features





PullClean filter cleaning system



SAFE REPLACEMENT OF THE ABSOLUTE FILTER



NEW LID LOCKING SYSTEM



ABSOLUTE FILTER