



Think out loud.

PRODUCT DESCRIPTION

DESCRIPTION

Flexible transparent dry erase surface on a white opaque vinyl film coated with a repositionable pressure acrylic adhesive and backed with a clear polyester release liner.

PRODUCT DATA	VALUE	TEST METHOD
--------------	-------	-------------

PHYSICAL PROPERTIES

Thickness mil (micron)	Film: 8.3 (211) +/- 10% Adhesive: 1.0-1.1 (25-28) +/- 0.1 (3) Liner: 1.4 (36) +/- 5%	ASTM D 3652
---------------------------	--	-------------

Dimensional Stability (%)	MD: 0.50 TD: 0.50	On Al panel at 160 F (71 C) for 24 hr
---------------------------	----------------------	--

ADHESION PROPERTIES

Expected Sheer (hours)	5.0	ASTM D 3654 Method A (1 hr dwell, 1 sq in, 4 lb load)
------------------------	-----	--

Tack (gm)	270	ASTM D 2979
-----------	-----	-------------

SERVICE TEMPERATURE RANGE	-20 F to 176 F (-29 C to 80 C)	
---------------------------	--------------------------------	--

APPLICATION TEMPERATURE	60 F (10 C) Note: Stabilize product in environment temperature 24 hrs before application.	
-------------------------	--	--

STORAGE STABILITY	18 Months stored at 70 F (21 C) and 50% RH	
-------------------	--	--

EXPECTED EXTERIOR LIFE	Five years if unopened (protected edges, vented area)	
------------------------	---	--

PERFORMANCE & SUITABILITY

All of the descriptive information, the typical performance data, and recommendations given shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. The information is merely an attempt to assist for possible use and shall not constitute any warranty implied or otherwise, guaranty, or obligation. All purchasers shall be responsible for independently determining the suitability for the installation and use of the product for the purpose intended.

