



INSTRUCTION
MANUAL

THIS PRODUCT IS FOR INDOOR USE ONLY.
CONSULT A QUALIFIED ELECTRICIAN BEFORE INSTALLATION.
READ AND SAVE THESE INSTRUCTIONS.


SIMPLY DESIGNED

METICULOUSLY HAND-CRAFTED


SOCIALLY RESPONSIBLE

*Thank you for empowering the artisan in you
and for being part of the story.*

PACKAGE CONTENT




B MOUNTING STRAP



C TUBE

SPUN CANOPY



E
CORD
RESTRAIN
SCREW

NIPPLE



WARNING This product is for indoor use only.
It's recommended that you consult a qualified electrician before installation.

HARDWARE CONTENT



G WIRE CONNECTOR
QTY:3

SAFETY INFORMATION

READ AND SAVE THESE INSTRUCTIONS

DANGER

For your protection and safety, carefully read and understand the information provided in this manual completely before attempting to assemble, install or operate this product. Failure to do so could lead to electrical shock, fire or other injuries that could be hazardous or even fatal.

DO NOT connect this fixture to an electrical system that does not provide a means for equipment grounding. Never use a fixture in a two-wire system that is not grounded. Installing a fixture into an electrical system not having a proper grounding means could cause metal parts of the fixture to carry electrical currents if any of the fixture wires, wire connections or splices were to become broken, cut or loose during the mounting or normal operation of the fixture. Under this condition, anyone coming in contact with the fixture would be subject to electrical shock, which could cause serious injury or death.

DO NOT connect the bare or green insulation fixture ground wire to the black (HOT) current-carrying wire or the white (NEUTRAL) house wire. Connection of these wires may cause metal parts of the fixture to carry electrical currents. Under this condition anyone coming in contact with the fixture would be subject to electrical shock, which could cause serious injury or death.

DO NOT damage or cut the wire insulation (covering) during installation of fixture. DO NOT permit wires to contact any surface having a sharp edge. To do so may damage or cut the wire insulation, which could cause serious injury or death from electrical shock.

WARNING

All electrical connections must be in agreement with local codes and ordinances, the National Electric Code (NEC) and ANSI/NFPA 70-1999. Contact your municipal building department or learn about your local codes, permits and /or inspections. To avoid personal injury, the use of gloves may be necessary while handling fixture parts with sharp edges.

DO NOT suspend any fixture by the house wires. A fixture must always be mounted directly to a mounting strap that is first attached to the outlet box. All fixtures must be mounted to an outlet box that is supported by the building structure. Wire connectors will not support the weight of a fixture. Suspending a fixture by the house wires and wire connectors could result in the fixture falling, with the possibility of personal injury and the danger of electrical shock or fire. To reduce the risk of fire, electrical shock or personal injury, wire connectors provided with this light fixture are designed to accept only one 12-gauge house wire and two lead wires from the light fixture. If your house wire is larger than 12-gauge or there is more than one house wire to connect to the corresponding fixture lead wires, consult an electrician for the proper size wire connectors to use.

CAUTION

Turn OFF ELECTRICITY at main fuse box (or circuit breaker box) before beginning installation by removing the fuse (or switching the circuit breaker off).

If you are not sure the lighting system has a grounding means, do not attempt to install this fixture. Contact a qualified, licensed electrician for information regarding the proper grounding methods as required by the local electrical code in your area.

DO NOT use bulbs having a wattage greater than the maximum value stated on the fixture. The use of bulbs with higher wattage than specified will increase temperatures and risk of fire.

If a dimmer control switch is used with this fixture, obtain professional advice to determine the correct type to use as well as the electrical rating required.

Risk of fire - most dwellings built before 1985 have supply wire rated for 140F/60C. Consult a qualified electrician before installation.

PREPARATION

Before beginning assembly of product, make sure all parts are present. Compare parts with packaging contents list and hardware contents list. If any part is missing or damaged, do not attempt to install, operate or assemble product.

(Estimated assembly time: 30-60 minutes)

Tools Required for Assembly (not included): Flathead Screwdriver, Phillips Screwdrivers, Wire Strippers, Pliers, Wire Cutters, Safety Glasses, Stepladder, Electrical Tape.

ASSEMBLY INSTRUCTIONS

1/ Turn off circuit breakers and wall switch to the fixture supply line leads

DANGER: Failure to disconnect power supply prior to installation may result in serious injury or death.

2/ Remove existing fixture and disconnect all electrical wiring.

3/ Attach mounting strap (B) to the outlet box (not included) using the existing screws provided with outlet box.

CAUTION: Make sure the outlet box can support 35 lbs. Hanging weight. Use metal outlet box; plastic outlet boxes are not recommended.

4/ Insert the cord into the canopy.



4a. You may need to cut the excess wire to simplify the wiring. You will need at least 10" of wire to work with.

Prepare wire by stripping 3/4" of insulation from wire ends using wire strippers (not included).

Feed the wire through the tube (C) in the mounting bar (B).

Tie wire into a knot.

4b. Connect bare/green ground house wire from outlet box to bare wire from fixture (A) using wire connector (G). Connect White house wire from outlet box to White wire from fixture (A) using wire connector (G). Connect Black house wire from outlet box to Black wire from fixture (A) using wire connector (G).



NOTE: Screw wire connectors (G) on in a clockwise direction.

WARNING Never connect ground wire to white or black power supply wires.

WARNING To reduce the risk of fire, electrical shock or personal injury, wire connectors (G) provided with this light fixture are designed to accept only one 12-gauge house wire and two leads wires from the light fixture. If your house wire is larger than 12-gauge or there is more than one house wire to connect to the corresponding fixture lead wires, consult an electrician for the proper size wire connectors to use.

5/ Wrap electrical tape around each individual wire connector (G) down to the wire.

WARNING Make sure no bare wire or wire strands are visible after making connections.

6/ Carefully arrange excess wiring and wire connectors (G) within canopy at top of fixture (A).

Align the nipple (F) in the canopy with the tube (C) on the mounting strap (B). Hold the cord still and twist the canopy until it is tight and secure to the mounting strap (B). Make sure the cord is not twisted.

Use (E) the cord restraint screw to tighten the cord in place.

CAUTION: DO NOT over-tighten cord restraint.

7/ Install 1 standard-base bulb (Not included).

Use either a 60-watt max. Incandescent bulb or a 13-watt LED.

CAUTION when replacing bulbs, please allow bulbs and glass shades to cool down before touching.

Restore power and test fixture (A). If lights do not function, please refer to troubleshooting section.

CARE & MAINTENANCE

This product is for indoor use only.

Shut off main power supply. Wipe fixture with only soft cloth.

DO NOT use brass cleaner on the fixture. The fixture has been sealed with a brass seal to prevent it from oxidation.

DO NOT take anything sharp to the fixture, if the varnish comes off the shade might oxidize and will not be replaced or refunded.

TROUBLESHOOTING

WARNING before beginning work, shut off the power supply to avoid electrical shock.

| PROBLEM | POSSIBLE CAUSE | CORRECTIVE ACTION |
|--|---|--|
| Bulb will not light. | a. Bulb us burned out. b. Power is off. c. Faulty connection. | a. Replace light bulb. b. Make sure power supply is ON. c. Check wiring and all connections. |
| Fuse blows out or circuit breaker trips. | a. Crossed wires. b. Power wire is grounding out. | a. Check wiring. b. Check all connections. |

WARRANTY

All our light fixtures are handmade therefore some irregularity in the etching, drilling or seal may occur. We do not refund any purchases for this reason.

We only warrant the light shade and the canopy against oxidation within 1 year from the date of purchase. If within this period the shade or the canopy is found to oxidize, take a copy of the bill of sale as a proof of purchase and the product in its original carton to the place of purchase. The store will, at its option, repair, replace or refund the purchase price to the consumer.

Hardware, cord and bulb are not under warranty.

All costs of installation and removal of the fixture is the responsibility of e consumer. This warranty does not cover fixture becoming defective due to misuse. Accidental damage or improper handling and/or installation and specifically excludes liability for direct, incidental or sub-sequential damages.

As some states do not allow exclusions of limitation on an implied warranty, the above exclusion and limitation may not apply. This warranty gives you specific rights and you also have other rights which may vary from state to state.

IF YOU HAVE ANY QUESTIONS PLEASE CONTACT US AT
DOUNIA@DOUNIAHOME.COM

WWW.DOUNIAHOME.COM



Please consult a qualified electrician before installation.