

RHODES

900

Straight Through Sight Flow Indicators - Stainless Steel

S E R I E S

Figure 933



933

with *Integral Spout*

Materials of Construction

Body	Stainless Steel ASTM A351 CF8M
Covers	Mild Steel BS EN 10025 S355J2G3
Glass	Toughened Soda Lime BS3463
Gaskets	Nickel reinforced graphite
Fasteners	Mild Steel Zinc Plated

Ratings 933 and 934

Pressure Ratings	Max Temperature: 250°C
Full Vacuum to 25	Min Temperature: -30°C

*At ambient temperature. Maximum pressure may be reduced by flange rating or by elevated temperatures. Please request further information if required.

Dimensions 933 and 934

Screwed (mm)	Screwed		Flanged		
	Length (mm)	Weight (Kg)	Flanged (mm)	Length (mm)	Weight (Kg)
15	90	0.9	-	-	-
20	90	0.9	20	140	3.0
25	110	1.7	25	140	3.5
40	130	3.1	40	180	6.5
50	170	5.8	50	220	10.5
			80	260	20.5
			100	310	35.5
			150	406	76

Figure 934



934

with *Flap and Scaleplate*

Materials of Construction

As the 933 but with:

Flap	316 Stainless Steel
Scaleplate	316 Stainless Steel

Flow information (l/min, water)

Size (mm)	Scale Reading on 934									
	1	2	3	4	5	6	7	8	9	10
15/20	3	4	5	7	8	9	10	14	20	25
25	5	7	9	10	13	15	16	20	26	35
40	9	13	17	20	24	27	32	39	57	70
50	13	20	26	31	37	43	52	70	106	150
80	77	91	104	118	132	148	175	206	250	300
100	84	113	138	161	190	240	283	340	500	630

Series end Connections 933 and 934

Screwed BSPT, BSPP, NPT, socket weld, butt weld

Flanged ANSI 150RF, ANSI 300RF, BS10 Table D,E,F, BS4504 PN16, PN25 and PN40

Other end connections available on request

Optional Extras

- All stainless steel construction
- Mica discs
- B7/2H fasteners
- Borosilicate glass to DIN7080
- PTFE gaskets



Declaration of Conformity