



Special Metal Reinforced pressure sensitive contact cement tape for PVC Base

Remur 95 is a patented metal re-enforced double sided installation contact cement adhesive tape that **prevents shrinkage of highly plasticized (up to 35%) extruded PVC base**. Remur 95 is also used for the flash-coving of highly plasticized vinyl flooring. Remur 95 is specifically designed for plasticized vinyl and is not suitable for rubber base or rubber backed carpet base. Remur must be installed on smooth surfaces. Remur 95 is manufactured in Switzerland by Sifloor AG (Uzin)

Applications:

Remur is a metal-reinforced special pressure sensitive dry acrylic adhesive system for the dimensionally stable installation of rigid and flexible PVC base or profiles on smooth substrates <1mm (<1/25") between highs and lows.

Remur allows quick and clean working without solvents. Remur is for interior areas only. Remur meets the TRGS 610.

Suitable skirting:

- Flexible PVC base with smooth backing
- PVC rigid skirting with smooth backing
- PVC cove formers with smooth backing (except: stair nosings)

For common building applications in interior areas. Request application consulting for other materials

Suitable substrates:

- Masonry
- Smooth plaster
- Painted surfaces
- Metal
- Plastics
- Wood
- Concrete
- Ceramics
- Gypsum (primed)
- Leveling compound

Product Sizes:

Item	Tape Width	Application
Remur 95	3.75"	PVC Base 4"
Remur 55	2.16"	For PVC Base 2.5"



Product features & properties:

- Dimensionally stable
- Avoids the use of contact cement or other liquid adhesive
- No prior fitting and priming
- 3 – 5 times faster
- Solvent-free / complies to TRGS 610 (technical regulations for dangerous substances)
- Will not dry out or become brittle
- EMICODE EC 1 PLUS / very low emission PLUS

Technical data:

Packaging: Carton
 Width of rolls: 55mm (2.16") and 95mm (3.75")
 Length of rolls: 50 m (165 ft.)
 Shelf life: min. 2 years
 Color: silver
 Working temperature: min. 18 °C (68°F)
 Open time: none
 Setup time: none
 Subject to use / traffic: immediately after installation
 Welding: immediately after installation

INSTALLATION INSTRUCTIONS

Substrate preparation:

- The substrate must be permanently dry, hard, load-bearing, level, free from grease, dust and silicon, in accordance with the respective national standards (EN, DIN, VOB, OE, SIA).
- Acclimatization: Allow skirting and Remur to acclimate over 24 hours at min. 18°C (68°F) in the room.
- Wallpaper must be cut/removed for the area covered by the base
- Dust binding: Bind dust with a solvent-free primer (e. g. UZIN PE 260).
- PVC cove formers, PVC soft skirting as well as the backing of floor coverings must be free from dust, dirt and grease. Clean well and rub dry with a clean rag.

The following is needed:

Remur, carpet knife, stair iron, rubber mallet, super glue, hot air blower, rag



Tips for processing:

1. Clean the profile backing
2. Put the release paper on the unwinding disk. Do not place rolls on any surface without the round release paper.
3. Apply Remur with the help of the unwinding plate 2 mm (1/10") from the floor covering to the wall and rub firmly.
4. Remove release paper, install PVC skirting (without stretching) and trim if necessary)
5. Tap along the entire PVC skirting with the rubber mallet and reheat with the hot air gun, if necessary.
6. Heat inside/outside corners of the PVC skirting with the hot air gun and pre-shape.
7. Join combinations with super glue, avoid open-joints.



Important notes:

Store Remur indoors on protected dry smooth surface, between 40 and 85°F and without exposure to direct sunlight.

Work Safety and Environmental Protection:

The product requires no particular precautions to ensure safety at work. For reasons of workplace hygiene, it is recommended that the installer you should not eat, drink or smoke while applying this product. Keep out of the reach of children.

Disposal:

Recycle empty cores and the cardboard packaging. Material remnants can be disposed of as household waste.

Performance of Remur 95:

Remur 95 prevents the shrinkage of highly plasticized (up to 35%) extruded PVC base by blocking plasticizer migration from the vinyl profile to the wall.

The installer must follow the generally acknowledged rules of the trade and of technology for the installation of floor covering and the respective applicable standards (ASTM, EN, DIN, VOB, OE, SIA)

The Non-Shrinkage performance warranty does not apply:

- If the product is exposed to unusual exposure to chemicals or to mechanical stress.
- If the product is used or installed differently than stated in the installation instructions.

Remur 95 Limitations of Application:

- Remur may not be used on stairs.
- Remur may not be exposed to moisture.
- Remur is not approved for use in vehicle manufacturing
- Remur may not be used in medical operating rooms, laboratories or manufacturing facilities unless the top of the base or profile is sealed with silicone to prevent the exposure of the adhesive to disinfectants or solvents.