

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

1 Identification

- **Product identifier**
- **Trade name:** MoldWiz® F-57NC Aerosol
- **Application of the substance / the mixture** Release agent
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Axel Plastics Research Laboratories, Inc.
50 Cambridge Drive
Monroe, CT 06468 USA
info@axelplastics.com
- **Information department:** Product safety department
- **Emergency telephone number:**
USA and Canada: 1-800-424-9300 (24 hours)
Outside of USA and Canada: 001-703-527-3887 (24 hours)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS04



GHS07



GHS08

- **Signal word** Danger

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 1)

- **Hazard-determining components of labeling:**

toluene
Solvent naphtha (petroleum), light aliph.
acetone
Distillates (petroleum), hydrotreated light

- **Hazard statements**

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

- **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 0
Reactivity = 3

- **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 0
Reactivity = 3

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 2)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Component Information:**

811-97-2	1,1,1,2-Tetrafluorethane	50 – 75%
115-10-6	dimethyl ether	25 – 50%
1330-20-7	xylene	≥ 2.5 – < 10%
108-88-3	toluene	≥ 0.1 – ≤ 2.5%
64742-89-8	Solvent naphtha (petroleum), light aliph.	≤ 2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	≤ 2.5%
67-64-1	acetone	≤ 2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 3)

Ensure adequate ventilation

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

· **Environmental precautions:**

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Small spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillage into an effluent treatment plant or proceed as follow. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: See Section 1 for emergency contact information and Section 13 for waste disposal.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Store in cool, dry place in tightly closed receptacles.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation.

Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50C, i.e. electric lights.

Do not pierce or burn, even after use. Keep ignition sources away-DO NOT SMOKE.

· **Conditions for safe storage, including any incompatibilities**

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Avoid freezing.

Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 4)

- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
Aerosols should be –
 - (i) Stored under cover and protected from exposure to the weather and direct sunlight;
 - (ii) kept at least 3 m from any source of heat or ignition; and
 - (iii) stored in a manner that reduces the risk of any damage to the aerosol containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

811-97-2 1,1,1,2-Tetrafluorethane

WEEL	Long-term value: 1000 ppm
------	---------------------------

115-10-6 dimethyl ether

WEEL	Long-term value: 1000 ppm
------	---------------------------

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

67-64-1 acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm BEI

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 5)

· Ingredients with biological limit values:
1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

67-64-1 acetone

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

If a risk assessment indicates engineering controls are not sufficient to protect worker health or comply with relevant legislation, use an approved respirator. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Respirators to be considered for this material include: Half-face filter respirator with Type A filter material.

For the European Union, refer to Standardization (CEN) standards EN 136, 140 and 405 for respirator masks and EN 149 and 143 for filter recommendations. In the United States of America, refer to OSHA Respiratory Protection Standard, 29 CFR 1910.134 and ANSI Z88.2 for respiratory selection, use and maintenance.

· **Protection of hands:**



The gloves listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Protective gloves are recommended to protect against contact with product. Polyvinyl alcohol, Viton, Safety 4H, Teflon. When splashing is possible, full chemically resistant protective clothing and boots are required. The following materials are acceptable for use as protective clothing: Polyvinyl alcohol (PVA), Viton, Teflon. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Remove contaminated clothing and wash before reuse. For non-fire emergencies, positive pressure SCBA and structural firefighter's protective clothing will provide only limited protection.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 6)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Chemical safety glasses with side shields, goggles or face shield.

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Aerosol

Color: Whitish

- **Odor:** Mild

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Not applicable, as aerosol.

- **Flash Point (C.O.C.):** Not applicable, as aerosol.

- **Percentage Volatile** 98.8 %

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Not determined.

- **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- **Oxidizing properties** Not determined.

- **Vapor pressure at 20 °C (68 °F):** 5,716 hPa (4,287.4 mm Hg)

- **Density:** Not determined.

- **Relative density** 1.230

- **Vapor density** Not determined.

- **Evaporation rate** Not applicable.

- **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 7)

- | | |
|----------------------------|--|
| · Viscosity: | < 50 cps @ 25C |
| · Dynamic: | Not determined. |
| · Kinematic: | Not determined. |
| · VOC content: | Not determined. |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** The product is stable under recommended storage conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	> 4,909 mg/kg
Dermal	LD50	> 3,031 mg/kg
Inhalative	LC50/4 h	> 19 mg/l

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	> 6,800 mg/kg (rat)
Dermal	LD50	> 3,400 mg/kg (rab)
Inhalative	LC50/4 h	> 10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

1330-20-7	xylene	3
108-88-3	toluene	3

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 8)

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **IARC Monographs**

- Group 1: Carcinogenic to humans
- Group 2A: Probably carcinogenic to humans
- Group 2B: Possibly carcinogenic to humans
- Group 3: Not classifiable as to its carcinogenicity to humans
- Group 4: Probably not carcinogenic to humans

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 - Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 - The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
 - The classification of the product may meet the criteria for a hazardous waste.
- **Uncleaned packagings:**
- **Recommendation:**
 - The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
 - This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

US
(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS


Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 9)

14 Transport information

<ul style="list-style-type: none"> · UN-Number · IMDG 	UN1950
<ul style="list-style-type: none"> · UN proper shipping name · IMDG 	AEROSOLS
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	
<ul style="list-style-type: none"> · Label 	ORM-D
<ul style="list-style-type: none"> · IMDG 	
<div style="text-align: center;">  </div>	
<ul style="list-style-type: none"> · Class 	2.2
<ul style="list-style-type: none"> · IATA 	
<ul style="list-style-type: none"> · Class · Label 	9 Miscellaneous dangerous substances and articles ID-8000
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	not regulated
<ul style="list-style-type: none"> · Environmental hazards: 	Not applicable.
<ul style="list-style-type: none"> · Special precautions for user · EMS Number: · Stowage Code 	Not applicable. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
<ul style="list-style-type: none"> · Segregation Code 	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL/73/78 and the IBC Code 	Not applicable.

(Contd. on page 11)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 10)

· **Transport/Additional information:**

· **IMDG**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **IATA**

· **Remarks:**

ID8000

· **UN "Model Regulation":**

not regulated

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
108-88-3	toluene
95-63-6	1,2,4-trimethylbenzene
67-63-0	propan-2-ol

· **TSCA (Toxic Substances Control Act) (Substances not listed):**

All ingredients are listed.

· **TSCA new (21st Century Act) (Substances not listed)**

64742-89-8	Solvent naphtha (petroleum), light aliph.
64742-95-6	Solvent naphtha (petroleum), light arom.

· **Proposition 65**

· **Chemicals known to cause cancer:**

98-82-8	cumene
---------	--------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3	toluene
----------	---------

· **US State Regulations**

· **Connecticut - Hazardous Air Pollutants - HLVs (30 min)**

None of the ingredients is listed.

· **Connecticut - Hazardous Air Pollutants - HLVs (8 hr)**

None of the ingredients is listed.

· **Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)**

None of the ingredients is listed.

· **Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations**

None of the ingredients is listed.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 11)

· Occupational Exposure Limits - TWAs

None of the ingredients is listed.

· Michigan - Occupational Exposure Limits - Skin Designations

None of the ingredients is listed.

· Michigan - Occupational Exposure Limits - TWAs

None of the ingredients is listed.

· Minnesota - Hazardous Substance List

None of the ingredients is listed.

· Minnesota - Permissible Exposure Limits - Skin Designations

None of the ingredients is listed.

· Minnesota - Permissible Exposure Limits - TWAs

None of the ingredients is listed.

· New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour

None of the ingredients is listed.

· New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual

None of the ingredients is listed.

· New York - Occupational Exposure Limits - Skin Designations

None of the ingredients is listed.

· New York - Occupational Exposure Limits - TWAs

None of the ingredients is listed.

· North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour

None of the ingredients is listed.

· North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour

None of the ingredients is listed.

· Oregon - Permissible Exposure Limits - TWAs

None of the ingredients is listed.

· Tennessee - Occupational Exposure Limits - Skin Designations

None of the ingredients is listed.

· Tennessee - Occupational Exposure Limits - TWAs

None of the ingredients is listed.

· Texas - Effects Screening Levels - Long Term

None of the ingredients is listed.

· Texas - Effects Screening Levels - Short Term

None of the ingredients is listed.

· Vermont - Permissible Exposure Limits - Skin Designations

None of the ingredients is listed.

· Vermont - Permissible Exposure Limits - TWAs

None of the ingredients is listed.

· Washington - Permissible Exposure Limits - Skin Designations

None of the ingredients is listed.

· Washington - Permissible Exposure Limits - STELs

None of the ingredients is listed.

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 12)

· **Washington - Permissible Exposure Limits - TWAs**

None of the ingredients is listed.

· **Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet**

None of the ingredients is listed.

· **Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet**

None of the ingredients is listed.

· **Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater**

None of the ingredients is listed.

· **Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
108-88-3	toluene	II
67-64-1	acetone	I

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **EPA Carcinogen Category Key**

EPA 2005 Guidelines:

CaH - Carcinogenic to humans.

L - Likely to be carcinogenic to humans.

SC - Suggestive evidence of carcinogenic potential.

II - Inadequate information to assess carcinogenic potential.

NL - Not likely to be carcinogenic to humans.

EPA 1999 Guidelines:

CaH - Carcinogenic to humans.

L - Likely to be carcinogenic to humans.

S - Suggestive evidence of carcinogenicity, but not sufficient to assess human carcinogenic potential.

I - Data are inadequate for an assessment of human carcinogenic potential.

NL - Not likely to be carcinogenic to humans.

EPA 1996 Guidelines:

K/L - Known/likely human carcinogen.

CBD - Carcinogenic potential cannot be determined.

NL - Not likely to be carcinogenic to humans.

EPA 1986 Guidelines:

A - Human carcinogen

B1 - Probable human carcinogen - based on limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in animals.

B2 - Probable human carcinogen - based on sufficient evidence of carcinogenicity in animals.

C - Possible human carcinogen.

D - Not classifiable as to human carcinogenicity.

E - Evidence of non-carcinogenicity for humans.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 14)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 13)

· Hazard pictograms

· Signal word Danger

· Hazard-determining components of labeling:

toluene
Solvent naphtha (petroleum), light aliph.
acetone
Distillates (petroleum), hydrotreated light

· Hazard statements

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The components of this product are listed on the South Korean (KECI) inventory.
The components of this product are listed on the USA (TSCA) inventory.
The components of this product are listed on the Canadian (DSL) inventory.
The components of this product are listed on the European (EINECS) inventory.
The components of this product are listed on the Australia (AICS) inventory.

(Contd. on page 15)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/28/2018

Reviewed on 08/28/2018

Trade name: MoldWiz® F-57NC Aerosol

(Contd. of page 14)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Disclaimer: This data is offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review recommendations in the specific context of the intended use and determine whether they are appropriate.

· **Procedure used to derive the classification** Calculation method.

· **Contact:** info@axelplastics.com

· **Date of preparation / last revision** 08/28/2018 / 10

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure – Compressed gas

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· *** Data compared to the previous version altered.**