

SAFETY DATA SHEET

1. Product Identification

Product name G2 Glue Resin, Part A

SDS Number F1110A00

Product type Epoxy polymer mixture.

Recommended use of the chemical and

restrictions on use

Directed at, but not limited to, the bonding of similar and dissimilar substrates.

Restrictions None known.

Manufacturer/Supplier information

Company nameSYSTEM THREE RESINS, INC.Address3500 W. Valley Hwy, Suite

Suite 105

Auburn, WA 98991-2436

United States

Telephone 1-253-333-8118

Website www.systemthree.com

Email support-08@systemthree.com

Emergency Contact CHEMTREC (U.S. and CANADA) 1-800-424-9300 CHEMTREC (Outside the U.S.) 1-703-527-0585

2. Hazard(s) Identification

Classification of substance or WARNING.

mixture/Signal Word Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2

Skin Sensitizer – Category 1 Reproductive Toxicity – Category 2

Specific Target Organ Toxicity (Single Exposure) [Respiratory tract irritation] –

Category 3

Acute Aquatic Toxicity – Category 2 Chronic Aquatic Toxicity – Category 2

GHS Label Elements

Hazard Pictograms







Hazard Statements/Classification of

H315 Causes skin irritation.

substance or mixture H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.H355 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects

Precautionary statements

<u>Precautionary Statements</u> P280 Wear protective gloves. Wear eye or face protection.

Prevention P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and

understood.

P261 Avoid breathing vapors.

Response P308 + P313 If exposed or concerned: Get medical attention.

Storage P401 Store above 32 °F / 0 °C

Disposal P501 Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Hazards not otherwise classified (HNOC) None Available.

3. Composition/Information On Ingredients

Chemical Name	CAS Number	Content (%)
Diglycidyl Ether of Bisphenol A	25068-38-6	80 – 90 %
Benzyl Alcohol	100-51-6	6-10 %
Para-tert-Butylphenol	98-54-4	6-10%
Diglycidyl Ether of Bisphenol F	28064-14-4	6-10%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

4. First-Aid Measures

Skin contact Remove contaminated clothing and shoes and wipe excess off skin. Flush skin

with water. Follow by washing in soap and water. If irritation occurs, seek medical attention. Do not reuse clothing until cleaned. Contaminated leather

articles (shoes) cannot be decontaminated and should be destroyed.

Eye contact Flush with water for 15 minutes holding eye lids open. Seek medical

attention.

Ingestion Do not give liquids if victim is unconscious of very drowsy. Otherwise, give no

more than 2 glasses of water and induce vomiting by giving 2 tablespoons syrup of ipecac (1 tablespoon and 1 glass of water for child). If ipecac is unavailable, give 2 glasses of water and induce vomiting by touching finger to back of throat. Keep head below hips while vomiting. Get medical attention.

Inhalation Remove victim to fresh air and provide oxygen if breathing is difficult. Give

artificial respiration if not breathing. Get medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physicianBurns. Irritation. Pre-existing skin conditions may be aggravated by prolonged

or repeated contact. Persons with sensitive airways (e.g., asthmatics) may be

sensitive to vapors.

Specific treatments Treat symptoms as they appear.

5. Fire-Fighting Measures

Suitable extinguishing media Foam, carbon dioxide, dry chemical, water fog.

Unsuitable extinguishing mediaNone known.

Specific hazards arising from the chemical Potential skin irritation.

Hazardous decomposition products None known.

Special protective actions for fire-fighters When fighting chemical fires, wear full protective equipment with self-

contained breathing apparatus. Water spray may be used to cool fire-exposed

containers. Toxic fumes may be evolved when this substance is burned.

Special protective equipment for fire-

fighters

Further information

Full fire suit and self-contained breathing apparatus.

Water spray may be used to cool fire-exposed containers. Toxic fumes may be

evolved when this substance is burned.

Epoxy in mass can create exotherm.

6. Accidental Release Measures

Personal precautions Wear proper personal protective equipment (PPE). Avoid direct contact with

material. Proper PPE includes: disposable gloves, eye protection and skin

protection.

Emergency procedures If material is spilled, avoid contact with material. Persons not wearing

appropriate protective equipment should leave the area of the spill until

cleanup is complete.

Methods and materials for

containment/cleanup

Stop spill at source, dike area to prevent spreading, pump liquid to salvage tank or drum. Remaining liquid may be taken up on clay, diatomaceous earth,

sawdust or other absorbent, and shoveled into disposal container.

Environmental precautions Skin sensitizer, harmful to aquatic life.

7. Handling and Storage

Precautions for safe handling Always wear protective, disposable gloves when handling epoxy products to

prevent exposure.

Precautions/Recommendations for

safe/proper storage

Store epoxy products in temperature stable environment, out of the reach of pets or children. Securely fasten container lids and tops, and prevent products

from sitting and below freezing temperatures.

8. Exposure Controls/Personal Protection

None established. **Occupational Exposure Limits**

Appropriate engineering controls If user operations generate dust, fumes, gas, vapor or mist, use process

> enclosures, local ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory

limits.

Use appropriate containment to avoid environmental contamination. Do not **Environmental exposure controls**

allow spill to enter sewers or waterways.

Individual protection measures/Personal

protective equipment

Eye/face protection Splash proof goggles or safety glasses with side shields are recommended.

Always wear eye protection when sanding cured epoxy to avoid dust in eyes.

Hand protection Always wear impervious gloves, neoprene, vinyl or rubber.

Skin protection Wear clean, body-covering clothing to avoid skin contact.

Respiratory protection Use a NIOSH-approved respiratory device when sanding cured epoxy to

prevent dust in lungs.

Special instructions for protection and hygiene

Wear gloves at all times when handling product, avoid direct contact with skin. When finished using product, dispose of gloves properly and wash hands with warm, soapy water.

9. Physical and Chemical Properties

Chemical family Epoxy Resin

Appearance Clear viscous liquid

Physical State Epoxy polymer mixture

Form Liquid

Color Water clear
Odor Phenolic odor

Density (Specific Gravity) 9.5 lb/gal (1.14)

Viscosity 2000-2200 cps @ 25°C

pH N/A

Melting point/freezing pointData not availableInitial boiling point and boiling rangeData not available

Flash point >300°F, Pensky-Martens Closed Cup

Evaporation rate Slower than ether
Flammability (solid, gas) Data not available

Upper/lower flammability limit (by volume)

Upper flammability limit (by volume) N/A

Lower flammability limit (by volume) N/A

Material VOC None

Vapor density

Relative density

Not determined

Solubility in water

Partition coefficient: n-octanol/water

Auto-ignition temperature

Data not available

300°C (572.00°F)

Decomposition temperature

Not available

10.Stability and Reactivity

Reactivity None
Chemical Stability Stable

Possibility of hazardous reactions Hazardous polymerization will not occur.

Conditions to avoid Epoxy resins and epoxy resin hardeners can react with each other producing

heat. They should not be mixed with each other under uncontrolled conditions or in large mass as the ensuing exotherm may result in heat and

smoke, resulting in hazardous decomposition products.

Incompatible materials Strong oxidizing agents, Lewis and mineral acids.

Hazardous decomposition productsOxides of carbon, aldehydes, acids.

Other hazards None known.

11. Toxicological Information

Acute Health Hazard (components)

No comprehensive data (ingestion, inhalation, dermal) on mixture (product).

Component	Result	Species	Dose	Exposure
Diglycidyl Ether of	LD50 Oral	Rat	11,400 mg/kg	-
Bisphenol A	LD50 Dermal	Rat	2,000 mg/kg	-
Benzyl Alcohol	LD50 Oral	Rat	1620 mg/kg	-
	LC50 Inhalation	Rat	>4178 mg/m3	4 hrs, aerosol
Para-tert-Butylphenol	LD50 Oral	Rat	>2000 mg/kg	-
	LC50 Inhalation	Rat	5.6 mg/l	-

Irritation/Corrosion (components)

No information on product itself.

Component	Result	Species	Test	Exposure
Diglycidyl Ether of Bisphenol A	Skin – Erythema/Eschar 404 Acute Dermal Irritation/Corrosion	Rabbit	1.5 – 2	-
	Skin – Edema 404 Acute Dermal Irritation/Corrosion	Rabbit	1.0 -1.5	-
	Eyes – 405 Acute Eye Irritation/Corrosion	Rabbit	0	-
	Eyes – Redness of the conjunctivae	Rabbit	0.7	-
	Skin – Moderate irritant	Rabbit		24 hrs
	Eyes – Mild irritant	Rabbit		-
Benzyl Alcohol	Eyes – 405 OECD Irritant	Rabbit		-
Para-tert-Butylphenol	Skin – Moderate irritant	Rabbit		4 hrs
	Eyes – Severe eye irritant	Rabbit		24 hrs

SensitizationNo information on product itself.MutagenicityNo information on product itself.CarcinogenicityNo information on product itself.Reproductive ToxicityNo information on product itself.TeratogenicityNo information on product itself.Specific target organ toxicity (single)No information on product itself.

<u>exposure</u>)

Component	Category	Route of exposure	Target organs
Diglycidyl Ether of Bisphenol A	Category 3		Respiratory tract irritation
Diglycidyl Ether of Bisphenol F	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated

exposure)

No information on product itself.

<u>Aspiration hazard</u> No information on product itself.

Potential acute health effects

Eye ContactCauses serious eye irritation.InhalationMay cause respiratory irritation.

Skin Contact Causes skin irritation. May cause an allergic skin reaction.

Ingestion Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical

and toxicological characteristics

Eye Contact Adverse symptoms may include the following:

Pain Watering Redness

Inhalation Adverse symptoms may include the following:

Respiratory tract irritation

Coughing

Skin Contact Adverse symptoms may include the following:

Irritation Redness

Ingestion No specific data.

<u>Delayed and immediate effects and also</u> <u>chronic effects from short and long term</u>

<u>exposure</u>

Potential chronic health effects

General Once sensitized, a severe allergic reaction may occur when subsequently

exposed to very low levels.

CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates (ATEmix)

Route	ATE value
Oral	8074.3 mg/kg
Dermal	2020.2 mg/kg
Inhalation (vapors)	4178 mg/l

12. Ecological Information

Ecotoxicity

Component	Result	Species	Exposure
Diglycidyl Ether of Bisphenol A	Acute LC50 1.3 mg/l – 203 Fish, Acute Toxicity Test	Fish — Fish	96 h
	Acute EC50 2.1 mg/l – 202 Daphnia sp. Acute Immobilization Test and Reproduction Test	Aquatic invertebrates. Water flea	48 h
	Acute NOEC 0.3 mg/l – 211 Daphnia Magna Reproduction Test	Aquatic invertebrates. Water flea	21 d
	Acute LC50 > 11 mg/l	Aquatic plants – Algae	72 h
Benzyl Alcohol	Acute LC50 460 mg/l	Fish	96 h

	Acute EC50 230 mg/l	Invertebrates	48 h
	Chronic NOEC 310 mg/l	Algae	72 h
Para-tert-Butylphenol	Acute LC50 – 5.14 mg/l	Fish	96 h
	Acute EC50 – 4.8 mg/l	Daphnia	48 h

Persistence and degradability

No information on product itself.

Bioaccumulative Potential

No information on product itself.

Component	LogPow	BCF	Potential
Diglycidyl Ether of Bisphenol A	2.64 – 3.78	3 – 31 31.00	Low
Diglycidyl Ether of Bisphenol F	3	-	low
Benzyl Alcohol	1.05	1.37 (calculated)	-

Mobility in Soil

Soil/water partition coefficient (KOC)No information on product itself.

Other adverse effects No known significant effects or critical hazards.

13. Disposal Considerations

Waste from residues/ unused productsProduct should not be allowed to enter drains, water courses or the soil;

dispose of this material and its containers in a safe way. Contact supplier if

guidance is required.

Contaminated packaging Dispose of container and unused contents in accordance with federal, state

and local requirements.

14. Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International Transport Regulations

Regulatory information	UN/NA number	Proper Shipping Name	Classes/*PG	Additional Information
DOT		Not regulated		
TDG		Not regulated		
IMO/IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (LIQUID EPOXY RESIN)	Class 9 III	Marine pollutant
IATA (Cargo)	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (LIQUID EPOXY RESIN)	Class 9 III	Marine pollutant
*PG: Packing group		·		

Special precautions for user:

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to

do in the event of an accident or spillage.

15. Regulatory Information

UNITED STATES

United States – TSCA 5(a)2 – Final significant new use rules: Not Listed.
United States – TSCA 5(a)2 – Proposed significant new use rules: Not Listed.

United States – TSCA 5(e) – Substance consent order: Not listed.

California Prop. 65

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer. WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient Name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Oxirane, 2-(phenoxymethyl)-	Yes	No	5 μg/day	No
Oxirane, 2-(chloromethyl)-	Yes	Yes	9 μg/day	No

EPA SARA 302 Extremely Hazardous

Substances

None required.

EPA SARA 302/304/311/312 Hazardous

Chemicals

Acute Health Hazard.

United States inventory (TSCA 8b)

All components are listed or exempted.

CANADA

WHMIS (Canada) Class D-2B: Material causing other toxic effects (Toxic).

Canadian NPRINone required.CEPA Toxic substancesNone required.

INTERNATIONAL REGULATIONS

International Lists Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted.

Korea inventory: All components are listed or exempted.

Japan inventory: All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

New Zealand inventory (NZIoC): All components are listed or exempted. **Philippines inventory (PICCS):** All components are listed or exempted.

Taiwan inventory (CSNN): All components are listed or exempted.

16. Other Information, Including Date of Preparation or Last Revision

HMIS Rating



Date of Preparation November 23, 2016

Date of Last Revision

Revision # 1.0

More Information 1-253-333-8118

Prepared by J. Bartlett, System Three Resins Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. System Three assumes no responsibility for injury from the use of the product described herein.



SAFETY DATA SHEET

1. Product Identification

Product name G2 Glue Hardener, Part B

SDS Number F1110B00

Product type Epoxy polymer mixture.

Recommended use of the chemical and

restrictions on use

Directed at, but not limited to, the bonding of similar and dissimilar substrates.

Restrictions None known.

Manufacturer/Supplier information

Company name SYSTEM THREE RESINS, INC.

Address 3500 W. Valley Hwy, Suite

Suite 105

Auburn, WA 98991-2436

United States

Telephone 1-253-333-8118

Website www.systemthree.com

Email support-08@systemthree.com

Emergency Contact CHEMTREC (U.S. and CANADA) 1-800-424-9300

CHEMTREC (Outside the U.S.) 1-703-527-0585

2. Hazard(s) Identification

Classification of substance or mixture/Signal Word

DANGER.

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2

Respiratory Sensitization – Category 1 Skin Sensitization – Category 1 Reproductive Toxicity – Category 2

Specific Target Organ Toxicity (Single Exposure) [eyes] – Category 1

Specific Target Organ Toxicity (Single Exposure) [Respiratory tract irritation] -

Category 3

Specific Target Organ Toxicity (Repeated Exposure) [skin, respiratory tract,

kidneys, liver] - Category 1

GHS Label Elements
Hazard Pictograms





Hazard Statements/Classification of substance or mixture

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs: (eyes)

H372 Causes damage to organs through prolonged or repeated exposure:

(skin, respiratory tract, kidneys, liver)

Precautionary statements

<u>Precautionary Statements</u> P201 Obtain special instructions before use.

Prevention P202 Do not handle until all safety precautions have been read and

understood.

P260 Do not breathe vapor.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P271 Use only outdoors or in well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the

workplace.

P280 Wear protective gloves. Wear eye or face protection.

P285 In case of inadequate ventilation wear respiratory protection.

Response P314 Get medical attention if you feel unwell.

P308 + P311 If exposed or concerned: Call a POISON CENTER or physician.

Storage P405 Store locked up.

Disposal P501 Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Hazards not otherwise classified (HNOC)

None Available.

3. Composition/Information On Ingredients

Chemical Name	CAS Number	Content (%)
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	68410-23-1	90 – 100%
with polyethylenepolyanines		
Triethylenetetramine	112-24-3	7 – 10%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

4. First-Aid Measures

Skin contact Wash with plenty of soap and water. Remove contaminated clothing and

shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse.

Eye contact Flush with water for 15 minutes holding eye lids open. Check for and remove

any contact lenses. Get medical attention. If necessary, call a poison center or

physician.

Ingestion Wash out mouth with water. Remove dentures if any. Remove victim to fresh

air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person in conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention

immediately. Maintain an open airway. Loosen tight clothing such as collar,

tie, belt, or waistband.

Inhalation Remove victim to fresh air and provide oxygen if breathing is difficult. Give

artificial respiration if not breathing. Get medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician In case of inhalation of decomposition products in a fire, symptoms may be

delayed. The exposed person may need to be kept under medical surveillance

for 48 hours.

Specific treatments Treat symptoms as they appear.

5. Fire-Fighting Measures

Suitable extinguishing media Foam, carbon dioxide, dry chemical, water fog.

Unsuitable extinguishing media None known.

Specific hazards arising from the chemical In a fire or if heated, a pressure increase will occur and the container may

burst.

Hazardous decomposition products
Special protective actions for fire-fighters

Carbon oxides, nitrogen oxides.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk

or without suitable training.

Special protective equipment for fire-

fighters

Further information

Full fire suit and self-contained breathing apparatus.

None known.

6. Accidental Release Measures

Personal precautionsWear proper personal protective equipment (PPE). Avoid direct contact with

material. Proper PPE includes: disposable gloves, eye protection and skin

protection.

Emergency procedures If material is spilled, avoid contact with material. Persons not wearing

appropriate protective equipment should leave the area of the spill until

cleanup is complete.

Methods and materials for

containment/cleanup

Stop spill at source, dike area to prevent spreading, pump liquid to salvage tank or drum. Remaining liquid may be taken up on clay, diatomaceous earth,

sawdust or other absorbent, and shoveled into disposal container.

Environmental precautions Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform relevant authorities if the product has

caused environmental pollution (sewers, waterways, soil or air).

7. Handling and Storage

Precautions for safe handling Always wear protective, disposable gloves when handling epoxy products to

prevent exposure. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is

inadequate.

Precautions/Recommendations for

safe/proper storage

Store epoxy products in temperature stable environment, out of the reach of pets or children. Securely fasten container lids and tops, and prevent products

from sitting and below freezing temperatures.

8. Exposure Controls/Personal Protection

Occupational Exposure Limits

Triethylenetetramine
AIHA WEEL (1999-01-01)
Time Weighted Average (TWA) 1 ppm
NIOSH REL (2005-09-30)

Appropriate engineering controls If user operations generate dust, fumes, gas, vapor or mist, use process

enclosures, local ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory

limits.

Environmental exposure controlsUse appropriate containment to avoid environmental contamination. Do not

allow spill to enter sewers or waterways.

Individual protection measures/Personal

protective equipment

Eye/face protection Splash proof goggles or safety glasses with side shields are recommended.

Always wear eye protection when sanding cured epoxy to avoid dust in eyes.

Hand protection Always wear impervious gloves, neoprene, vinyl or rubber. **Skin protection** Wear clean, body-covering clothing to avoid skin contact.

Respiratory protectionUse a NIOSH-approved respiratory device when sanding cured epoxy to

prevent dust in lungs.

Special instructions for protection and

hygiene

Wear gloves at all times when handling product, avoid direct contact with skin. When finished using product, dispose of gloves properly and wash hands

with warm, soapy water.

9. Physical and Chemical Properties

Chemical family Polyamide curing agent

Appearance Viscous liquid

Physical State Epoxy polymer mixture

Form Liquid

Color Reddish-brown
Odor Characteristic

 Density
 970 kg/m3 (8.09 lb/gal)

 Viscosity
 13,000 CPS @ 25°C (77°F)

pH N/A

Melting point/freezing pointData not availableInitial boiling point and boiling rangeData not available

Flash point Open cup: >110°C (230°F), ASTM D 4206

Evaporation rate Data not available
Flammability (solid, gas) Data not available

Upper/lower flammability limit (by volume)

Upper flammability limit (by volume) N/A

Lower flammability limit (by volume) N/A

Material VOC None

Vapor density 1 [Air=1]

Relative density Not determined

Solubility in water Slightly

Partition coefficient: n-octanol/waterData not availableAuto-ignition temperatureData not availableDecomposition temperatureData not available

10. Stability and Reactivity

Reactivity Stable under normal conditions.

Chemical Stability Stable

Possibility of hazardous reactions Hazardous polymerization will not occur.

Conditions to avoid Avoid exposure – obtain special instructions before use. Avoid all possible

sources of ignition (spark or flame).

Incompatible materials Strong oxidizing agents.

Hazardous decomposition productsUnder normal conditions or storage and use, hazardous decomposition

products should not be produced.

Other hazards Heating this substance above 300°F in the presence of air may cause slow

oxidative decomposition; above 500°F polymerization may occur. Some combinations of resins and curing agents can produce exothermic reactions which in large masses can cause runaway polymerization and charring of the reactants. Fumes and vapors from the thermal and chemical decompositions

vary widely in composition and toxicity.

11. Toxicological Information

Acute Health Hazard (components)

No comprehensive data (ingestion, inhalation, dermal) on mixture (product).

Component	Result	Species	Dose	Exposure
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	LD50 Oral	Rat	>5,000 mg/kg	-
Triethylenetetramine	LD50 Oral	Rat	2,500 mg/kg	-

Irritation/Corrosion (components)

No information on product itself.

Component	Result	Species	Score	Exposure
Triethylenetetramine	Eyes – Moderate irritant	Rabbit		24 hrs
	Skin – Severe irritant	Rabbit		24 hrs
	Eyes – Severe irritant	Rabbit		

SensitizationNo information on product itself.MutagenicityNo information on product itself.

<u>Carcinogenicity</u> No information on product itself.

Reproductive Toxicity No information on product itself.

<u>Teratogenicity</u> No information on product itself.

Specific target organ toxicity (single exposure)

No information on product itself.

Component	Category	Route of exposure	Target organs
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	Category 3		Respiratory tract irritation
Triethylenetetramine	Category 1		Eyes

Specific target organ toxicity (repeated

No information on product itself.

exposure)

Component	Category	Route of exposure	Target organs
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	Category 2		Skin
Triethylenetetramine	Category 1 Category 2		Respiratory tract Skin
			Liver Kidneys

Aspiration hazard

No information on product itself.

Potential acute health effects

Eye Contact Causes serious eye irritation.

Inhalation May cause respiratory irritation. May cause allergy or asthma symptoms or

breathing difficulties if inhaled. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin Contact Causes skin irritation. May cause an allergic skin reaction.

Ingestion Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical

and toxicological characteristics

Eye Contact Adverse symptoms may include the following:

Pain Watering Redness

Inhalation Adverse symptoms may include the following:

Respiratory tract irritation

Coughing

Wheezing and breathing difficulties

Asthma

Reduced fetal weight Increase in fetal deaths Skeletal malformations

Skin Contact Adverse symptoms may include the following:

Irritation Redness

Reduced fetal weight Increase in fetal deaths Skeletal malformations

Ingestion Adverse symptoms may include the following:

Reduced fetal weight Increase in fetal deaths Skeletal malformations

<u>Delayed and immediate effects and also</u> <u>chronic effects from short and long term</u> <u>exposure</u>

Potential chronic health effects

General Causes damage to organs through prolonged or repeated exposure: Once

sensitized, a severe allergic reaction may occur when subsequently exposed

to very low levels.

Carcinogenicity No known significant effects or critical hazards.

Mutagenicity No known significant effects or critical hazards.

Teratogenicity Suspected of damaging the unborn child.

Developmental effects No known significant effects or critical hazards.

Fertility effects Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates (ATEmix) Not available.

Route	ATE value
Oral	N/A
Dermal	N/A
Inhalation (vapors)	N/A

12. Ecological Information

Ecotoxicity

Component	Result	Species	Exposure
Triethylenetetramine	Acute LC50 – 33,900 μg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 – 3,700 μg/l Fresh water	Aquatic plants – Green algae	96 h

<u>Persistence and degradability</u> No information on product itself.

<u>Bioaccumulative Potential</u> No information on product itself.

Component	LogPow	BCF	Potential
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines		492.00	Low
Triethylenetetramine	-1.661.4	-	low

Mobility in Soil

Soil/water partition coefficient (KOC)No information on product itself.

Other adverse effects No known significant effects or critical hazards.

13. Disposal Considerations

Waste from residues/ unused products

The generation of waste should be avoided or minimized wherever possible. Product should not be allowed to enter drains, water courses or the soil; dispose of this material and its containers in a safe way. Contact supplier if guidance is required.

and local requirements.

14. Transport Information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International Transport Regulations

Regulatory information	UN/NA number	Proper Shipping Name	Classes/*PG	Additional Information
DOT		Not regulated		
TDG		Not regulated		
IMO/IMDG		Not regulated		
IATA (Cargo)		Not regulated		

*PG: Packing group

Special precautions for user: Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to

do in the event of an accident or spillage.

15. Regulatory Information

UNITED STATES

U.S. Federal Regulations United States – TSCA 12(b) – Chemical export notification: None Required.

United States – TSCA 5(a)2 – Final significant new use rules: Not Listed.
United States – TSCA 5(a)2 – Proposed significant new use rules: Not Listed.

United States – TSCA 5(e) – Substance consent order: Not listed.

California Prop. 65 None required.

EPA SARA 302 Extremely Hazardous None required.

Substances

EPA SARA 302/304/311/312 Hazardous None required.

Chemicals

United States inventory (TSCA 8b) All components are listed or exempted.

CANADA

WHMIS (Canada) Class D-2B: Material causing other toxic effects (Toxic).

Canadian NPRINone required.CEPA Toxic substancesNone required.

INTERNATIONAL REGULATIONS

International Lists Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted.

Korea inventory: All components are listed or exempted.

Japan inventory: All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

New Zealand inventory (NZIoC): All components are listed or exempted. Philippines inventory (PICCS): All components are listed or exempted. Taiwan inventory (CSNN): All components are listed or exempted.

16. Other Information, Including Date of Preparation or Last Revision

HMIS Rating



Date of Preparation December 21, 2016

Date of Last Revision

Revision # 1.0

More Information 1-253-333-8118

Prepared byN. Kim, System Three Resins Inc.

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. System Three assumes no responsibility for injury from the use of the product described herein.