

SMART IAQ Sensor Product specs

EnviroKlenz SMART IAQ Sensor

- Power Requirements: DC 12V/2A, or Standard 120V
- Wireless Connection: Bluetooth, 2.4 GHz/5GHz, WIFI
- Dimensions, per sensor: 5in(L) * 2in(W) * 3in(H)
- · Weight: 300g
- Treatment size: 2 sensors for 20-40ft vehicles, 3 sensors for 50ft+ vehicles
- Measures: PM2.5, PM1, TVOCs, CO2, CO, Temperature, Humidity
- Integrates With: EnviroKlenz SMART Mount™ filtration system





EnviroKlenz SMART Science™ Dashboard

- Offers real-time and historical data readings of up to 7 different in-room conditions, manual control of SMART ecosystem, data reporting capabilities for benchmarking, and AI & ML performance recommendations
- Buildings or fleets can utilize dashboard capabilities for energy tracking, hierarchal digital property organization, and robust management of connected devices for lighting, HVAC, audio, existing building management systems and more

AIR CLEANING INTEGRATIONS: COMPATIBLE WITH SMART SCIENCE™ SYSTEM



EnviroKlenz SMART Mount™

- Model number: ED340-0300-SMRT
- Square Foot Coverage: 440 600
- Power Requirements: 12 V, 100-240 V
- Airflow rate: 350 m3/h, 97L/S
- Decibels: Silent 34dB, Night 45dB, Low 50dB, High 60dB
- Dimensions: 14" L x 6" W x 14" H
- Weight: 12.1lbs
- Components: EnviroKlenz SMART Filter, independent SMART IAQ Sensor
- Applications: Buses, Trains, Aircrafts, Industrial facilities, Hotel rooms, Restaurants, Convention centers, Casinos, Other large spaces



EnviroKlenz SMART Cube™

- Model Number: ED340-0250-SMRT
- Square Foot Coverage: 1,000
- Power Requirements: 115V/60Hz/ 1 amp
- CFM (for each speed): 85, 150, 200, 250; 350
- Decibels: Whisper Mode: 54; Low: 56; Medium: 59; High: 62
- Dimensions: Depth: 15" x Width: 15" x Height: 19"
- · Weight: 38lbs
- Components: EnviroKlenz SMART Filter, SMART IAQ Monitor
- Applications: Public buildings, corporate offices, classrooms, other highly occupied spaces