



PRODUCT: **tesa 60985**

DESCRIPTION: Double-Sided Paper

APPLICATIONS: Foam Lamination. Fabric Lamination. Bonding to low surface energy materials such as polyethylene and polypropylene. Mounting metallic and filmic nameplates and control panels.

TECHNICAL SPECIFICATIONS:

Carrier:	Paper
Total Thickness:	0.17 mm
Tensile Strength:	24 N/25mm
Adhesive Power:	18.7 N/25mm
Elongation at Break:	3%
Temperature Resistance:	150°C
Colours Available:	Translucent

PRODUCT PROPERTIES: tesa 60985 is a paper tissue tape coated on both sides with a very high tack, aggressive acrylic adhesive. It has a treated paper release liner for easy handling and die-cutting.

tesa self-adhesive tapes are used successfully in many sectors, to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problem. Each tesa product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We therefore recommend that you carry out your own tests in each case, to confirm that the tesa self-adhesive tape which you envisage using is appropriate for your particular application. The Advisory Section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty.