LASERGLOSS

Specifications

Material

» Microsurfaced impact acrylic

Sheet Size

» 24 1/8" x 48 3/4" (613 x 1238mm)

Finish

» Gloss

Thickness 2-ply

» 1/16" (1.6mm) (Gauges are approximate.)

Engraving Method

- » Rotating carbide

Engraving Depth

» .005" (.013mm)

Usage

- » Interior Signage
- » Exterior Signage
- » Personal Identification
- » Control Panels
- » Equipment ID Tags
- » Safety Signage
- » Recreational Signage
- » Industrial Signage/Tags
- » Trophies, Awards, & Plagues

Fabrication

- » Saws
- » Drills
- » Shears
- » Laser Vector Cuts
- » Bevels
- » Heat Bendable
- » Screen Prints
- » Hot Stamps
- » Bonds » Permits Fine Engraving

Visit www.rowmark.com for Rowmark's complete line of products for rotary engraving, laser engraving and sublimation.

Find answers to all your auestions in the Technical Help section. Be sure to check out support tools under the Sales Tools and Downloads sections.

For technical assistance, call 1-877-ROWMARK (419-429-3160), visit www.rowmark.com or email inquiries@rowmark.com. Can't find exactly what you're looking for? Contact your authorized Rowmark distributor or speak with one of our customer

To request a sample or promotional literature, please call 1-877-ROWMARK (419-429-3160) or email samples@rowmark.com.





service specialists at 1-800-243-3339 (419-425-2407).

LaserGloss Exterior Sign Kit

Fabricate the LaserGloss Exterior Sign Kit by downloading the file found under the downloads section of our website at www.rowmark.com.















rowmark.com / 1.877 ROWMARK / samples@rowmark.com

LASERGLOSS EXTERIOR

LaserGloss Exterior features a stunning, laser-friendly gloss finish that can stand up to the harshest elements. With a tough, exterior-rated gloss top layer designed for outdoor use, LaserGloss Exterior will keep it's finish year after year in virtually any application!

