



CONSTRUCTION
PLASTICS

Product Specification Sheet

Construction Plastics Ltd.
Unit 8, 39-45 Porana Road, Glenfield, 0627
www.constructionplastics.co.nz
Ph. 09 444 2260



DPC - Damp Proof Course

500 microns (0.5 mm) thick.

High quality polythene material.

Each size comes in a 30 metre roll.

Complies with New Zealand and Australian Standards (AS / NZ 2904 / 1995).

Product Code	Width	Length	Colour	Material
CP-DPC50-A	50 mm	30 m	Black	Embossed PE
CP-DPC75-A	75 mm	30 m	Black	Embossed PE
CP-DPC90-A	90 mm	30 m	Black	Embossed PE
CP-DPC140-A	140 mm	30 m	Black	Embossed PE
CP-DPC200-A	200 mm	30 m	Black	Embossed PE
CP-DPC300-A	300 mm	30 m	Black	Embossed PE

Technical Properties

Weight:	450 g/m ²
Tension:	Longitudinal 300 N/cm, Transverse 250 N/cm
Fracture Elongation:	Longitudinal 200%, Transverse 100%
Break Tension:	20N
Water impermeability test - 30 minutes:	0.3Mpa, no leaking
Cold Bending @ -20 degrees Celcius:	No cracking

*The above product specifications are based on a typical item, Construction Plastics Limited does not accept liability for any minor variations in the product. If you feel the product or the specifications listed are incorrect, please contact us.

Visit www.constructionplastics.co.nz for our best and latest pricing.