

Fast, effective, repair of vinyl fence and siding holes!

## Quick Fix Siding, Vinyl Window and Fence Repair Cosmetic Patch Instructions

- PLEASE READ ALL STEPS OF THIS GUIDE FIRST BEFORE STARTING YOUR VINYL SIDING OR VINYL FENCE REPAIR. 0
- Please visit www.fencedaddv.com for more information. 0
- Our Quick Fix Vinyl Siding and Vinyl Fence Repair Kit is ideal for: Vinyl Siding holes, Vinyl Window holes, holes in cemented fence posts, multiple small BB sized holes, base-ball size holes, broken panels, rails with damage, cracks and breaks, holes up to 5" in diameter and repair of most fence pickets! This is a cosmetic repair only. Use our Fence Daddy Vinyl Repair Kit for a more complete


## TIPS

- After sanding wipe area with water or alcohol before applying Quick Fix Patches.
- 1) Getting Started. Cut off and remove any loose hanging vinyl plastic from the fence with a box cutting knife or file, even if this means making the damaged area slightly larger.
- 2) Fence Preparation. Important! (Don't skip this step or product might not work as expected!) Using 120 grit sandpaper, roughen directly around the damaged fence area. Sand in a circle and extend outward up to 8 inches around the perimeter of the damaged fence area. This will remove the weathered vinyl fence surface around the damaged area. Fence surface preparation is crucial for proper adhesion of the Fence Daddy Quick Fix Patch. Clean and remove any remaining dust and debris from the fence with a slightly damp cloth.
- 3) Applying the Patch. Trim the provided 7 inch by 11 inch white Fence Daddy Quick Fix Patch with scissors so that the patch will overlap the fence hole on all sides by a minimum of 1 inch (see picture 3!) Remove the adhesive Fence Daddy Patch backing and apply adhesive side of the patch to the fence. If your fence has line grooves or paneling indentations (as seen in picture 4), apply the patch first into the grooves, pressing down with the provided putty knife and then smooth the patch toward the hole until hole is covered completely.

Apply the Fence Daddy Patch to the fence with firm pressure so the adhesive patch material adheres to the fence. Push all air bubbles to the outside of the Fence Daddy patch on all sides. Smooth the patch so that it will lay perfectly flat on the fence and all corners of the patch are adhering to the fence. (Note) If hole is through both sides of fence, each side of fence will need the Fence Daddy Patch applied before moving on to the next step.

## Your fence will look as good as new!

Picture 1




Picture 5 Does yours look like this?



Grey circle = Sanded areas

Picture 2




Picture 6 (Paint if Desired Acrylic Paint)




Picture 3



Picture 7 Your Fence will look Like New



Picture 4 (Smooth out bubbles)



## Enjoy the Benefits of FD:

- No need to dig up fence posts
- No fence repairmen to call
- No parts to order and replace
- No fence disassembly required
- Fast, effective
- Easy to use
- Takes minutes
- Works with most vinvl fences and siding
- No maintenance required
- Cost effective
- You can DIY (Do it Yourself)



Please visit www.FenceDaddy.com for a video version of these instructions.

Also check out FAQ's, product tips, suggestions and additional vinyl fence products!

