



Filter Pack



Filter Pack Flushing Assembly



Water Reservoir



Lid with Hinged Pour Spout and Lip

STEP 3: FLUSH THE FILTER

Hold the flushing adapter up to the faucet and turn on the water at low pressure for **3 - 5 minutes**. The adapter is designed to fit any standard size faucet. If you have one of those fancy after market faucets in your kitchen, then try a bathroom sink for better results.

NOTE: During this process not all water will pass through the filter, but a majority needs to pass through the filter. 3-5 gallons is needed to flush the filter. Lower your water pressure until most water exits the bottom openings.



STEP 4: REMOVE THE FLUSHING ADAPTER

To remove the flushing adapter, simply unscrew it from the filter. The adapter is recyclable; you can discard it once you're finished



STEP 5: ATTACH FILTER TO PITCHER RESERVOIR

Screw filter on to the threaded base of the pitcher reservoir.



STEP 6: YOU'RE READY TO GO!

Place the reservoir back into the pitcher, fill with tap water and bam! You now have the cleanest water on the block! (Unless someone else on your street has Clearly Filtered too)



STEP 1: RELAX! YOU GOT THIS!

Preparing your filter for its big day does not need to be difficult or stressful. Just follow the steps below and we will lead you through it!



STEP 2: PRE-SOAK THE FILTER

Place the filter in a bowl of tap water and let soak for 10-15 minutes. To see best results, soak the filter over night.

