

Performance Data for the ClearlyFiltered Filtered Shower Head

Replacement Element	Product Type	Rated Capacity	Operating Temperatures	Flow Rate
Model CF-SHRF	Filtered Shower Head	5,000 Gallons (1,800 L)	85-120° F (30-48° C)	2.5 GPM (9.5 LPM)
Manufacturer Contact Information: ClearlyFiltered, Inc. Rancho Santa Margarita, CA 877-876-2740				

Testing performed according to NSF/ANSI standard #177 for Shower Filtration Systems. The contaminants listed have been reduced to a concentration equal to or less than the permissible limits of $\geq 50\%$ reduction as set forth by NSF/ANSI standard #177. The results of which are reported below. Not all contaminants may be present in all tap water. Product tested under controlled laboratory conditions, actual filter performance may vary. The filtration system being tested is designed for removing shower contaminants and is not intended for drinking water treatment or to be used with non-potable water sources. Please refer to any local or state regulations with regards to maximum allowable flow rates.

Contaminant Reduction Claims

Chemicals	
Contaminant	Service Life
Free Chlorine	5,000 Gallons
Combined Chlorine	5,000 Gallons

Aesthetic Effects	
Contaminant	Service Life
Dirt	5,000 Gallons
Sediment	5,000 Gallons
Odor	5,000 Gallons
Iron Oxide	5,000 Gallons
Hydrogen Sulfide	5,000 Gallons