



Disinfectant Spray Portable Spray Equipment

We have the knowledge. We have the technology.

SPRAY DISINFECTANT ON SURFACES

In addition to direct human-to-human transmission, contaminated surfaces also pose a risk of transmitting viruses and pathogens.

The WAGNER Group is a global expert in surface coatings. Our mission: We bring color, protection and function to surfaces.

This makes us the ideal partner when it comes to disinfecting surfaces. With our mobile spraying units, the most common disinfectants can be applied to surfaces quickly, easily and even over large areas. In this way we support people through our innovation and contribute to an effective reduction of the spread of viruses.



EFFICIENT SURFACE COVERAGE

Spraying technology allows a comprehensive surface coating with disinfectant – subsequently the microbial presence of bacteria, fungi or viruses can be reduced.

WHERE

Particular attention must be paid to areas in daily use, as well as to areas frequented by people who are or were already ill.

- Locker Rooms, Bathrooms, (Sanitary facilities)
- Office Spaces
- Restaurants and food preparation areas
- Education facilities
- Public transport
- Public amenities, entryways and public spaces



LOW PRESSURE SPRAY

BC100H-08-1090
MEDIUM SPEED APPLICATION

- Self Contained Running at 110v
- 2.5 Gallon Reservoir
- 25 Feet of Hoses



MEDIUM PRESSURE SPRAY

PK-0B14-PC-407
FAST SPEED APPLICATION

- Self Contained Running at 110v
- High Volume Fluid Delivery
- 35 Feet of Hoses



SAFETY INSTRUCTIONS

Please observe the following safety instructions before use:

- Always wear the necessary personal protective equipment ("PPE", see safety data sheet of the device: gloves, goggles and mask)
- Never point the fluid stream at people or animals - there is a risk of injury
- Thoroughly read the operating instructions of the machine as well as the safety data sheet of the material and follow the instructions contained therein
- Do not spray any electrical devices and equipment
- When using flammable liquids, the machine must be operated outside the room where the spraying occurs (danger zone = 5 m distance from the application area)
- If flammable disinfectants are used, sufficient ventilation must be ensured. Furthermore, no warm or hot surfaces are to be disinfected. If possible, electrical systems should be switched off and light switch operations prevented. There is a risk of explosion!

CHECKLIST

1 You have read the operating manual and all safety instructions and understand how the device functions. Legal, regulatory and normative requirements must be observed.

3 You have installed the spray device 5m outside of the hazard zone.

6 Remove all electronic devices from the area to be disinfected.

2 You have read all the information provided by the manufacturer of the material and have taken appropriate measures against all potential risks.

4 You have ensured there is sufficient natural or artificial ventilation of the work area.

7 You are wearing suitable breathing protection. You are wearing suitable work clothes, protective goggles, protection for your ears and gloves.

ATTENTION! USE ALCOHOL-BASED DISINFECTANTS ONLY WITH AIR ASSISTED AIRLESS SPRAYERS (E.G PK-OC14-PC)

5 You have checked that there are no possible ignition sources such as lit cigarettes, sparks and hot surfaces in the work area.

8 You have not changed the device or gun and you are using only original parts from WAGNER.

ATTENTION! THE FOLLOWING POINTS MUST BE FULFILLED AFTER USING THE DEVICE.

Flush the system thoroughly with water immediately after use or during work interruptions! Ensure that there is no remaining disinfectant liquid in the unit after use!

Wagner Systems Inc.

Liquid Division - C.A. Technologies brand of the Wagner Group

337 South Arthur Ave

Louisville, CO 80027

T 888.820.4498

F 303.438.5708

www.spraycat.com

