



ROBAR INDUSTRIES LTD.

SUBMITTAL INFORMATION

ROBAR 2600 SERIES SERVICE SADDLE

USE

Robar 2600 series service saddle are used to take a service outlet off any transmission or distribution line.

MATERIALS

Saddle Body

T-304 Stainless Steel, fully passivated

Size 2" - 3" - 24 gauge

Size 4" - 8" - 20 gauge. Option of 18 gauge

Size 10" - 30" - 18 gauge

Outlet thread are compliant with AWWA C-800-05

Gasket

Gaskets are made from Nitrile Butadiene Rubber (NBR) compound. Meets ASTM D2000 standard.

Other materials available on request.

Fasteners

5/8 inch diameter, T-304L Stainless Steel and heavy hex nuts. Nuts coated with anti-galling compound. Meets AWWA C111 standards.

PRESSURE

When following Robar installation instructions correctly the 2"-20" saddles will handle working pressures up to 250 PSI. 24"-30" up to 100 PSI. Contact Robar for higher working pressures.

SIZES AVAILABLE

2" - 30" available. Contact Robar for larger sizes.

Outlet sizes - 3/4" - 2", "IP" or "CC"



Effective: 01/01/2020

ROBAR IND LTD. - BRITISH COLUMBIA

Phone: 604-591-8811

Toll Free: 800-663-6553

Fax: 604-591-5288

LES PRODUITS INDUSTRIELS ROBAR INC. - QUEBEC

Phone: 450-441-7525

Toll Free: 800-315-9525

Fax: 450-441-4894

Website: www.robarindustries.com / E-mail: waterworks@robarindustries.com