



TriboDyn Fully Synthetic Multi-Vehicle ATF

TriboDyn® Fully Synthetic MV-ATF is a proprietary multi-vehicle automatic transmission fluid specially formulated for service in Automotive & Heavy-Duty applications. It is engineered to minimize corrosion & wear, reduce operating temperature, maximize gear & transmission life, perform under extreme pressure & heat, provide smooth, positive shift engagement, and eliminate clutch drag & transmission shudder. Is recommended for use in all street, truck & off-road vehicles, including all forms of High Performance Racing with automatic transmissions.

TriboDyn® Fully Synthetic MV-ATF is suitable for use in most passenger cars, and light & heavy-duty truck applications including:

Aisin Warner AW-1*	Ford WSS M2C 922 A1, 924-A	Nissan Matic-S*
Allison C-4	(XT-8-QAW) (JWS 3309)	Porsche ATF 3403 M115
Allison C-3	GM Type A	Porsche LT 71141
Allison TES-295	GM T IV	Saab T IV
Allison TES-389	Honda DW-1	Saturn T IV
AS 68 RC (T IV)	Honda ATF-Z1	Scion (All Vehicles)
Audi G 052 025	Hyundai/Kia Red 1, SP-II, III	Shell 3403, M115
Audi G 052 162	Hyundai/Kia SP-IV* Hyundai	Shell LA2634
Audi G 055 025	NWS-9638* Idemitsu K17	Subaru ATF, ATF-HP
Audi 5HP LT 71141	Isuzu Bescom ATF II, III	Suzuki ATF 3309
(Audi G-052-162-A1 / A2)	Jaguar ATF 3403 M115	Texaco ETL-7045E
Audi 5HP (ZF 5 HP 30)	Jaguar LT 71141	Texaco ETL-8072B
Audi G-055-025-A2(JWS 3309)	JASO 1-A	Texaco N402
BMW ETL-7045, 7045E		Toyota T-III & T-IV
(83 22 0 026 922)	JWS 3309 (T IV)	Toyota WS (JWS 3324) *
BMW LA2634	JWS 3324 (WS)*	Voith 55.6335.XX (G607)
BMW LT 71141	MAN 339F	Voith 55.6336.XX (G1363)
BMW 5 HP (ZF 5 HP 30)	MAN 339 V1	Volvo 97340
BMW 5 HP LT 71141	MAN 339 V2	Volvo 97341
BMW MINI 83 22 0 402 413 9	MAN 339 Z1	VW G 052 025
(JWS 3309)	MAN 339 Z2	VW G 052 162
Caterpillar Powershift TO-2	Mazda ATF-M III Mazda	VW G 052 099
Chrysler ATFs	ATF-M V Mercedes	VW G 055 025
Chrysler Mopar AS 68 RC (T IV)	Benz 236.1	VW 5HP LT 71141
Daewoo LT 71141	Mercedes Benz 236.2	(Audi G-052-162-A1 / A2)
DEXRON® DEXRON®-II,	Mercedes Benz 236.5	VW 5HP (ZF 5 HP 30)
IID, IIE DEXRON®-IIIF, IIIG,	Mercedes Benz 236.6	ZF TE-ML 03D, 04D, 05L, 09,
IIIH DEXRON® VI*	Mercedes Benz 236.7	11B, 14A, 16L, 17C
Esso LT 71141	Mercedes Benz 236.9	ZF TE-ML 14B
	Mercedes Benz 236.10	ZF 5 HP 18FL / 19FL / 24A
Fiat, Typo T IV	Mercedes Benz 236.11	
Ford FNR5	Mitsubishi SP-II, SP-III, SP IV, J2	
Ford MERCON®	NAG 1 (Jeep Cherokee)	
(XT-2-QDR, XT-2-QSM SYN)	Nissan 402	
Ford MERCON® V	Nissan Matic-D, J, K	

*Vis requirement not met

TYPICAL PROPERTIES	
Viscosity: cSt @ 40°C	33.64
cSt @ 100°C	7.41
Gravity, °API	34.66
Specific Gravity @ 60°F	0.8516
Viscosity Index	196
Brookfield Viscosity at -40°C, cP	10,300
Flash Point (PMCC), °C	>170
Pour Point, °F	-60
Appearance/Color	Red