

MODEL BX2822D



SPECIFICATIONS

Double insulated kiln wall with 2.5" brick plus 1" of block insulation. Floor & lid are 3" firebrick.

Maximum Temperature: cone 10, 2345 °F

Electrical Requirements

<u>240 volt 1ph</u>	<u>208 volt 1ph</u>
63.0 amps	72.5 amps
15100 watts	15100 watts

Wiring Requirements

Copper wire size: #4, #2 if the circuit is longer than 40 feet

Fuse or Breaker: 240v 80amp, 208v 90 amp

Receptacle: Direct Wire

UL listed and CSA approved.

WARRANTY: Two Year Parts & Labour

LOCATING YOUR KILN

Place the kiln to the left of the proper electrical outlet, so the cord can be plugged in without touching the metal jacket.

Remove all flammable materials such as curtains, plastics, paper or shelves in the area of the kiln, and allow at least 12 inches of space between the kiln and walls.

Fire the kiln on the stand provided. Air circulation is necessary to prevent overheating.

PHYSICAL DIMENSIONS

Firing Chamber - 8.3 cubic feet

Width: 28 inches

Depth: 22.5 inches

Height: 28.5 inches (without stand)

Width: 35 inches

*** Please allow 12 inches surrounding all sides**

THE SOUNDING STONE
 **Pottery Supplies**
104 Trottier Bay
Winnipeg, MB
R3T 3Y5
Ph (204) 284-2964
Fax 453-5210
www.soundingstone.com