



SKUTT
CERAMIC PRODUCTS



MODEL KM1018-3

SPECIFICATIONS

Three inch thick lid, base & walls
Maximum Temperature: cone 10, 2345 °F

Electrical Requirements

<u>240 volt 1ph</u>	<u>208 volt 1ph</u>
39.4 amps	40.0 amps
9460 watts	8320 watts

Wiring Requirements

*Copper wire size: #6,
#4 if circuit is longer than 40 feet.*
Fuse or Breaker: 50
*Receptacle: 2 pole, 3 wire grounding
Nema 6-50R configuration*



UL listed and CSA approved.

WARRANTY: Two Year Parts & Labour

LOCATING YOUR KILN

*Place the kiln to the left of the proper electrical outlet,
so the cord can be plugged in without touching the metal jacket.*

*Remove all flammable materials such as curtains, plastics, paper
or shelves in the area of the kiln, and allow at least 18 inches of space
between the kiln and walls.*

*Fire the kiln on the stand provided. Air circulation is necessary
to prevent overheating.*

PHYSICAL DIMENSIONS

Firing Chamber - 4.2 cubic feet
Width: 22.5 inches
Depth: 18 inches

Height: 32 inches
Width: 28.5 inches

** Please allow 18 inches surrounding all sides*

THE SOUNDING STONE
Pottery Supplies
104 Trottier Bay
Winnipeg, MB
R3T 3Y5
Ph (204) 284-2964
Fax 453-5210
www.soundingstone.com