



SKUTT
CERAMIC PRODUCTS



MODEL KM1227PK

SPECIFICATIONS

Three inch thick lid, base & walls
Maximum Temperature: cone 10, 2345 °F

Electrical Requirements

<u>240 volt 1ph</u>	<u>208 volt 1ph</u>
60.0 amps	69.0 amps
14,300 watts	14,300 watts

Wiring Requirements

Copper wire size: #4,
#2 if circuit is longer than 40 feet.
Fuse or Breaker: 80
Receptacle: Direct Wire, No Receptacle

UL listed and CSA approved.

WARRANTY: Two Year Parts & Labour

LOCATING YOUR KILN

Place the kiln to the left of the proper electrical outlet,
so the cord can be plugged in without touching the metal jacket.

Remove all flammable materials such as curtains, plastics, paper
or shelves in the area of the kiln, and allow at least 18 inches of space
between the kiln and walls.

Fire the kiln on the stand provided. Air circulation is necessary
to prevent overheating.

PHYSICAL DIMENSIONS

Firing Chamber - 9.9 cubic feet
Width: 28 inches
Depth: 27 inches

Height: 43 inches
Width: 34.5 inches

*** Please allow 18 inches surrounding all sides**

THE SOUNDING STONE
Pottery Supplies
104 Trottier Bay
Winnipeg, MB
R3T 3Y5
Ph (204) 284-2964
Fax 453-5210
www.soundingstone.com