



**SKUTT**  
CERAMIC PRODUCTS



## MODEL KM614-3

### SPECIFICATIONS

*Three inch thick lid, base & walls*  
*Maximum Temperature: cone 6, 2200 °F*

#### Electrical Requirements

**120 volt**  
**20.0 amps**  
**2,300 watts**

*This kiln will not operate in a standard household outlet*

#### Wiring Requirements

**Copper wire size: #10**  
**Fuse or Breaker: 30**  
**Receptacle: 2 pole, 3 wire grounding**  
**Nema 5-30R configuration**

**UL listed and CSA approved.**

**WARRANTY: Two Year Parts & Labour**



### LOCATING YOUR KILN

*Place the kiln to the left of the proper electrical outlet, so the cord can be plugged in without touching the metal jacket.*

*Remove all flammable materials such as curtains, plastics, paper or shelves in the area of the kiln, and allow at least 18 inches of space between the kiln and walls.*

*Fire the kiln on the stand provided. Air circulation is necessary to prevent overheating.*

### PHYSICAL DIMENSIONS

**Firing Chamber - .8 cubic feet**  
**Width: 11 inches**  
**Depth: 13.5 inches**

**Height: 27.5 inches**  
**Width: 17 inches**

**\* Please allow 18 inches surrounding all sides**

**THE SOUNDING STONE**  
*Pottery Supplies*  
104 Trottier Bay  
Winnipeg, MB  
R3T 3Y5  
Ph (204) 284-2964  
Fax 453-5210  
[www.soundingstone.com](http://www.soundingstone.com)