



**SKUTT**  
CERAMIC PRODUCTS



## MODEL KM818-3-30A

### SPECIFICATIONS

*Three inch thick lid, base & walls  
Maximum Temperature: cone 8, 2300 °F*

#### Electrical Requirements

<u>240 volt 1ph</u>	<u>208 volt 1ph</u>
21.7 amps	21.7 amps
5200 watts	4500 watts

#### Wiring Requirements

*Copper wire size: #10,  
#8 if circuit is longer than 40 feet.  
Fuse or Breaker: 30  
Receptacle: 2 pole, 3 wire grounding  
Nema 6-30R configuration*

*UL listed and CSA approved.*

*WARRANTY: Two Year Parts & Labour*



### LOCATING YOUR KILN

*Place the kiln to the left of the proper electrical outlet,  
so the cord can be plugged in without touching the metal jacket.*

*Remove all flammable materials such as curtains, plastics, paper  
or shelves in the area of the kiln, and allow at least 18 inches of space  
between the kiln and walls.*

*Fire the kiln on the stand provided. Air circulation is necessary  
to prevent overheating.*

### PHYSICAL DIMENSIONS

*Firing Chamber - 2.3 cubic feet  
Width: 16.5 inches  
Depth: 18 inches*

*Height: 34 inches  
Width: 22.5 inches*

*\* Please allow 18 inches surrounding all sides*

**THE SOUNDING STONE**  
*Pottery Supplies*  
104 Trottier Bay  
Winnipeg, MB  
R3T 3Y5  
Ph (204) 284-2964  
Fax 453-5210  
www.soundingstone.com