



SKUTT
CERAMIC PRODUCTS



MODEL KMT1022-3

SPECIFICATIONS

*Three inch thick lid, base & walls
Maximum Temperature: cone 10, 2345 °F*

Electrical Requirements

<u>240 volt 1ph</u>	<u>208 volt 1ph</u>
48.0 amps	48.0 amps
11520 watts	9984 watts

Wiring Requirements

*Copper wire size: #6, #4 if the circuit is
longer than 40 feet*

Fuse or Breaker: 60

Receptacle: Direct Wire

UL listed and CSA approved.

WARRANTY: Two Year Parts & Labour

LOCATING YOUR KILN

*Place the kiln to the left of the proper electrical outlet,
so the cord can be plugged in without touching the metal jacket.*

*Remove all flammable materials such as curtains, plastics, paper
or shelves in the area of the kiln, and allow at least 18 inches of space
between the kiln and walls.*

*Fire the kiln on the stand provided. Air circulation is necessary
to prevent overheating.*

PHYSICAL DIMENSIONS

Firing Chamber - 5.7 cubic feet

Width: 22.5 inches

Depth: 22.5 inches

Height: 36 inches

Width: 28.5 inches

** Please allow 18 inches surrounding all sides*

THE SOUNDING STONE
Pottery Supplies
104 Trottier Bay
Winnipeg, MB
R3T 3Y5
Ph (204) 284-2964
Fax 453-5210
www.soundingstone.com