



SKUTT
CERAMIC PRODUCTS



MODEL KMT1027-3

SPECIFICATIONS

Three inch thick lid, base & walls
Maximum Temperature: cone 10, 2345 °F

Electrical Requirements

240 volt 1ph	208 volt 1ph
48.0 amps	48.0 amps
11520 watts	9984 watts

Wiring Requirements

Copper wire size: #6, #4 if the circuit is longer than 40 feet

Fuse or Breaker: 60

Receptacle: Direct Wire

UL listed and CSA approved.

WARRANTY: Two Year Parts & Labour

LOCATING YOUR KILN

Place the kiln to the left of the proper electrical outlet, so the cord can be plugged in without touching the metal jacket.

Remove all flammable materials such as curtains, plastics, paper or shelves in the area of the kiln, and allow at least 18 inches of space between the kiln and walls.

Fire the kiln on the stand provided. Air circulation is necessary to prevent overheating.

PHYSICAL DIMENSIONS

Firing Chamber - 6.4 cubic feet

Width: 22.5 inches

Depth: 27 inches

Height: 41 inches

Width: 28.5 inches

*** Please allow 18 inches surrounding all sides**

THE SOUNDING STONE
Pottery Supplies
104 Trottier Bay
Winnipeg, MB
R3T 3Y5
Ph (204) 284-2964
Fax 453-5210
www.soundingstone.com