



SKUTT
CERAMIC PRODUCTS

MODEL KMT714



SPECIFICATIONS

Two and a half inch thick lid, base & walls
Maximum Temperature: cone 8, 2300 °F

Electrical Requirements
208/240 volt 1ph
20.0 amps
3,600 watts

Wiring Requirements
Copper wire size: #10,
#8 if circuit is longer than 40 feet.
Fuse or Breaker: 30
Receptacle: 2 pole, 3 wire grounding
Nema 14-30R configuration

UL listed and CSA approved.



WARRANTY: One Year Parts & Labour

LOCATING YOUR KILN

*Place the kiln to the left of the proper electrical outlet,
so the cord can be plugged in without touching the metal jacket.*

*Remove all flammable materials such as curtains, plastics, paper
or shelves in the area of the kiln, and allow at least 18 inches of space
between the kiln and walls.*

*Fire the kiln on the stand provided. Air circulation is necessary
to prevent overheating.*

PHYSICAL DIMENSIONS

Firing Chamber - 1.4 cubic feet
Width: 14.5 inches
Depth: 13.5 inches

Height: 34.5 inches
Width: 19.5 inches

*** Please allow 18 inches surrounding all sides**

THE SOUNDING STONE
Pottery Supplies
104 Trottier Bay
Winnipeg, MB
R3T 3Y5
Ph (204) 284-2964
Fax 453-5210
www.soundingstone.com