



 Bluetooth®

90S

Fujikura 90S Fusion Splicer

The 90S is the latest core alignment splicer from Fujikura. It's designed to give you high quality splices and to stay in the field. The 90S kit solves problems seen in the field today, from splicing poor quality legacy fiber to automated equipment maintenance and upkeep. The 90S can be utilized in any field splicing application seen today: bend-insensitive fibers in drop cables, long-haul terrestrial and submarine LEAF fibers, loose buffer fiber, splice on connectors, and the list goes on. The speed and accuracy of the 90S even make it suitable for certain production and specialty environments, where high output, tight packaging, and low loss requirements are needed. Regardless your use-case, the 90S is designed to keep you going with an extended battery life from 200 to 300 splice and heat cycles, and by alleviating the need for traditional operation tasks such as; frequent arc calibrations, cleaver blade rotations, cleaver usage tracking, and manual splicing operations with its multiple automated and ease-of-use features. A multi-purpose sheath clamp, redesigned work tray, cooling tray, and optional cable clamp make the 90S kit more versatile than any of its predecessors in adapting to varying work conditions and environments. Put our 90S to the test by contacting us to see its capabilities first-hand, 1-800-235-3423.



In Work Tray



Wind Protector Open

Features

- Cleaver tracking and upkeep with wireless communication
- Automated wind protector, sheath clamps and splice operation
- Fiber type identification
- Loose and tight buffer with same sheath clamp
- Lithium-ion battery with 300 splices/shrinks per charge
- 5 mm cleave length for small package needs
- Multi-function transit case with integrated workstation

Applications

- Distribution fiber repair
- Long-haul network installation
- Field termination with splice-on connectors
- Access network installation
- Fanout kits, pigtailed and splice cassettes
- OSP cable installation and repair
- Optical modules – splitters, couplers, MUXs, EDFAs and attenuators

STOCK ITEM

SAME DAY SHIPPING

Fujikura 90S Fusion Splicer


Ordering Information

DESCRIPTION	AFL NO.
90S Fusion Splicer (machine only) Includes: Includes: ADC-20 AC Adapter, ACC-14 AC Cord, BTR-15 Battery, ELCT2-16B Spare Electrodes (pair), Sheath Clamps, SP-03 Fiber Holder Set Plates, USB-01-01 Cable, Alcohol Pot, Splicer Carrying Strap, Quick Reference Guide, Work Tray J-Plate, SS03 single fiber stripper and CC39 Transit Case with Carrying Strap	S017519
90S Fusion Splicer Kit (with cleaver) Includes: CT50 Cleaver, ADC-20 AC Adapter, ACC-14 AC Cord, BTR-15 Battery, ELCT2-16B Spare Electrodes (pair), Sheath Clamps, SP-03 Fiber Holder Set Plates, USB-01 Cable, Alcohol Dispenser, Splicer Carrying Strap, Quick Reference Guide, Work Tray J-Plate, SS03 single fiber stripper and CC39 Transit Case with Carrying Strap	S017521
90S Fusion Splicer without Bluetooth (machine only) Includes: ADC-20 AC Adapter, BTR-15 Battery, ACC-14 AC Cord, ELCT2-16B Spare Electrodes (pair), Sheath Clamps, SP-03 Fiber Holder Set Plates, USB-01 Cable, Alcohol Pot, Splicer Carrying Strap, Quick Reference Guide, Work Tray J-Plate, SS03 Single Fiber Stripper and CC39 Transit Case with Carrying Strap	S017000
One Year Extended Warranty	S012996
Two Year Extended Warranty	S013000

Recommended Products for the 90S


DESCRIPTION	AFL NO.
Cleavers	
CT08 Cleaver	S017004
CT50 Cleaver	S017030
Fiber Holders (pair)	
FH-70-250 (250 µm coated fiber)	S017111
FH-70-900 (900 µm jacketed fiber)	S017113
FH-70-160 (160 µm coated fiber)	S017095
FH-60-LT900 (Loose buffer 900 µm fiber)	S015181
FH-60-LT900 (each)	S015275
FUSEConnect® Accessories	
FH-FC-20 (900 µm within 2.0 mm sheathing) (each)	S014696
FH-FC-30 (900 µm within 3.0 mm sheathing) (pair)	S014695
FH-FC-900 (900 µm cable) (each)	S014697
CLAMP-FC-2000 (pair)	S014705
CLAMP-FC-3000 (pair)	S014704
Power Supply Options and Equipment	
ADC-20 AC Adapter	S017513
ACC-14 AC Power Cord	S014536
BTR-15 Battery	S017512
DCC-20 Power Cord (connects AC Adapter to cigarette lighter socket)	S017527
DCC-21 Power Cord (connects AC Adapter to power source via alligator clips)	S017528
DCA-03 DC Adapter (Connect AC Adaptor without battery)	S017526

DESCRIPTION	AFL NO.
Miscellaneous	
ELCT2-16B Electrodes	S013532
Portable Tripod Workstation (see product profile for more detail)	S014773
ASW-02 Splicing Workstation (see product profile for more detail)	S010532
JP-10 J-Plate (Cooling tray attaches to splicer)	S017522
JP-10-FC J-Plate with Fiber Clamps	S017523
CLAMP-DC-12 (Drop cable clamp for work tray)	S017550
USB-01 Cable	S014777
CC39 Transit Case	S017514
Splicer V-Groove Cleaning Kit	S014397




Fiber Holders

- Wide range of sizes for various applications
- Loose & Tight Buffer options available



Portal Tripod Work Station

- Sturdy work tray supports the splicer, cleaver and accessories
- Tripod supports a load capacity of up to eleven pounds



V-Groove Cleaning Kit

- Removes environmental contamination from the v-groove of the splicer
- Maintains performance and ensures fiber alignment

Fujikura 90S Fusion Splicer

Specifications

PARAMETER	VALUE	
Fiber Alignment Method	Active core alignment	
Fiber Count Can Be Spliced	Single fiber	
Applicable Fiber	Fiber Type	Single mode optical fiber
	Cladding Dia.	Multi mode optical fiber
Applicable Coating	Sheath Clamp	80 to 150 μm
		Coating dia. : Max. 3,000 μm Cleave length : 5 to 16 mm
Fiber Splice Performance	Splice Loss	ITU-T G.652 : Avg. 0.02 dB
		ITU-T G.651 : Avg. 0.01 dB
		ITU-T G.653 : Avg. 0.04 dB
		ITU-T G.655 : Avg. 0.04 dB
Splice Loss	ITU-T G.657 : Avg. 0.02 dB	
	SM FAST mode : Avg. 8 to 10 sec. AUTO mode : Avg. 14 to 16 sec.	
Applicable Protection Sleeve	Sleeve Type	Heat-shrinkable sleeve
	Sleeve Length	Max. 66 mm
	Sleeve Dia.	Max. 6.0 mm before shrinking
Sleeve Heat Performance	Heat Time	60 mm slim mode : Avg. 9 to 10 sec.
		60 mm mode : Avg. 13 to 15 sec.
Fiber Tensile Test Force	Approx. 2.0 N	
Electrode Life	Approx. 5,000 splices	
Physical Description	Dimensions W	Approx. 170 mm without projection
	Dimensions D	Approx. 173 mm without projection
	Dimensions H	Approx. 150 mm without projection
	Weight	Approx. 2.8 kg including battery
Environmental Condition	Temperature	Operate : -10 to 50°C
		Storage : -40 to 80°C
	Humidity	Operate : 0 to 95% RH non-condensing Storage : 0 to 95% RH non-condensing
Altitude	Max. 5,000 m	
Ac Adaptor	Input	AC100 to 240 V, 50/60 Hz, Max. 1.5 A
Battery Pack	Type	Rechargeable Lithium Ion
	Output	Approx. DC14.4V / 6,380 mAh
	Capacity	Approx. 300 splice and heat cycles
	Temperature	Recharge : 0 to 40°C
		Storage : -20 to 30°C
Battery Life	Approx. 500 recharge cycles	
Display	LCD Monitor	TFT 5 inches with touch screen
	Magnification	200 to 320x
Illumination	V-Grooves	LED lamp
Interface	PC	USB2.0 Mini B type
	External Led Lamp	USB2.0 A type, Approx. DC5V, 500 mA
	Ribbon Stripper	Mini DIN 6 pin, DC12V, Max. 1A
	Wireless	Bluetooth 4.1 LE
Data Storage	Splice Mode	100 splice modes
	Heat Mode	30 heat modes
	Splice Result	20,000 splices
	Splice Image	100 images
Screw Hole For Tripod		1/4-20 UNC
Other Features	Automatic Functions	Splice mode select by fiber type analysis
		Discharge power calibration
		Wind protector : open/close
		Sheath clamp : open
		Heater lid : open/close
Heater clamp : open/close		
Reference Guide	Video and PDF file stored in splicer	
Sheath Clamp	Easy sleeve positioning clamp	
Electrode	Replaceable without tool	