

U.S. Patent 9,217,688



Features

- 1-button to auto-focus, center, capture, analyze, and save
- IEC, IPC, and user-defined pass/fail analysis
- Untethered, compact, hand-held inspection
- Use independently or pair with OTDR
- Save 10K results internally or share via WiFi or USB

Applications

- Inspect connectors on patch cords or in bulkhead adapters
- Optical network installation, troubleshooting, and maintenance
- Inspect MPO/MTP multi-fiber connectors
- Assure critical fiber infrastructure performs properly
- Keep fiber connections working at optimal performance levels
- Verify proper connector cleaning practices are being used

FOCIS Flex makes connector inspection simple, fast, and convenient. With the press of a single button, FOCIS Flex auto-focuses, captures and centers the end-face image, applies Pass/Fail rules, displays image and Pass/Fail results, saves results internally and/or wirelessly transfers data to a paired FlexScan OTDR or a smart device. It is fast, small, and easy to use to enable 100% connector inspection.

Independent, untethered operation: With rechargeable battery and integrated display, FOCIS Flex can be used independently without requiring an external OTDR or display unit.

Optional pairing with FlexScan OTDR or smart devices: Captured images and Pass/Fail results can be immediately displayed and easily saved on either paired FlexScan OTDR or a smart device equipped with the AFL's free FOCIS Flex App. This capability enables inspection results to be included in reporting and archiving.

Save results internally or externally: FOCIS Flex internally stores up to 10,000 results using file-naming capabilities similar to those of the FlexScan OTDR. A micro-USB port supports fast upload of internally stored results to PC and ensures your FOCIS Flex software can be updated to the latest features and supported languages.


Wide range of adapter tips: Interchangeable adapter tips support connector inspection for a wide range of both single-fiber and multifiber patchcords and bulkhead-mounted connectors having either PC or APC polished end-faces.


Bundled kits for significant savings: FOCIS Flex is available in kits that include a Basic license for Test Result Manager (TRM® 3.0), user-selected adapter tips and cleaning supplies, and a soft carry case.

Easy reporting and archiving: Included Test Result Manager (TRM 3.0) provides data processing and reporting locally via a PC. The FOCIS Flex mobile App is available for free download from Google play or App Store for sharing data with smart devices.



U.S. Patent 9,217,688





Pass/Fail results in seconds: With the press of a single button, FOCIS Flex auto-focuses, captures and centers the end-face image, applies Pass/Fail rules, displays image and Pass/Fail results. Captured Pass/Fai results are easily viewed in either Image or Table view.

Image view shows end-face image with Pass/Fail region overlay, failing scratches/defects highlighted in red, and passing scratches/defects highlighted in green.

Table view shows analysis rule applied to determine Pass/Fail, analysis Zone IDs (A, B, C, D), scratch analysis results for each zone, and defect analysis results for each zone.

Specifications a

OPTICAL PERFORMANCE			
Field of View (viewed on FOCIS Flex)	Live: 710 x 860 μm; Captured, Zoomed Out: 560 x 600 μm; Captured, Partially Zoomed In: 360 x 390 μm; Captured, Fully Zoomed In: 180 x 195 μm		
Field of View (Viewed on a PC)	Stored, Zoomed Out: 700 x 525 µm; Stored, Fully Zoomed In: 240 x 180 µm		
Manual Detection Capability (minimum)	0.25 μm		
Auto Analysis Resolution	<1.0 μm		
Captured Image Size (Pixels)	648 x 480 VGA; Images stored internally in three .JPG files, one at each FOV		
OPERATING FEATURES			
Focus	Auto-focus and manual focus		
Centering	Auto-centering after capture		
Pass/Fail Analysis	IEC 61300-3-35 (2015), IPC and user-defined criteria		
Image Capture and File Storage Capacity	10,000 files		
File Format (Image and Pass/Fail Results)	jpg, gif		
Bluetooth Characteristics	SPP to FlexScan and FlexTester OTDRs; IAP to iOS devices		
USB Characteristics	USB 1.1 mass storage device		
Supported Languages	English, Chinese Simplified, Chinese Traditional, Finnish, French, German, Italian, Japanese, Korean, Polish, Russian, Spanish, Turkish		
PHYSICAL AND POWER CHARACTERISTICS			
Display size, type, resolution	2.4", TFT, 240 x 320 with brightness control		
Battery Type	NiMH, user replaceable		
Battery Operating Time (typical)	8 hours (60 tests in 20 minutes each hour; auto-off enabled)		
Recharge Time	<4.5 hours		
Power Save Features	Auto-off (disabled, 2, 5, 10 minutes)		
AC Charger voltage, frequency, current	100-240 V, 50/60 Hz, 5VDC, 2A		
Size	47 x 37 x 183 mm (1.8 x 1.5 x 7.2 in)		
Weight	240 g (0.5 lb)		
ENVIRONMENTAL CHARACTERISTICS			
Operating Temperature	0 to +50 °C		
Storage Temperature	-40 to +70 °C		
Relative Humidity	95%, non-condensing		
Transit and shock	2G vibration, 30G shock		

Notes:

a. All specifications valid at 23°C \pm 2°C (73.4°F \pm 3.6°F).



U.S. Patent 9,217,688

FlexScan OTDR PRO and BIPM Kits with FOCIS Flex

PRO Kits include the following items:

- FlexScan with accessories (AC charger, carry strap, SC/2.5 mm connector adapters, TRM® 3.0 Advanced Test Results Manager, carry case)
- FOCIS Flex Fiber Optic Connector Inspection System with accessories (AC charger, USB cable, soft carry case/holster)
- Two user-selected adapter tips and one user-selected One-Click Cleaner
- 150 m Fiber Ring (launch cable) with user-specified connectors

Complete kits expand on PRO Kits by adding bend insensitive fiber identifier with optional power meter (OFI-BIPM).

See FlexScan data sheet for FlexScan PRO and Complete Kit ordering information.

FOCIS Flex Adapter Tips (Contact AFL for adapter tips for other connector types)

DESCRIPTION	AFL NO.	
SC-UPC bulkhead adapter tip	FFLX-01-SC	
FC-UPC bulkhead adapter tip	FFLX-01-FC	
ST-UPC bulkhead adapter tip	FFLX-01-ST	
LC-UPC bulkhead adapter tip	FFLX-01-LC	
Universal 2.5 mm, UPC ferrule adapter tip	FFLX-01-U25	
Universal 1.25 mm, UPC ferrule adapter tip	FFLX-01-U125	
SC-APC bulkhead adapter tip	FFLX-4S-ASC	
FC-APC bulkhead adapter tip	FFLX-4S-AFC	
LC-APC bulkhead adapter tip	FFLX-4S-ALC	
Universal 2.5 mm, APC ferrule adapter tip	FFLX-01-A25	
Universal 1.25 mm, APC ferrule adapter tip	FFLX-01-A125	
FOCIS Flex adapter extension tube, straight, 46 mm	FFLX-01-EXTS46	
FOCIS Flex adapter extension tube, straight, 80 mm:	FFLX-01-EXTS80	
E2000 PC/UPC bulkhead adapter tip		
E2000 APC bulkhead adapter tip	FFLX-4S-E2KA	
Tip for SC/APC (OptiTap®) bulkhead adapter	FFLX-4S-OTA	
Tip for OptiTip® APC ferrule and bulkhead adapter	DFS1-01-0013MR	
MTP/PC ferrule & bulkhead adapter extended tip kit (base plus MTP/PC front end tip)	DFS1-00-0037MR	
MTP/PC and MTP/APC ferrule & bulkhead adapter extended tip kit (base,MTP/PC, MTP/APC front end tips)	DFS1-00-0042MR	
MTP/APC ferrule and bulkhead adapter extended tip kit (base plus MTP/APC front end tip)		

Ordering Information

DESCRIPTION	AFL NO.
FOCIS Flex Kit, soft carry case/holster, USB cable, AC charger, TRM® 3.0 reporting software, reference guide, no tips	FOCIS-FLX-P4XN
FOCIS Flex Kit, soft carry case/holster, USB cable, AC charger, TRM 3.0 reporting software, reference guide, 2 user-selected UPC adapter tips (ferrule and bulkhead), user-selected One-Click cleaner	FOCIS-FLX-P4XU
FOCIS Flex Kit, soft carry case/holster, USB cable, AC charger, TRM 3.0 reporting software, reference guide, 2 user-selected APC adapter tips (ferrule and bulkhead), user-selected One-Click cleaner	FOCIS-FLX-P4XA
FOCIS Flex Kit, soft carry case/holster, USB cable, AC charger, TRM 3.0 reporting software, reference guide, user-selected UPC adapter tips (ferrule and bulkhead), 2 user-selected APC adapter tips (ferrule and bulkhead), user-selected One-Click cleaner	FOCIS-FLX-P4XUA



U.S. Patent 9,217,688

Test Management and Reporting Software

DESCRIPTION	AFL NO.
TRM 3.0 with Basic License, USB delivery (included with all FOCIS Flex kits) TRM3-BASIC	
TRM 3.0 upgrade from Basic to Advanced License, USB delivery	TRM3-UPGRADE
TRM 3.0 upgrade from Basic to Advanced License, email delivery	TRM3-UP-EMAIL
FOCIS Flex App (Google play or App Store)	Free Download

Recommended Products



FlexScan® FS300 (quad) and FS200 (single-mode) OTDRs

- SmartAuto® 1-button automated testing for fast results
- LinkMap® color-coded icons for easy troubleshooting
- FleXpress® mode (FS200) completes OTDR test in <5 seconds!
- Integrated Source, Power Meter and VFL



OFI-BIPM Optical Fiber Identifier

- World class signal sensitivity
- Trigger lock, positive stop for optimum detection
- Integrated optical power meter option

Qualifications

FS200

CATEGORY	REGULATION/STANDARD	QUALIFICATION
CE Marking	EU	Compliant to relevant EU Directives on health, safety, and environmental protection, and certified with CE marking
IEC		Compliant to IEC 61010-1 for safety requirements for electrical equipment
	EN	Compliant to EN 61010-1 for safety requirements for electrical equipment
Safety /EMC /EMI FCC FDA IEC	IEC	Compliant to IEC 61326-1 for EMC requirements for electrical equipment
	EN	Compliant to EN 61326-1 for EMC requirements for electrical equipment
	EN	Compliant to EN 55011 for EMC requirements for industrial, scientific and medical equipment
	FCC	Compliant to code of federal regulations FCC 47 CFR 15 on unlicensed transmissions
	FDA	Compliant to code of federal regulations FDA 21 CFR 1040.10 and 1040.11 on laser products
	IEC	Compliant to IEC 60825-1 for safety of laser products
RoHS	EU	Compliant to EU regulations Directive 2011/65/EU (RoHS 2) and Directive 2015/863 (RoHS 3)
Test Method	IEC	Compliant to IEC 61300-3-35 for visual inspection of fiber optic connectors and fiber-stub transceivers
IPC		Compliant to IPC-8497-1 for cleaning methods and contamination assessment for optical assembly

Contact Sales@AFLglobal.com to schedule a demonstration or learn how to buy.

Visit www.AFLglobal.com/Test to learn more about FOCIS Flex.

International Sales and Service Contact Information available at www.AFLglobal.com/Test/Contacts.