

3 PORT MINI SWITCH

FEATURES

- Complies with IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX/100Base-FX and IEEE 802.3x flow control
- Provides media conversion for TP and Fiber optic media types
- Extends network span from 2km (Multimode) to 20km (Single Mode)
- 10/100Mbps, auto-negotiation on TP port
- Supports back-pressure-based flow control for Half-Duplex and pause-frame-based flow control for Full-Duplex

These mini-switches provide a simple and inexpensive way to add additional computers to a network. The 3-port Mini Switch has (2) 100Mbps fiber ports and (1) 10/100Mbps twisted pair copper port. Meets IEEE 802.3, 802.3u and 802.3x Standards. This switch provides Media conversion for TP and fiber optic media types and extends network spans and has 10/100Mbps, auto-negotiation on the twisted pair port. External power supply included.

SPECIFICATIONS

| | |
|----------------|---|
| TP Port | 10/100Mbps, Shielded RJ-45 |
| FX Port | 100 Base - FX |
| LED Indicators | Power, Link/Act, Speed, Duplex/Collision |
| Input Power | 100 to 240VAC, 50 to 60Hz |
| Power Supply | External Power Adaptor (DC 5V/2A) |
| Temperature | 0 to 60 degrees |
| Humidity | 5% to 90% |
| Dimension | 26.7(H) x 70.8(W) x 94(D)mm |
| F1-SWMM1 | (2) 100Base-FX MM/SC and One 10/100Base-T/TX Port |
| F1-SWSM1 | (2) 100Base-FX SM/SC and One 10/100Base-T/TX Port |