

# DUAL SOURCE LC VISUAL FAULT LOCATOR



## FEATURES

- Dual visual fault locator for duplex LC cables
- 9 volt battery included
- Small handheld design
- Can activate single or both sources simultaneously, one modulates while one is constant
- Easy to identify the fault's location
- Easy verification of duplex cable polarity
- Quick identification of continuity of installation
- Low battery indicator light
- "A" and "B" source indicator lights
- Ergonomically friendly handheld soft case
- Plug and Play LC mating sleeve allows for secure connection

Fosco introduces its Duplex LC Visual Fault Locator. Because LC connectors are commonly clipped together this product eliminates the common mistake that is made of crossing Tx and Rx patchcords to active equipment. This unit allows the user to toggle between the "A" and "B" sources to ensure that everything is properly connected. Unit comes with: Carrying pouch, 9V Battery, User Manual, One Year Warranty

## SPECIFICATIONS

|                           |                                          |
|---------------------------|------------------------------------------|
| <b>Source Type</b>        | LASER                                    |
| <b>Wavelength</b>         | -1.0 dBm to +1.0 dBm Typical 0dBm ( 1mW) |
| <b>Output power level</b> | 9 Volt Alkaline                          |
| <b>Safety</b>             | CLASS 2 ( Avoid direct eye exposure)     |
| <b>Output Type</b>        | Continuous Wave(CW)                      |
| <b>Fiber type</b>         | Dual Singlemode or Multimode Fiber       |
| <b>Connector Type</b>     | LC- UPC                                  |
| <b>Battery Type</b>       | 9V Alkaline                              |
| <b>Battery life</b>       | 20 hours of continuous usage             |
| <b>Temperature Range</b>  | 0 - 50° C                                |
| <b>Dimensions</b>         | 75 X 105 X 27mm                          |
| <b>Weight (oz)</b>        | 16                                       |