

VISUAL FAULT LOCATOR - HAND HELD



FEATURES

- Stabilized Visible Laser
- Battery Operated - 9 Volt
- 1mW Laser Diode @ 650nm
- Continuous Wave or Pulsed Wave
- Ruggedized Rubber Holster
- Singlemode or Multimode Use

CONNECTOR STYLES

- 2.5mm Universal Adapter - (Singlemode & Multimode)(SC, FC, ST)
- LC - (Singlemode & Multimode)
- FC/APC - Singlemode
- SC/APC - Singlemode
- MT-RJ - Singlemode & Multimode

SPECIFICATIONS

Outpower	1mW min	Pulse Rate	1Hz
Wavelength	650nm Typ	Operating Temperature	-10° to + 50° Celsius
Battery	9 Volt Alkaline	Weight	7.5 oz
Battery Life (typical)	30hrs continuous 40hrs modulated	Size	6.25"L x 3.25"W x 1.25"D
Range	5km - Multimode 7km - Singlemode	Emission Indicator	Power indicator in sync when laser in use

ORDERING INFORMATION

OF-1000-UF	Visual Fault Locator with 2.5mm Universal Adapter (MM & SM)
OF-1000U-LC	Visual Fault Locator with LC Adapter (MM & SM)
OF-1000U-FCA	Visual Fault Locator with FC/APC Adapter (SM)
OF-1000U-SCA	Visual Fault Locator with SC/APC Adapter (SM)
OF-1000U-MTRJ	Visual Fault Locator with MT-RJ Adapter (MM & SM)