




# MDU SIMPLEX DROP FIBER

## CLEARCURVE® RISER, WHITE SC/APC



Zeus presents: **MDU Drop Fiber**: MDU Drop fiber is composed of 1 fiber Corning ClearCurve® ZBL Indoor / Outdoor Riser cable, terminated with (1) SC/APC or (1) LC/APC Green Connector, and spooled on a 7 inch spool.

### SPECIFICATIONS

<b>Storage Temperature</b>	-40°C to +70°C
<b>Operating Temperature</b>	-40°C to +70°C

### CABLE CHARACTERISTICS

<i>Mechanical</i>		<i>Optical</i>	
<b>Fiber Count</b>	1	<b>Fiber Type</b>	Corning ClearCurve® ZBL
<b>Strength Member</b>	Aramid Yarn	<b>Core Size</b>	9/125
<b>Overall Jacket Material</b>	Poly Vinyl Chloride	<b>Attenuation (MAX)</b>	0.4dB/km @1550nm
<b>Nominal Outer Diameter (mm)</b>	2.85 (3mm)	<b>Mode-Field Diameter[1310/1550nm]</b>	8.6/9.65µm
<b>Bend Radius [1 turn](mm)</b>	10	<b>Numerical Aperture</b>	0.14
<b>Weight (lbs/km)</b>	17		




FTTx Solution



# MDU SIMPLEX DROP FIBER

## SC/APC 3.0mm CONNECTOR



SC/APC connector which is in accordance with IEC 61754-4. Its performance meets with all the requirement of GR-326-CORE.

### SPECIFICATIONS

Type (mm)	3.0
Insertion Loss (IL)	<0.3dB
Return Loss (RL)	>60dB
Ferrule ID	0.125 $\mu$ m
Per Angle (°)	8°
Body Color	Green
Boot Color	Green

### ORDERING INFORMATION

Z1MDUSMDFYAYA31	MDU Drop fiber, Simplex, SM, ZBL, Riser, 3mm, 31 Meters (100 feet), on spool, SC/APC, connector on inside leg
Z1MDUSMDFYAYA61	MDU Drop fiber, Simplex, SM, ZBL, Riser, 3mm, 61 Meters (200 feet), on spool, SC/APC, connector on inside leg
Z1MDUSMDFYAYA92	MDU Drop fiber, Simplex, SM, ZBL, Riser, 3mm, 92 Meters (300 feet), on spool, SC/APC, connector on inside leg
Z1MDUSMDFYAYA153	MDU Drop fiber, Simplex, SM, ZBL, Riser, 3mm, 153 Meters (500 feet), on spool, SC/APC, connector on inside leg
Z1MDUSMDFLALA31	MDU Drop fiber, Simplex, SM, ZBL, Riser, 3mm, 31 Meters (100 feet), on spool, LC/APC, connector on inside leg
Z1MDUSMDFLALA61	MDU Drop fiber, Simplex, SM, ZBL, Riser, 3mm, 61 Meters (200 feet), on spool, LC/APC, connector on inside leg
Z1MDUSMDFLALA92	MDU Drop fiber, Simplex, SM, ZBL, Riser, 3mm, 92 Meters (300 feet), on spool, LC/APC, connector on inside leg
Z1MDUSMDFLALA153	MDU Drop fiber, Simplex, SM, ZBL, Riser, 3mm, 153 Meters (500 feet), on spool, LC/APC, connector on inside leg



FTTx Solution