

DESCRIPTION

PTFE based thread sealant.

TEMPERATURE RANGE

-50°F to 400°F.

FEATURES

Non-Hardening, Non-Dripping, Corrosion Inhibiting, Self-Lubricating, Non-Seizing Allows Disassembly Contains No Solvents, Non-Staining.

CHARACTERISTICS

This is a non-curing compound with good lubricity and low friction characteristics. High Performance Thread Sealant. Easy to apply.

CHEMICAL COMPATIBILITY

Excellent, Inert to most solvents, acids, chemicals. For use on Chlorine Service.

SHELF LIFE

Unlimited.

PACKAGED

8 oz.

SAFETY

Due to the reactive nature of Chlorine, care should be taken not to contaminate sealant.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.
CONSULT SDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE. **NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Limited_Warranty_At_Delivery_Deacon.pdf You can also email us at sales@jetlube.com