

DESCRIPTION

PTFE based thread sealant.

TEMPERATURE RANGE

-50°F to 400°F.

FEATURES

Non-Hardening, Non-Dripping, Corrosion Inhibiting, Self-Lubricating, Non-Seizing Allows Disassembly Contains No Solvents, Non-Staining.

CHARACTERISTICS

This is a non-curing compound with good lubricity and low friction characteristics. High Performance Thread Sealant. Easy to apply.

CHEMICAL COMPATIBILITY

Excellent, Inert to most solvents, acids, chemicals. For use on Oxygen Service.

SHELF LIFE

2 years in closed containers.

PACKAGED

½ pints.

SAFETY

Due to the reactive nature of oxygen, care should be taken not to contaminate sealant.

Testing by NASA White Sands Test Facility

NASA-STD-6001 (ASTM D 2512) Compatibility of Materials with Liquid Oxygen
(Impact Sensitivity Threshold and Pass-Fail Techniques,) (Test 13A)
100% Liquid Oxygen, 12.4 psia

ASTM G 72-82 Autogenous Ignition Temperature Determination in High Pressure Oxygen (AIT TEST)
100% Oxygen, 1500 psia.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT SDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE. **NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS**

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Limited_Warranty_At_Delivery_Deacon.pdf You can also email us at sales@jetlube.com