

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

SECTION 1. IDENTIFICATION

Product name : C-55
SDS-Identcode : 027G

Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation
Address : 2126 Vanco Drive
Irving TX 75061,
Telephone : 855-243-9164/972-865-8961
Telefax : 214-631-3047
Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887
(24-hours/7 days)
E-mail address : www.bestolife.com

Recommended use of the chemical and restrictions on use


Recommended use : Industrial use
Thread Compound (Pipe Dope) and Jacking grease for use in
Offshore industries
Mining, (without offshore industries)
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-
pheres.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity : Category 2
Reproductive toxicity : Category 1A
Effects on or via lactation
Specific target organ toxicity : Category 1 (Kidney, Central nervous system, Blood)
- repeated exposure

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H351 Suspected of causing cancer.
H360FD May damage fertility. May damage the unborn child.
H362 May cause harm to breast-fed children.
H372 Causes damage to organs (Kidney, Central nervous system, Blood) through prolonged or repeated exposure.

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust, fume, gas, mist, vapors or spray.
P263 Avoid contact during pregnancy and while nursing.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves, protective clothing, eye protection and face protection.
Response:
P308 + P313 IF exposed or concerned: Get medical attention.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Lead	7439-92-1	>= 50 - < 70
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 20 - < 30
Talc	14807-96-6	>= 5 - < 10
Graphite	7782-42-5	>= 1 - < 5
Dolomite	16389-88-1	>= 1 - < 5
12-Hydroxy lithium stearate	7620-77-1	>= 1 - < 5
Quartz	14808-60-7	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

- In case of eye contact : Wash clothing before reuse.
Thoroughly clean shoes before reuse.
: Flush eyes with water as a precaution.
 - If swallowed : Get medical attention if irritation develops and persists.
: If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
 - Most important symptoms and effects, both acute and delayed : Suspected of causing cancer.
May damage fertility. May damage the unborn child.
May cause harm to breast-fed children.
Causes damage to organs through prolonged or repeated exposure.
 - Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
 - Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
 - Unsuitable extinguishing media : None known.
 - Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
 - Hazardous combustion products : Lead compounds
Carbon oxides
Metal oxides
 - Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
 - Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
 Date of first issue: 04/29/2015

disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : For outdoor use only
 Avoid contact during pregnancy and while nursing.
 Do not get on skin or clothing.
 Do not breathe dust, fume, gas, mist, vapors or spray.
 Do not swallow.
 Avoid contact with eyes.
 Wash skin thoroughly after handling.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Keep container tightly closed.
 Do not eat, drink or smoke when using this product.
 Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
 Store locked up.
 Keep tightly closed.
 Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents
 Organic peroxides
 Explosives
 Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Lead	7439-92-1	TWA	0.05 mg/m ³ (Lead)	ACGIH
		PEL	0.05 mg/m ³ (Lead)	OSHA CARC
		TWA	0.05 mg/m ³ (Lead)	NIOSH REL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL

SAFETY DATA SHEET



C-55

Version
17.0

Revision Date:
10/20/2020

SDS Number:
104371-00023

Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

		ST (Mist)	10 mg/m ³	NIOSH REL
Talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
Graphite	7782-42-5	TWA (Respirable)	2.5 mg/m ³	NIOSH REL
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
Dolomite	16389-88-1	TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
12-Hydroxy lithium stearate	7620-77-1	TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	3 mg/m ³	ACGIH
Quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL
		PEL (respirable)	0.05 mg/m ³	OSHA CARC

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

II

Quartz

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
 Date of first issue: 04/29/2015

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
Lead	7439-92-1	Lead (Lead)	In blood	Not criti-cal	200 µg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

See 29 CFR 1910.1025 for additional requirements relating to lead exposure.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Viscous semi-solid

Color : black

Odor : Petroleum

Odor Threshold : No data available

pH : Not applicable (not an aqueous solution)

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : ≥ 392 °F / ≥ 200 °C
Method: ASTM D 92, Cleveland open cup
Distillates (petroleum), hydrotreated heavy naphthenic

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 2.3

Density : No data available

Solubility(ies)
Water solubility : negligible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Lead:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

	Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials
Talc:	
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
Graphite:	
Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 423 Assessment: The substance or mixture has no acute oral toxicity
Acute inhalation toxicity	: LC50 (Rat): > 2 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403
Dolomite:	
Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 420 Assessment: The substance or mixture has no acute oral toxicity Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 3 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials
12-Hydroxy lithium stearate:	
Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Assessment: The substance or mixture has no acute oral toxicity
Quartz:	
Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg

C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

Skin corrosion/irritation

Not classified based on available information.

Components:**Lead:**

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Talc:

Species : Rabbit
Result : No skin irritation

Graphite:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Dolomite:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

12-Hydroxy lithium stearate:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Lead:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit
Result : No eye irritation

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 05/04/2020
17.0	10/20/2020	104371-00023	Date of first issue: 04/29/2015

Remarks : Based on data from similar materials

Talc:

Species : Rabbit
 Result : No eye irritation

Graphite:

Species : Rabbit
 Result : No eye irritation
 Method : OECD Test Guideline 405

Dolomite:

Species : Rabbit
 Result : No eye irritation
 Method : OECD Test Guideline 405
 Remarks : Based on data from similar materials

12-Hydroxy lithium stearate:

Species : Rabbit
 Result : No eye irritation
 Remarks : Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Lead:**

Test Type : Maximization Test
 Routes of exposure : Skin contact
 Species : Guinea pig
 Method : OECD Test Guideline 406
 Result : negative
 Remarks : Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type : Buehler Test
 Routes of exposure : Skin contact
 Species : Guinea pig
 Result : negative
 Remarks : Based on data from similar materials

Talc:

Routes of exposure : Skin contact
 Species : Humans
 Result : negative

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 05/04/2020
17.0	10/20/2020	104371-00023	Date of first issue: 04/29/2015

Graphite:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

Dolomite:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative
Remarks	: Based on data from similar materials

12-Hydroxy lithium stearate:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Lead:**

Genotoxicity in vitro	: Test Type: In vitro sister chromatid exchange assay in mammalian cells Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Ingestion Result: positive Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

C-55

Version 17.0	Revision Date: 10/20/2020	SDS Number: 104371-00023	Date of last issue: 05/04/2020 Date of first issue: 04/29/2015
-----------------	------------------------------	-----------------------------	---

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Rat
Application Route: Ingestion
Result: negative

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Dolomite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Suspected of causing cancer.

Product:

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Components:**Lead:**

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : positive
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Mouse

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
 Date of first issue: 04/29/2015

Application Route : Skin contact
 Exposure time : 78 weeks
 Method : OECD Test Guideline 451
 Result : negative

Talc:

Species : Mouse
 Application Route : inhalation (dust/mist/fume)
 Exposure time : 2 Years
 Result : negative

Quartz:

Species : Humans
 Application Route : inhalation (dust/mist/fume)
 Result : positive
 Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

IARC	Group 1: Carcinogenic to humans	
	Quartz (Silica dust, crystalline)	14808-60-7
	Group 2B: Possibly carcinogenic to humans	
	Lead	7439-92-1
OSHA	OSHA specifically regulated carcinogen	
	Lead (Lead and inorganic lead compounds)	7439-92-1
	OSHA specifically regulated carcinogen	
	Quartz (crystalline silica)	14808-60-7
NTP	Reasonably anticipated to be a human carcinogen	
	Lead	7439-92-1
	Known to be human carcinogen	
	Quartz (Silica, Crystalline (Respirable Size))	14808-60-7

Reproductive toxicity

May damage fertility. May damage the unborn child.
 May cause harm to breast-fed children.

Components:

Lead:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
 Species: Mouse
 Application Route: Ingestion
 Result: positive
 Remarks: Based on data from similar materials

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: positive
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Positive evidence of adverse effects on sexual function and fertility from human epidemiological studies., Positive evidence of adverse effects on development from human epidemiological studies., Studies indicating a hazard to babies during the lactation period

Talc:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Dolomite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 05/04/2020
17.0	10/20/2020	104371-00023	Date of first issue: 04/29/2015

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Kidney, Central nervous system, Blood) through prolonged or repeated exposure.

Components:**Lead:**

Target Organs	:	Kidney, Central nervous system, Blood
Assessment	:	Causes damage to organs through prolonged or repeated exposure.

12-Hydroxy lithium stearate:

Routes of exposure	:	Ingestion
Assessment	:	No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Quartz:

Routes of exposure	:	inhalation (dust/mist/fume)
Target Organs	:	Lungs
Assessment	:	Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity**Components:****Lead:**

Species	:	Rat
NOAEL	:	0.0015 mg/kg
LOAEL	:	0.005 mg/kg
Application Route	:	Ingestion
Exposure time	:	6 - 12 Months
Remarks	:	Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Species	:	Rat
NOAEL	:	> 0.98 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	28 Days
Remarks	:	Based on data from similar materials

Dolomite:

Species	:	Mouse
NOAEL	:	1,300 mg/kg
Application Route	:	Ingestion
Exposure time	:	28 Days
Remarks	:	Based on data from similar materials

C-55

Version	Revision Date:	SDS Number:	Date of last issue: 05/04/2020
17.0	10/20/2020	104371-00023	Date of first issue: 04/29/2015

12-Hydroxy lithium stearate:

Species	: Rat
NOAEL	: > 88 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Quartz:

Species	: Humans
LOAEL	: 0.053 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Remarks	: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Lead:**

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 0.107 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Ceriodaphnia dubia (water flea)): 0.029 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.025 mg/l Exposure time: 72 h
	: EC10 (Pseudokirchneriella subcapitata (green algae)): 6.1 µg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: EC10 (Pimephales promelas (fathead minnow)): 20 µg/l Exposure time: 30 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: EC10 (Ceriodaphnia dubia (water flea)): 1.7 µg/l Exposure time: 7 d

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Remarks: Based on data from similar materials

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
 Date of first issue: 04/29/2015

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d
 Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
 Exposure time: 10 min
 Remarks: Based on data from similar materials

Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l
 Exposure time: 24 h

Graphite:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
 Exposure time: 96 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209

Dolomite:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 16.6 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203
 Remarks: No toxicity at the limit of solubility.
 Based on data from similar materials

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 16.6 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility.
Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Quartz:

Ecotoxicology Assessment

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

12-Hydroxy lithium stearate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Bioaccumulative potential

No data available

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead)
Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s. (Lead)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Lead)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

SAFETY DATA SHEET



C-55

Version 17.0 Revision Date: 10/20/2020 SDS Number: 104371-00023 Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

California Prop. 65

WARNING: This product can expose you to chemicals including Lead, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Lead	7439-92-1
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Talc	14807-96-6
Graphite	7782-42-5

California Permissible Exposure Limits for Chemical Contaminants

Lead	7439-92-1
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Talc	14807-96-6
Graphite	7782-42-5

California Regulated Carcinogens

Lead	7439-92-1
Quartz	14808-60-7

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

AICS : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET



C-55


Version
17.0

Revision Date:
10/20/2020

SDS Number:
104371-00023

Date of last issue: 05/04/2020
Date of first issue: 04/29/2015

NFPA 704:



HMIS® IV:

HEALTH	*	4
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to

SAFETY DATA SHEET



C-55

Version 17.0	Revision Date: 10/20/2020	SDS Number: 104371-00023	Date of last issue: 05/04/2020 Date of first issue: 04/29/2015
-----------------	------------------------------	-----------------------------	---

50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/20/2020

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8