



## **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

#### **SECTION 1. IDENTIFICATION**

Product name : COPPER ROCK

SDS-Identcode : 304G

#### Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation Address : 2126 Vanco Drive

Irving TX 75061,

Telephone : 855-243-9164/972-865-8961

Telefax : 214-631-3047

Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887

(24-hours/7 days)

E-mail address : www.bestolife.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Industrial use

Thread Compound (Pipe Dope) and Jacking grease for use in

Offshore industries

Mining, (without offshore industries)

Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-

pheres.

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Eye irritation : Category 2A

Skin sensitization : Category 1

#### **GHS** label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Precautionary Statements : Prevention:

P261 Avoid breathing dust, fume, gas, mist, vapors or spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves, eye protection and face protec-

tion.





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical atten-

tion.

P337 + P313 If eye irritation persists: Get medical attention.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### Components

| Chemical name                          | CAS-No.    | Concentration (% w/w) |
|--|------------|-----------------------|
| Distillates (petroleum), hydrotreated  | 64742-54-7 | >= 30 - < 50          |
| heavy paraffinic                       |            |                       |
| Distillates (petroleum), hydrotreated  | 64742-52-5 | >= 20 - < 30          |
| heavy naphthenic                       |            |                       |
| Graphite                               | 7782-42-5  | >= 10 - < 20          |
| Copper metal powder                    | 7440-50-8  | >= 10 - < 20          |
| Talc                                   | 14807-96-6 | >= 10 - < 20          |
| Dilithium azelate                      | 38900-29-7 | >= 5 - < 10           |
| Calcium oxide                          | 1305-78-8  | >= 1 - < 5            |
| Dolomite                               | 16389-88-1 | >= 1 - < 5            |
| Tris[bis(2-                            | 15991-76-1 | >= 1 - < 5            |
| ethylhexyl)dithiocarbamato-S,S']       |            |                       |
| antimony                               |            |                       |
| Antimony, dialkyl dithiocarbamate      | 15890-25-2 | >= 1 - < 5            |
| Quartz                                 | 14808-60-7 | >= 1 - < 5            |
| 2,5-Bis(octyldithio)-1,3,4-thiadiazole | 13539-13-4 | >= 0.1 - < 1          |
| Benzenesulphonic acid, propenated,     | 68610-84-4 | >= 0.1 - < 1          |
| calcium salts, overbased               |            |                       |

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.





Version **Revision Date:** SDS Number: Date of last issue: 05/06/2020 11/04/2020 120330-00016 Date of first issue: 05/19/2015 11.0

In case of skin contact In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of contact, immediately flush eyes with plenty of water In case of eye contact

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting. If swallowed

> Get medical attention if symptoms occur. Rinse mouth thoroughly with water. May cause an allergic skin reaction.

Most important symptoms and effects, both acute and

Protection of first-aiders

delayed

Causes serious eye irritation.

First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Treat symptomatically and supportively. Notes to physician

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical None known.

Unsuitable extinguishing

media

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides Metal oxides

Nitrogen oxides (NOx)

Sulfur oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

Ш

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Advice on safe handling : For outdoor use only

Do not get on skin or clothing.

Avoid breathing dust, fume, gas, mist, vapors or spray.

Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

| Components   | CAS-No.    | Value type<br>(Form of<br>exposure)          | Control parameters / Permissible concentration | Basis     |
|--|------------|--|--|-----------|
| Distillates (petroleum), hydrotreated heavy paraffinic | 64742-54-7 | TWA (Mist)                                   | 5 mg/m³  | OSHA Z-1  |
|  |            | TWA (Mist)                                   | 5 mg/m³  | NIOSH REL |
|  |            | ST (Mist)                                    | 10 mg/m <sup>3</sup>                           | NIOSH REL |
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | TWA (Mist)                                   | 5 mg/m³  | OSHA Z-1  |
|  |            | TWA (Inhal-<br>able particu-<br>late matter) | 5 mg/m³  | ACGIH     |
|  |            | TWA (Mist)                                   | 5 mg/m <sup>3</sup>                            | NIOSH REL |
|  |            | ST (Mist)                                    | 10 mg/m <sup>3</sup>                           | NIOSH REL |
| Graphite   | 7782-42-5  | TWA (Respirable)                             | 2.5 mg/m³                                      | NIOSH REL |
|  |            | TWA (Respirable particulate mat-             | 2 mg/m³  | ACGIH     |



# **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

|  |            | ter)                                |   |           |
|--|------------|-------------------------------------|---|-----------|
|  |            | TWA (Dust)                          | 15 Million<br>particles per cubic<br>foot | OSHA Z-3  |
| Copper metal powder  | 7440-50-8  | TWA (Dust and mist)                 | 1 mg/m³<br>(Copper)                       | ACGIH     |
|  |            | TWA<br>(Fumes)                      | 0.2 mg/m³<br>(Copper)                     | ACGIH     |
|  |            | TWA (Dust)                          | 1 mg/m³<br>(Copper)                       | NIOSH REL |
|  |            | TWA (Mist)                          | 1 mg/m³<br>(Copper)                       | NIOSH REL |
|  |            | TWA (dusts and mists)               | 1 mg/m <sup>3</sup><br>(Copper)           | OSHA Z-1  |
|  |            | TWA<br>(Fumes)                      | 0.1 mg/m³<br>(Copper)                     | OSHA Z-1  |
| Talc   | 14807-96-6 | TWA (Dust)                          | 20 Million<br>particles per cubic<br>foot | OSHA Z-3  |
|  |            | TWA (Respirable)                    | 2 mg/m³                                   | NIOSH REL |
|  |            | TWA (Respirable particulate matter) | 2 mg/m³                                   | ACGIH     |
| Calcium oxide  | 1305-78-8  | TWA                                 | 2 mg/m³                                   | ACGIH     |
|  |            | TWA                                 | 2 mg/m³                                   | NIOSH REL |
|  |            | TWA                                 | 5 mg/m³                                   | OSHA Z-1  |
| Dolomite   | 16389-88-1 | TWA (Respirable)                    | 5 mg/m³<br>(Calcium car-<br>bonate)       | NIOSH REL |
|  |            | TWA (total)                         | 10 mg/m³<br>(Calcium car-<br>bonate)      | NIOSH REL |
| Tris[bis(2-<br>ethylhexyl)dithiocarbamato-<br>S,S'] antimony | 15991-76-1 | TWA                                 | 0.5 mg/m³<br>(antimony)                   | OSHA Z-1  |
| , 1  |            | TWA                                 | 0.5 mg/m <sup>3</sup> (antimony)          | ACGIH     |
|  |            | TWA                                 | 0.5 mg/m <sup>3</sup> (antimony)          | NIOSH REL |
| Antimony, dialkyl dithiocarbamate                            | 15890-25-2 | TWA                                 | 0.5 mg/m <sup>3</sup> (antimony)          | OSHA Z-1  |
|  |            | TWA                                 | 0.5 mg/m <sup>3</sup> (antimony)          | ACGIH     |
|  |            | TWA                                 | 0.5 mg/m <sup>3</sup> (antimony)          | NIOSH REL |
| Quartz   | 14808-60-7 | TWA (Respirable dust)               | 0.05 mg/m <sup>3</sup>                    | OSHA Z-1  |
|  |            | TWA (respirable)                    | 10 mg/m3<br>/ %SiO2+2                     | OSHA Z-3  |
|  |            | TWA (respirable)                    | 250 mppcf<br>/ %SiO2+5                    | OSHA Z-3  |





## **COPPER ROCK**

| Version | Revision Date: | SDS Number:  | Date of last issue: 05/06/2020  |
|---------|----------------|--------------|---------------------------------|
| 11.0    | 11/04/2020     | 120330-00016 | Date of first issue: 05/19/2015 |

| TWA (Respirable particulate matter) | 0.025 mg/m³<br>(Silica) | ACGIH     |
|-------------------------------------|-------------------------|-----------|
| TWA (Respirable dust)               | 0.05 mg/m³<br>(Silica)  | NIOSH REL |
| PEL (respirable)                    | 0.05 mg/m <sup>3</sup>  | OSHA CARC |

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Quartz

П

**Engineering measures** : Minimize workplace exposure concentrations.

Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m3 - total dust, 5 mg/m3 - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m3 - respirable particles, 10 mg/m3 -

inhalable particles.

## Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective



# **COPPER ROCK**

Version **Revision Date:** SDS Number: Date of last issue: 05/06/2020 11/04/2020 120330-00016 Date of first issue: 05/19/2015 11.0

clothing (gloves, aprons, boots, etc).

Hygiene measures If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Viscous semi-solid Appearance

Color copper

Odor Petroleum

Odor Threshold No data available

pΗ Not applicable (not an aqueous solution)

Melting point/freezing point No data available

Initial boiling point and boiling

range

No data available

>= 399 °F / >= 204 °C Flash point

Method: ASTM D 92, Cleveland open cup

Distillates (petroleum), hydrotreated heavy naphthenic

Evaporation rate Not applicable

Flammability (solid, gas) Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure Not applicable

Relative vapor density Not applicable

Relative density

Density No data available

Solubility(ies)

Water solubility negligible

Partition coefficient: n-

octanol/water

Autoignition temperature No data available

Not applicable



## **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reac- : Can react with strong oxidizing agents.

tions

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Skin contact Ingestion Eye contact

#### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

## **Components:**

## Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist



## **COPPER ROCK**

Version Revision Date: SDS Number: Date of last issue: 05/06/2020 11.0 11/04/2020 120330-00016 Date of first issue: 05/19/2015

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

**Graphite:** 

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Copper metal powder:

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 5.11 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal



## **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

toxicity

Talc:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Dilithium azelate:

Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg

Method: OECD Test Guideline 420

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Calcium oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 425

Acute inhalation toxicity : (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

**Dolomite:** 

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony:



## **COPPER ROCK**

Version Revision Date: SDS Number: Date of last issue: 05/06/2020 11.0 11/04/2020 120330-00016 Date of first issue: 05/19/2015

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 3.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Benzenesulphonic acid, propenated, calcium salts, overbased:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 1.9 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

**Components:** 

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials



## **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials

**Graphite:** 

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Copper metal powder:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Talc:

Species : Rabbit

Result : No skin irritation

Dilithium azelate:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Remarks : Based on data from similar materials

Result : No skin irritation

Calcium oxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Remarks : Based on data from similar materials

**Dolomite:** 

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Benzenesulphonic acid, propenated, calcium salts, overbased:

Species : Rabbit

Result : No skin irritation

Remarks : Based on data from similar materials



# **COPPER ROCK**

Version Revision Date: SDS Number: Date of last issue: 05/06/2020 11.0 11/04/2020 120330-00016 Date of first issue: 05/19/2015

#### Serious eye damage/eye irritation

Causes serious eye irritation.

**Product:** 

Result : Irritation to eyes, reversing within 21 days

#### **Components:**

# Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

## Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit

Result : No eye irritation

Remarks : Based on data from similar materials

Graphite:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Copper metal powder:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Talc:

Species : Rabbit

Result : No eye irritation

Dilithium azelate:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Calcium oxide:

Species : Rabbit

Result : Irreversible effects on the eye Method : OECD Test Guideline 405

Dolomite:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials



## **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

# 2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

## Benzenesulphonic acid, propenated, calcium salts, overbased:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified based on available information.

#### **Components:**

#### Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Remarks : Based on data from similar materials

## Distillates (petroleum), hydrotreated heavy naphthenic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

#### **Graphite:**

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact
Species : Mouse
Result : negative

## Copper metal powder:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative



# **COPPER ROCK**

Version Revision Date: SDS Number: Date of last issue: 05/06/2020 11.0 11/04/2020 120330-00016 Date of first issue: 05/19/2015

Talc:

Routes of exposure : Skin contact
Species : Humans
Result : negative

Dilithium azelate:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

Calcium oxide:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

**Dolomite:** 

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : positive

Assessment : Probability or evidence of high skin sensitization rate in

humans

Benzenesulphonic acid, propenated, calcium salts, overbased:

Test Type : Human repeat insult patch test (HRIPT)

Routes of exposure : Skin contact Result : positive

Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitization in humans

#### Germ cell mutagenicity

Not classified based on available information.





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

#### **Components:**

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Graphite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Copper metal powder:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Method: Directive 67/548/EEC, Annex V, B.12.

Result: negative

Remarks: Based on data from similar materials





Version Revision Date: SDS Number: Date of last issue: 05/06/2020 11.0 11/04/2020 120330-00016 Date of first issue: 05/19/2015

Talc:

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro

Species: Rat

**Application Route: Ingestion** 

Result: negative

Dilithium azelate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Calcium oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Dolomite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: equivocal

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Benzenesulphonic acid, propenated, calcium salts, overbased:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

**Product:** 

Carcinogenicity - Assess-

ment

: Petroleum distillates have been classified as not carcinogenic

based on DMSO extract content < 3% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note L).





Version **Revision Date:** SDS Number: Date of last issue: 05/06/2020 11/04/2020 120330-00016 Date of first issue: 05/19/2015 11.0

## **Components:**

## Distillates (petroleum), hydrotreated heavy paraffinic:

Species Mouse Application Route
Exposure time Skin contact : 78 weeks

: OECD Test Guideline 451 Method

Result : negative

Remarks Based on data from similar materials

## Distillates (petroleum), hydrotreated heavy naphthenic:

Species Mouse Application Route Skin contact Exposure time 78 weeks

**OECD Test Guideline 451** Method

Result negative

Talc:

Species : Mouse

Application Route : inhalation (dust/mist/fume)

Exposure time 2 Years Result : negative

Calcium oxide:

Species Rat Application Route Ingestion Exposure time 104 weeks Result : negative

Remarks Based on data from similar materials

Quartz:

Species Humans

Application Route inhalation (dust/mist/fume)

Result positive

These substance(s) are inextricably bound in the product and Remarks

therefore do not contribute to a dust inhalation hazard.

Positive evidence from human epidemiological studies (inhala-Carcinogenicity - Assess-

ment tion)

**IARC** Group 1: Carcinogenic to humans

> Quartz 14808-60-7

(Silica dust, crystalline)

**OSHA** OSHA specifically regulated carcinogen

14808-60-7 Quartz

(crystalline silica)

Known to be human carcinogen

Quartz 14808-60-7





# **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

(Silica, Crystalline (Respirable Size))

## Reproductive toxicity

Not classified based on available information.

#### **Components:**

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

**Application Route: Ingestion** 

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Skin contact Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

**Graphite:** 

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Copper metal powder:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rabbit

Application Route: Ingestion

Result: negative

Talc:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat



## **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

Application Route: Ingestion

Result: negative

Dilithium azelate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Skin contact

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Skin contact

Result: negative

Remarks: Based on data from similar materials

Calcium oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

**Dolomite:** 

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Antimony, dialkyl dithiocarbamate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the



## **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

#### 2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

## Benzenesulphonic acid, propenated, calcium salts, overbased:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 415

Result: negative

Remarks: Based on data from similar materials

#### STOT-single exposure

Not classified based on available information.

#### **Components:**

## Calcium oxide:

Assessment : May cause respiratory irritation.

# STOT-repeated exposure

Not classified based on available information.

## **Components:**

#### Quartz:

Routes of exposure : inhalation (dust/mist/fume)

Target Organs : Lungs

Assessment : Shown to produce significant health effects in animals at con-

centrations of 0.02 mg/l/6h/d or less.



## **COPPER ROCK**

Version **Revision Date:** SDS Number: Date of last issue: 05/06/2020 11/04/2020 120330-00016 Date of first issue: 05/19/2015 11.0

#### Repeated dose toxicity

#### **Components:**

## Distillates (petroleum), hydrotreated heavy paraffinic:

Species Rabbit NOAEL 1,000 mg/kg Application Route Skin contact Exposure time 4 Weeks

Method **OECD Test Guideline 410** 

Remarks Based on data from similar materials

Species Rat

Species NOAEL Application Route  $> 980 \text{ mg/m}^3$ 

: inhalation (dust/mist/fume)

Exposure time 4 Weeks

# Distillates (petroleum), hydrotreated heavy naphthenic:

Species Rat

NOAEL > 0.98 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 28 Days

Remarks Based on data from similar materials

## Copper metal powder:

Species Rat

NOAEL :  $>= 2 \text{ mg/m}^3$ 

Application Route inhalation (dust/mist/fume)

Exposure time : 28 Days

## Dilithium azelate:

Species Rat

NOAEL 1,089.75 mg/kg Application Route Skin contact Exposure time 28 Davs

Remarks Based on data from similar materials

# Calcium oxide:

Species Rat

NOAEL >= 0.399 mg/l

Application Route inhalation (dust/mist/fume)

Exposure time

Method **OECD Test Guideline 413** 

## **Dolomite:**

Species Mouse NOAEL 1,300 mg/kg Application Route Ingestion Exposure time 28 Days

Remarks Based on data from similar materials



## **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

## Antimony, dialkyl dithiocarbamate:

Species : Ra

NOAEL : >= 1,000 mg/kg
Application Route : Ingestion

Exposure time : 54 Days

Quartz:

Species : Humans LOAEL : 0.053 mg/m³

Application Route : inhalation (dust/mist/fume)

Remarks : These substance(s) are inextricably bound in the product and

therefore do not contribute to a dust inhalation hazard.

## 2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Species : Rat

NOAEL : 330 mg/kg Application Route : Ingestion Exposure time : 54 Days

Method : OECD Test Guideline 422

## Benzenesulphonic acid, propenated, calcium salts, overbased:

Species : Rat

NOAEL : > 300 mg/kg
Application Route : Ingestion
Exposure time : 29 Days

Method : OECD Test Guideline 407

Remarks : Based on data from similar materials

Species : Rat

NOAEL : > 600 mg/kg
Application Route : Skin contact
Exposure time : 28 Days

Method : OECD Test Guideline 410

Remarks : Based on data from similar materials

# **Aspiration toxicity**

Not classified based on available information.

#### **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

#### **Components:**

# Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l

Exposure time: 10 min Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l

Exposure time: 10 min

Remarks: Based on data from similar materials

Graphite:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction



# BESTOLIFE PREMIUM COMPOUNDS

## **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

: EL50 (Pseudokirchneriella subcapitata (green algae)): > 100

plants

mg/l Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): >

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Copper metal powder:

Toxicity to fish : LC50:  $> 10 - 100 \mu g/l$ 

Exposure time: 96 h

Toxicity to fish (Chronic tox-

icity)

: NOEC:  $> 1 - 10 \mu g/I$ 

Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l

Exposure time: 24 h

Dilithium azelate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

Calcium oxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Crangon crangon (shrimp)): > 1 mg/l

Exposure time: 14 d

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

**Dolomite:** 

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 16.6 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility.

Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 16.6 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility.

Based on data from similar materials

Toxicity to algae/aquatic

plants

NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony:

Toxicity to daphnia and other : aquatic invertebrates (Chron-

Exposure time: 21 d

ic toxicity)

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

NOEC (Daphnia magna (Water flea)): 0.02 mg/l





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

**Ecotoxicology Assessment** 

Chronic aquatic toxicity : Very toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

Antimony, dialkyl dithiocarbamate:

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.02 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

**Ecotoxicology Assessment** 

Chronic aquatic toxicity : Very toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

Quartz:

**Ecotoxicology Assessment** 

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 45 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

LL50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 1

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,000 mg/l

Exposure time: 3 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 209

Benzenesulphonic acid, propenated, calcium salts, overbased:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h



## **COPPER ROCK**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l

Exposure time: 8 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

## Persistence and degradability

#### **Components:**

## Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

#### Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

## Dilithium azelate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 83 % Exposure time: 30 d

Method: OECD Test Guideline 301D

Remarks: Based on data from similar materials

## Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony:

Biodegradability : Result: Not readily biodegradable.

Remarks: Based on data from similar materials





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

Antimony, dialkyl dithiocarbamate:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 20 % Exposure time: 28 d

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Benzenesulphonic acid, propenated, calcium salts, overbased:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301D

Method. OECD Test Guideline 301D

Remarks: Based on data from similar materials

Bioaccumulative potential

**Components:** 

Dilithium azelate:

Partition coefficient: n- : log Pow: -3.53

octanol/water

2,5-Bis(octyldithio)-1,3,4-thiadiazole:

Partition coefficient: n- : log Pow: > 6.5

octanol/water Method: OECD Test Guideline 117

Benzenesulphonic acid, propenated, calcium salts, overbased:

Partition coefficient: n- : log Pow: > 4

octanol/water Remarks: Expert judgment

Mobility in soil

No data available

Other adverse effects

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or

death.

If not otherwise specified: Dispose of as unused product.





Version Revision Date: SDS Number: Date of last issue: 05/06/2020 11.0 11/04/2020 120330-00016 Date of first issue: 05/19/2015

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

**UNRTDG** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper metal powder, Tris[bis(2-ethylhexyl)dithiocarbamato-

S,S'] antimony)

Class : 9
Packing group : III
Labels : 9

**IATA-DGR** 

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Copper metal powder, Tris[bis(2-ethylhexyl)dithiocarbamato-

S,S'] antimony)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 956

aircraft)

Packing instruction (passen-

ger aircraft)

Environmentally hazardous : yes

**IMDG-Code** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

956

(Copper metal powder, Tris[bis(2-ethylhexyl)dithiocarbamato-

S,S'] antimony)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Copper metal powder, Tris[bis(2-ethylhexyl)dithiocarbamato-

S,S'] antimony)

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171

Marine pollutant : yes(Copper metal powder, Tris[bis(2-

ethylhexyl)dithiocarbamato-S,S'] antimony)





Version Revision Date: SDS Number: Date of last issue: 05/06/2020 11.0 11/04/2020 120330-00016 Date of first issue: 05/19/2015

Remarks : Above applies only to containers over 119 gallons or 450

liters.

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

#### **CERCLA Reportable Quantity**

| Components          | CAS-No.   | Component RQ | Calculated product RQ |
|---------------------|-----------|--------------|-----------------------|
|                     |           | (lbs)        | (lbs)                 |
| Copper metal powder | 7440-50-8 | 5000         | 38166                 |

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Copper metal 7440-50-8 >= 10 - < 20 %

powder

Tris[bis(2- 15991-76-1 >= 1 - < 5 %

ethylhex-

yl)dithiocarbamat o-S,S'] antimony

Antimony, dialkyl 15890-25-2 >= 1 - < 5 %

dithiocarbamate

## **US State Regulations**

#### Pennsylvania Right To Know

| • |  |            |
|---|--|------------|
|   | Distillates (petroleum), hydrotreated heavy paraffinic | 64742-54-7 |
|   | Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 |
|   | Graphite   | 7782-42-5  |
|   | Copper metal powder                                    | 7440-50-8  |
|   | Talc   | 14807-96-6 |
|   | Hydroxystearate sebacate lithium complexes             | 68815-49-6 |
|   | Dilithium azelate                                      | 38900-29-7 |
|   | Polybutene   | 9003-29-6  |
|   | Isobutylene-butene copolymer                           | 9044-17-1  |
|   | Calcium oxide  | 1305-78-8  |
|   | Water  | 7732-18-5  |
|   | Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony   | 15991-76-1 |
|   |  |            |



# **COPPER ROCK**

Version Revision Date: SDS Number: Date of last issue: 05/06/2020 11.0 11/04/2020 120330-00016 Date of first issue: 05/19/2015

Antimony, dialkyl dithiocarbamate 15890-25-2 Quartz 14808-60-7 Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts 68649-42-3

## California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### California List of Hazardous Substances

| Distillates (petroleum), hydrotreated heavy paraffinic | 64742-54-7 |
|--|------------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 |
| Graphite   | 7782-42-5  |
| Copper metal powder                                    | 7440-50-8  |
| Talc   | 14807-96-6 |
| Calcium oxide  | 1305-78-8  |
| Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony   | 15991-76-1 |
| Antimony, dialkyl dithiocarbamate                      | 15890-25-2 |
|  |            |

#### **California Permissible Exposure Limits for Chemical Contaminants**

| Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), hydrotreated heavy naphthenic Graphite Copper metal powder Talc Calcium oxide Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony Antimony, dialkyl dithiocarbamate Quartz | 64742-54-7 |
|---|------------|
| Distillates (petroleum), hydrotreated heavy naphthenic  | 64742-52-5 |
| Graphite  | 7782-42-5  |
| Copper metal powder   | 7440-50-8  |
| Talc  | 14807-96-6 |
| Calcium oxide   | 1305-78-8  |
| Tris[bis(2-ethylhexyl)dithiocarbamato-S,S'] antimony  | 15991-76-1 |
| Antimony, dialkyl dithiocarbamate   | 15890-25-2 |
| Quartz  | 14808-60-7 |

#### **California Regulated Carcinogens**

Quartz 14808-60-7

#### The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

AICS : All ingredients listed or exempt.

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**






 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/06/2020

 11.0
 11/04/2020
 120330-00016
 Date of first issue: 05/19/2015

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response, Compensation. and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Pre-



# BESTOLIFE PREMIUM COMPOUNDS

## **COPPER ROCK**

Version Revision Date: SDS Number: Date of last issue: 05/06/2020 11.0 11/04/2020 120330-00016 Date of first issue: 05/19/2015

vention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 11/04/2020

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8