



A CSW Industrials Company

SAFETY DATA SHEET

Issuing Date 22-Mar-2018

Revision Date 07-Mar-2019

Revision Number 3



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name GEAR GUARD® AEROSOL

Other means of identification

Product Code(s) 17941

(M)SDS Number 1428425-GEAR

Synonyms JET-LUBE® GEAR GUARD® (Aerosol form), OPEN GEAR LUBE

Recommended use of the chemical and restrictions on use

Recommended Use For industrial use only Lubricants, Greases and Release Products

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Identification Jet-Lube, LLC.

Address Jet Lube LLC
930 Whitmore Drive
Rockwall, Texas USA 75087

Telephone US Office: Phone:+1-972-771-1000 Fax:+1-972-722-2108

E-mail Sales@jetlube.com

Emergency telephone number

Company Emergency Phone Number 1-800-699-6318

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL)
1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

Skin sensitization	Category 1
--------------------	------------



Germ cell mutagenicity	Category 1B
Aspiration toxicity	Category 1
Gases Under Pressure	Compressed Gas

Appearance Black**Physical state** Liquid spray**Odor** Solvent**GHS Label elements, including precautionary statements****Danger****Hazard statements**

May cause an allergic skin reaction

May cause genetic defects

May be fatal if swallowed and enters airways

Contains gas under pressure; may explode if heated

**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Contaminated work clothing must not be allowed out of the workplace

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of water and soap

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Protect from sunlight. Store in a well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Causes mild skin irritation Toxic to aquatic life Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Synonyms

JET-LUBE® GEAR GUARD® (Aerosol form), OPEN GEAR LUBE

Chemical Name	CAS-No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Petroleum gases	68476-85-7	23-28	-	-
Petroleum distillates, hydrotreated light	64742-47-8	20-25	-	-
Asphalt	8052-42-4	20-25	-	-
Petroleum distillates, hydrotreated light naphthenic	64742-53-6	10-15	-	-
Acetone	67-64-1	5-10	-	-
Graphite	7782-42-5	1-5	-	-
1,3,4-Thiadiazole, 2,5-bis(octyldithio)-	13539-13-4	1-5	-	-

4. FIRST AID MEASURES

First aid measures

General advice

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.

Inhalation

Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.

Eye contact

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

Skin contact

In case of contact with liquefied gas, thaw frosted parts with lukewarm water. Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

Ingestion

Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid breathing vapors or mists. See section 8 for more information.

Most important symptoms and effects, both acute and delayed



Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
Specific hazards arising from the chemical	Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket. Product is or contains a sensitizer. May cause sensitization by skin contact.
Hazardous Combustion Products	Carbon oxides.
Explosion Data	
Sensitivity to Mechanical Impact	Yes.
Sensitivity to Static Discharge	None.
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists.
Other Information	Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling



Advice on safe handling

Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Store locked up. Keep out of the reach of children. Store away from other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Limits**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Petroleum gases 68476-85-7	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2000 ppm TWA: 1000 ppm TWA: 1800 mg/m ³	
Petroleum distillates, hydrotreated light 64742-47-8	TWA: 5 mg/m ³ STEL: 10 mg/m ³ (as oil mist)	TWA: 5 mg/m ³ (as oil mist)		
Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene-soluble aerosol fume, inhalable particulate matter	-	Ceiling: 5 mg/m ³ fume 15 min	
Petroleum distillates, hydrotreated light naphthenic 64742-53-6	5 mg/m ³ (as oil mist) 2 mg/m ³ (inhalable)	5 mg/m ³ (as oil mist)		
Acetone 67-64-1	STEL = 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 1800 mg/m ³ (vacated) TWA: 750 ppm (vacated) STEL: 1000 ppm (vacated) STEL: 2400 mg/m ³	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³	
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable particulate matter all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust	
Chemical Name	Alberta	British Columbia	Ontario TWAEV	Quebec
Petroleum gases 68476-85-7	TWA: 1000 ppm STEL: 1500 ppm	TWA: 1000 ppm STEL: 1250 ppm	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³
Petroleum distillates, hydrotreated light 64742-47-8		TWA: 200 mg/m ³ Skin		
Asphalt	TWA: 5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³	TWA: 5 mg/m ³

8052-42-4				
Acetone 67-64-1	TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 750 ppm STEL: 1800 mg/m ³	TWA: 250 ppm STEL: 500 ppm	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm TWA: 1190 mg/m ³ STEL: 1000 ppm STEL: 2380 mg/m ³
Graphite 7782-42-5	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves. Neoprene gloves. Nitrile rubber. Viton™.

Skin and body protection Wear suitable protective clothing. Lightweight protective clothing. Long sleeved clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Liquid spray
Appearance Black
Odor Solvent
Color No information available
Odor Threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks Method</u>
pH	7	
Melting / freezing point	Not applicable	None known
Boiling point / boiling range	>315 °C	None known
Flash Point	> 315 °C	Cleveland Open Cup (COC)
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	1.23	
Water Solubility	Negligible	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water	Not Applicable	
Autoignition temperature	No data available	None known
Decomposition temperature		



Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	1000	
Oxidizing properties	No information available	
Other Information		
Softening Point	No information available	
Molecular Weight	No information available	
VOC Content (%)	No information available	
Liquid Density	No information available	
Bulk Density	No information available	
Particle Size	No information available	
Particle Size Distribution	No information available	

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	Excessive heat.
Incompatible materials	None known based on information supplied.
Hazardous Decomposition Products	Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	Specific test data for the substance or mixture is not available. May cause sensitization by skin contact. (based on components). Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Repeated exposure may cause skin dryness or cracking.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Information on toxicological effects

Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Numerical measures of toxicity



Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	6,450.00 mg/kg
ATEmix (inhalation-dust/mist)	3.80 mg/L

Unknown acute toxicity No information available

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	Inhalation LC50
Petroleum distillates, hydrotreated light	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Asphalt	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 94.4 mg/m ³ (Rat) 4.5 h
Petroleum distillates, hydrotreated light naphthenic	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 2180 mg/m ³ (Rat) 4 h
Acetone	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No information available.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	May cause sensitization by skin contact.
Germ cell mutagenicity	Classification based on data available for ingredients. Contains a known or suspected mutagen.
Carcinogenicity	No information available.
Legend	
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Petroleum distillates, hydrotreated light		96h LC50: = 2.4 mg/L (Oncorhynchus mykiss) 96h LC50: = 45 mg/L (Pimephales promelas) 96h LC50: = 2.2 mg/L (Lepomis macrochirus)	-	96h LC50: = 4720 mg/L
Petroleum distillates, hydrotreated light naphthenic		96h LC50: > 5000 mg/L (Oncorhynchus mykiss)	-	48h EC50: > 1000 mg/L
Acetone		96h LC50: = 8300 mg/L (Lepomis macrochirus) 96h LC50: 6210 - 8120	EC50 = 14500 mg/L 15 min	48h EC50: 10294 - 17704 mg/L 48h EC50: 12600 - 12700 mg/L

		mg/L (Pimephales promelas) 96h LC50: 4.74 - 6.33 mL/L (Oncorhynchus mykiss)		
--	--	-----------------------------------------------------------------------------------	--	--

Persistence and Degradability No information available.

Bioaccumulation

Chemical Name	Log Pow
Petroleum gases	2.8
Asphalt	6
Acetone	-0.24

Mobility No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number U002

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Acetone 67-64-1	Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No. UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.2
Description UN1950, AEROSOLS, 2.2
Emergency Response Guide Number 126

TDG

UN Number UN1950
Proper Shipping Name AEROSOLS
Hazard Class 2.2
Packing Group None
Description UN1950, AEROSOLS, 2.2

MEX



UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.2
Description	UN1950, AEROSOLS, 2.2

ICAO

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.2
Description	UN1950, AEROSOLS, 2.2

IATA

UN Number	UN1950
Proper Shipping Name	AEROSOLS, NON-FLAMMABLE
Hazard Class	2.2
Packing Group	None
ERG Code	2L
Description	UN1950, AEROSOLS, NON-FLAMMABLE, 2.2

IMDG

UN Number	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2
Packing Group	None
EmS-No.	F-D, S-U
Description	UN1950, AEROSOLS, 2.2

RID

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.2
Classification code	5A
Description	UN1950, AEROSOLS, 2.2
ADR/RID-Labels	2.2

ADR

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.2
Classification code	5A
Tunnel restriction code	(E)
Description	UN1950, AEROSOLS, 2.2, (E)

ADN

UN-No.	UN1950
Proper Shipping Name	AEROSOLS
Hazard Class	2.2
Classification code	5A
Special Provisions	190, 327, 344, 625
Description	UN1950, AEROSOLS, 2.2
Hazard Labels	2.2
Limited Quantity	1 L
Ventilation	VE04

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

TSCA	Complies.
DSL/NDSL	Complies.
EINECS/ELINCS	Complies.
ENCS	Complies.
KECL	Complies.
PICCS	Complies.
AICS	Complies.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS-No	Weight-%	SARA 313 - Threshold Values %
Asphalt - 8052-42-4	8052-42-4	20-25	0.1

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone 67-64-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.



U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Petroleum gases 68476-85-7	X	X	X	X	
Asphalt 8052-42-4	X	X	X		X
Petroleum distillates, hydrotreated light naphthenic 64742-53-6		X			X
Acetone 67-64-1	X	X	X	X	
Graphite 7782-42-5	X	X	X		

16. OTHER INFORMATION

NFPA	Health hazards 2	Flammability 4	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2 *	Flammability 4	Physical hazards 0	Personal Protection X
<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>			

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 22-Mar-2018

Revision Date 07-Mar-2019

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

