

DESCRIPTION

Deacon Mold-Pac[™] HD is a Damming, Molding, and Positioning Putty. Formulated as a thicker version of DEACON Mold-Pac[™].

FEATURES

Resistant to extreme temperatures, can be easily and quickly removed, remains flexible and retains molten Babbitt and low melting point materials, easily packed in place, holds tight, Asbestos free. Available in extruded lengths that are easier to get out of the container and reduce prep time/costs.

APPLICATIONS

Damming compound (for pouring Babbitt bearings, epoxies, dielectric fluids, various molten alloys, etc.), Vibration suppression, positioning delicate parts, holding solder while soldering wires on generators, Aids in positioning during welding/brazing.

PACKAGING

Bulk Size: 10 lb. container, 50 lb. pail.
Extruded: 5/8", 3/4", 1", 1 1/8", 1 3/8" dia. (6 lb. pail)

SHELF LIFE

Two years.

FOR INDUSTRIAL USE BY PROFESSIONALLY TRAINED PERSONNEL ONLY.

CONSULT SDS & TECH SHEET FOR ALL SAFETY, TECHNICAL, & WARRANTY INFORMATION BEFORE USE. NOT RECOMMENDED FOR USE ON NUCLEAR APPLICATIONS

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Limited_Warranty_At_Delivery_Deacon.pdf You can also email us at sales@jetlube.com