

SUPR COPR BRUSH-TOP



1 & 2 lb Plastic Container

PRODUCT CHARACTERISTICS

Color:	Copper
Penetration: (ASTM D217)	310-330
NLGI Grade:	1
Weight/Gallon:	10.2 pounds/gallon
Thickener:	Lithium
Fluid Type:	Petroleum
Dropping Point: (ASTM D2265)	≥350°F (≥177°C)
Flash Point:	≥392°F (≥200°C)
Brushable To:	10°F (-12°C)
Shelf Life: (Unopened container)	4 Years
Contains:	Copper, graphite, and other nonmetallic additives

*NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

DESCRIPTION

BESTOLIFE® Supr Copr is a non-lead, non-zinc anti-seize industrial lubricant compound available in small containers with brush top lids. Its high copper content allows it to bear high-pressure stress.

APPLICATIONS

Suited for use on all threaded and flanged connections, studs, bolts and screw threads in high temperature environments.

Applicable materials: most metals, plastic, copper, brass, cast iron, and steel.

Suggested Applications: Battery posts, exhaust system bolts, threads, gears, chains, cables, sprockets, and rollers

TECHNICAL DATA

Supr Copr applies easily in a wide range of temperatures and conditions, is resistant to washout and will not harden or bleed excessively in storage. It's non-hardening consistency allows for easy assembly and disassembly of parts.

PACKAGING

PRODUCT NUMBER	CONTAINER SIZE	CONTAINER WEIGHT
634004	1 pint	1 lb (12/case)
634003	1 quart	2 lb (6/case)

Note: All package sizes are not listed. Call your sales representative for a complete listing.

