

# SAFETY DATA SHEET



## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
Date of first issue: 05/19/2015

---

### SECTION 1. IDENTIFICATION

Product name : WHITE COLLAR

SDS-Identcode : 301G

#### Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation  
Address : 2126 Vanco Drive  
Irving TX 75061,  
Telephone : 855-243-9164/972-865-8961  
Telefax : 214-631-3047  
Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887  
(24-hours/7 days)  
E-mail address : www.bestolife.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Industrial use  
Thread Compound (Pipe Dope) and Jacking grease for use in  
Offshore industries  
Mining, (without offshore industries)  
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-  
pheres.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Eye irritation : Category 2A

Skin sensitization : Category 1

#### GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**  
P261 Avoid breathing dust, fume, gas, mist, vapors or spray.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing must not be allowed out of  
the workplace.  
P280 Wear protective gloves, eye protection and face protec-  
tion.

---

## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P333 + P313 If skin irritation or rash occurs: Get medical attention.  
 P337 + P313 If eye irritation persists: Get medical attention.  
 P363 Wash contaminated clothing before reuse.

**Disposal:**

P501 Dispose of contents and container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 30 - < 50
Zinc oxide	1314-13-2	>= 20 - < 30
Talc	14807-96-6	>= 5 - < 10
Dolomite	16389-88-1	>= 1 - < 5
12-Hydroxy lithium stearate	7620-77-1	>= 1 - < 5
Calcium oxide	1305-78-8	>= 1 - < 5
Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)	57855-77-3	>= 1 - < 5
Quartz	14808-60-7	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
 Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
 Remove contaminated clothing and shoes.  
 Get medical attention.  
 Wash clothing before reuse.  
 Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
 If easy to do, remove contact lens, if worn.  
 Get medical attention.

# SAFETY DATA SHEET



## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
Date of first issue: 05/19/2015

---

- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
Causes serious eye irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Metal oxides  
Fluorine compounds  
Sulfur oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

## SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : For outdoor use only  
 Do not get on skin or clothing.  
 Avoid breathing dust, fume, gas, mist, vapors or spray.  
 Do not swallow.  
 Do not get in eyes.  
 Wash skin thoroughly after handling.  
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
 Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
 Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
 Strong oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
Zinc oxide	1314-13-2	TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (Respirable particulate matter)	2 mg/m <sup>3</sup>	ACGIH
		STEL (Respirable particulate matter)	10 mg/m <sup>3</sup>	ACGIH
		TWA (Dust)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (Fumes)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Fumes)	10 mg/m <sup>3</sup>	NIOSH REL
		C (Dust)	15 mg/m <sup>3</sup>	NIOSH REL
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA	5 mg/m <sup>3</sup>	OSHA Z-1

# SAFETY DATA SHEET



## WHITE COLLAR

Version  
8.0

Revision Date:  
11/04/2020

SDS Number:  
120076-00017

Date of last issue: 05/06/2020  
Date of first issue: 05/19/2015

Talc	14807-96-6	(Fumes)		
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	2 mg/m <sup>3</sup>	NIOSH REL
Dolomite	16389-88-1	TWA (Respirable particulate matter)	2 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable)	5 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
12-Hydroxy lithium stearate	7620-77-1	TWA (Inhalable particulate matter)	10 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable particulate matter)	3 mg/m <sup>3</sup>	ACGIH
Calcium oxide	1305-78-8	TWA	2 mg/m <sup>3</sup>	ACGIH
		TWA	2 mg/m <sup>3</sup>	NIOSH REL
		TWA	5 mg/m <sup>3</sup>	OSHA Z-1
Quartz	14808-60-7	TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL
		PEL (respirable)	0.05 mg/m <sup>3</sup>	OSHA CARC

**These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.**

II

Quartz

### Engineering measures

: Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m<sup>3</sup> - total dust, 5 mg/m<sup>3</sup> - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise

## WHITE COLLAR

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
8.0	11/04/2020	120076-00017	Date of first issue: 05/19/2015

---

Specified of 3 mg/m<sup>3</sup> - respirable particles, 10 mg/m<sup>3</sup> - inhalable particles.

**Personal protective equipment**

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

## Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Contaminated work clothing should not be allowed out of the workplace.  
Wash contaminated clothing before re-use.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: Viscous semi-solid
Color	: light gray
Odor	: Petroleum
Odor Threshold	: No data available
pH	: Not applicable (not an aqueous solution)
Melting point/freezing point	: No data available

# SAFETY DATA SHEET



## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
Date of first issue: 05/19/2015

---

Initial boiling point and boiling range : No data available

Flash point :  $\geq 392$  °F /  $\geq 200$  °C  
Method: ASTM D 92, Cleveland open cup  
Distillates (petroleum), hydrotreated heavy naphthenic

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.3

Solubility(ies)  
Water solubility : negligible

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : Can react with strong oxidizing agents.

## WHITE COLLAR

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
8.0	11/04/2020	120076-00017	Date of first issue: 05/19/2015

Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

## SECTION 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5.53 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402 Remarks: Based on data from similar materials

**Zinc oxide:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5.7 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

**Talc:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Remarks: Based on data from similar materials
---------------------	---	--

**Dolomite:**



## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
 Method: OECD Test Guideline 420  
 Assessment: The substance or mixture has no acute oral toxicity  
 Remarks: Based on data from similar materials
- Acute inhalation toxicity : LC50 (Rat): > 3 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Assessment: The substance or mixture has no acute inhalation toxicity  
 Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
 Method: OECD Test Guideline 402  
 Assessment: The substance or mixture has no acute dermal toxicity  
 Remarks: Based on data from similar materials

**12-Hydroxy lithium stearate:**

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
 Assessment: The substance or mixture has no acute oral toxicity

**Calcium oxide:**

- Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
 Method: OECD Test Guideline 425
- Acute inhalation toxicity : (Rat): > 5 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Method: OECD Test Guideline 436  
 Remarks: Based on data from similar materials
- Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg  
 Method: OECD Test Guideline 402  
 Assessment: The substance or mixture has no acute dermal toxicity  
 Remarks: Based on data from similar materials

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
- Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Quartz:**

- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**WHITE COLLAR**

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
Date of first issue: 05/19/2015

---

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

**Zinc oxide:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

**Talc:**

Species : Rabbit  
Result : No skin irritation

**Dolomite:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

**12-Hydroxy lithium stearate:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

**Calcium oxide:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**WHITE COLLAR**

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
8.0	11/04/2020	120076-00017	Date of first issue: 05/19/2015

---

**Zinc oxide:**

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

**Talc:**

Species	: Rabbit
Result	: No eye irritation

**Dolomite:**

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

**12-Hydroxy lithium stearate:**

Species	: Rabbit
Result	: No eye irritation
Remarks	: Based on data from similar materials

**Calcium oxide:**

Species	: Rabbit
Result	: Irreversible effects on the eye
Method	: OECD Test Guideline 405

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days
Remarks	: Based on data from similar materials

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative
Remarks	: Based on data from similar materials

**Zinc oxide:**

Test Type	: Maximization Test
Routes of exposure	: Skin contact

## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

Species : Guinea pig  
 Method : OECD Test Guideline 406  
 Result : negative

**Talc:**

Routes of exposure : Skin contact  
 Species : Humans  
 Result : negative

**Dolomite:**

Test Type : Local lymph node assay (LLNA)  
 Routes of exposure : Skin contact  
 Species : Mouse  
 Method : OECD Test Guideline 429  
 Result : negative  
 Remarks : Based on data from similar materials

**12-Hydroxy lithium stearate:**

Test Type : Local lymph node assay (LLNA)  
 Routes of exposure : Skin contact  
 Species : Mouse  
 Method : OECD Test Guideline 429  
 Result : negative

**Calcium oxide:**

Test Type : Local lymph node assay (LLNA)  
 Routes of exposure : Skin contact  
 Species : Mouse  
 Method : OECD Test Guideline 429  
 Result : negative  
 Remarks : Based on data from similar materials

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Test Type : Buehler Test  
 Routes of exposure : Skin contact  
 Species : Guinea pig  
 Result : positive  
 Remarks : Based on data from similar materials

Assessment : Probability or evidence of low to moderate skin sensitization rate in humans

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative

## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
 Species: Mouse  
 Application Route: Intraperitoneal injection  
 Method: OECD Test Guideline 474  
 Result: negative  
 Remarks: Based on data from similar materials

**Zinc oxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Result: negative

Test Type: In vitro mammalian cell gene mutation test  
 Method: OECD Test Guideline 476  
 Result: equivocal

Test Type: Chromosome aberration test in vitro  
 Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
 Species: Rat  
 Application Route: inhalation (dust/mist/fume)  
 Method: OECD Test Guideline 474  
 Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
 Species: Rat  
 Application Route: inhalation (dust/mist/fume)  
 Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
 Species: Mouse  
 Application Route: Intraperitoneal injection  
 Method: OECD Test Guideline 474  
 Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

**Talc:**

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
 Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative

**WHITE COLLAR**

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

**Dolomite:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative  
 Remarks: Based on data from similar materials

**Calcium oxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative

Test Type: Chromosome aberration test in vitro  
 Method: OECD Test Guideline 473  
 Result: negative  
 Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
 Method: OECD Test Guideline 476  
 Result: negative  
 Remarks: Based on data from similar materials

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative  
 Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
 Method: OECD Test Guideline 476  
 Result: negative  
 Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro  
 Method: OECD Test Guideline 473  
 Result: negative  
 Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Product:**

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Mouse  
 Application Route : Skin contact  
 Exposure time : 78 weeks  
 Method : OECD Test Guideline 451

# SAFETY DATA SHEET



## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
Date of first issue: 05/19/2015

---

Result : negative

### Zinc oxide:

Species : Mouse  
Application Route : Ingestion  
Exposure time : 1 Years  
Result : negative  
Remarks : Based on data from similar materials

### Talc:

Species : Mouse  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Years  
Result : negative

### Calcium oxide:

Species : Rat  
Application Route : Ingestion  
Exposure time : 104 weeks  
Result : negative  
Remarks : Based on data from similar materials

### Quartz:

Species : Humans  
Application Route : inhalation (dust/mist/fume)  
Result : positive  
Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

**IARC**      Group 1: Carcinogenic to humans  
Quartz      14808-60-7  
(Silica dust, crystalline)

**OSHA**      OSHA specifically regulated carcinogen  
Quartz      14808-60-7  
(crystalline silica)

**NTP**      Known to be human carcinogen  
Quartz      14808-60-7  
(Silica, Crystalline (Respirable Size))

### Reproductive toxicity

Not classified based on available information.

### Components:

#### Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

Species: Rat  
 Application Route: Ingestion  
 Result: negative  
 Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: inhalation (dust/mist/fume)  
 Method: OECD Test Guideline 414  
 Result: negative  
 Remarks: Based on data from similar materials

**Talc:**

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: Ingestion  
 Result: negative

**Dolomite:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative  
 Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative  
 Remarks: Based on data from similar materials

**Calcium oxide:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative  
 Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Mouse  
 Application Route: Ingestion  
 Method: OECD Test Guideline 414  
 Result: negative

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the



## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative  
 Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
 Species: Rat  
 Application Route: Ingestion  
 Method: OECD Test Guideline 422  
 Result: negative  
 Remarks: Based on data from similar materials

**STOT-single exposure**

Not classified based on available information.

**Components:****Calcium oxide:**

Assessment : May cause respiratory irritation.

**STOT-repeated exposure**

Not classified based on available information.

**Components:****Zinc oxide:**

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

**12-Hydroxy lithium stearate:**

Routes of exposure : Ingestion  
 Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

**Quartz:**

Routes of exposure : inhalation (dust/mist/fume)  
 Target Organs : Lungs  
 Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

**Repeated dose toxicity****Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rat  
 NOAEL : > 0.98 mg/l  
 Application Route : inhalation (dust/mist/fume)  
 Exposure time : 28 Days  
 Remarks : Based on data from similar materials

**WHITE COLLAR**

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
Date of first issue: 05/19/2015

---

**Zinc oxide:**

Species : Rat, male  
NOAEL : 0.0015 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 3 Months  
Method : OECD Test Guideline 413

**Dolomite:**

Species : Mouse  
NOAEL : 1,300 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days  
Remarks : Based on data from similar materials

**12-Hydroxy lithium stearate:**

Species : Rat  
NOAEL : > 88 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days

**Calcium oxide:**

Species : Rat  
NOAEL :  $\geq 0.399$  mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Species : Rat  
NOAEL : 100 mg/kg  
LOAEL : 300 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408

**Quartz:**

Species : Humans  
LOAEL : 0.053 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Remarks : These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

**Aspiration toxicity**

Not classified based on available information.

## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity****Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203  
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
 Exposure time: 21 d  
 Remarks: Based on data from similar materials
- Toxicity to microorganisms : NOEC: > 1.93 mg/l  
 Exposure time: 10 min  
 Remarks: Based on data from similar materials

**Zinc oxide:**

- Toxicity to fish : LC50: > 0.1 - 1 mg/l  
 Exposure time: 96 h  
 Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.136 mg/l  
 Exposure time: 72 h  
 NOEC (Pseudokirchneriella subcapitata (green algae)): > 0.01 - 0.1 mg/l  
 Exposure time: 72 h  
 Remarks: Based on data from similar materials
- Toxicity to fish (Chronic toxicity) : NOEC (Jordanella floridae (flagfish)): > 0.01 - 0.1 mg/l  
 Exposure time: 14 Weeks  
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): > 0.01 - 0.1 mg/l  
 Exposure time: 7 d  
 Remarks: Based on data from similar materials

**Talc:**

## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l  
 Exposure time: 24 h

**Dolomite:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 16.6 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203  
 Remarks: No toxicity at the limit of solubility.  
 Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 16.6 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202  
 Remarks: No toxicity at the limit of solubility.  
 Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials

**12-Hydroxy lithium stearate:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201

**Calcium oxide:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203  
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 202  
 Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials

EC10 (Pseudokirchneriella subcapitata (green algae)): > 1

## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Crangon crangon (shrimp)): > 1 mg/l  
 Exposure time: 14 d  
 Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50: > 100 mg/l  
 Exposure time: 3 h  
 Method: OECD Test Guideline 209  
 Remarks: Based on data from similar materials

**Calcium bis(di C8-C10, branched, C9 rich, alkyl)naphthalenesulphonate):**

Toxicity to fish : LL50 (Cyprinus carpio (Carp)): > 100 mg/l  
 Exposure time: 96 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 203  
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
 Exposure time: 48 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 202  
 Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 10 mg/l  
 Exposure time: 72 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials

EL10 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l  
 Exposure time: 72 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2.2 mg/l  
 Exposure time: 21 d  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 211

Toxicity to microorganisms : NOEC: > 100 mg/l  
 Exposure time: 3 h  
 Method: OECD Test Guideline 209  
 Remarks: Based on data from similar materials

## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
 Date of first issue: 05/19/2015

**Quartz:****Ecotoxicology Assessment**

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

**Persistence and degradability****Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.  
 Biodegradation: 2 - 4 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B

**12-Hydroxy lithium stearate:**

Biodegradability : Result: Readily biodegradable.  
 Biodegradation: 78 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301C

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Biodegradability : Result: Not readily biodegradable.  
 Remarks: Based on data from similar materials

**Bioaccumulative potential****Components:****Zinc oxide:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
 Bioconcentration factor (BCF): 78 - 2,060

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Partition coefficient: n-octanol/water : log Pow: > 6.6

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.  
 Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
 Empty containers retain residue and can be dangerous.

## WHITE COLLAR

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
8.0	11/04/2020	120076-00017	Date of first issue: 05/19/2015

Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.

If not otherwise specified: Dispose of as unused product.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 3077  
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  
 (Zinc oxide, Antimony, dialkyl dithiocarbamate)  
 Class : 9  
 Packing group : III  
 Labels : 9

**IATA-DGR**

UN/ID No. : UN 3077  
 Proper shipping name : Environmentally hazardous substance, solid, n.o.s.  
 (Zinc oxide, Antimony, dialkyl dithiocarbamate)  
 Class : 9  
 Packing group : III  
 Labels : Miscellaneous  
 Packing instruction (cargo aircraft) : 956  
 Packing instruction (passenger aircraft) : 956  
 Environmentally hazardous : yes

**IMDG-Code**

UN number : UN 3077  
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  
 (Zinc oxide, Antimony, dialkyl dithiocarbamate)  
 Class : 9  
 Packing group : III  
 Labels : 9  
 EmS Code : F-A, S-F  
 Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

UN/ID/NA number : UN 3077  
 Proper shipping name : Environmentally hazardous substance, solid, n.o.s.  
 (Zinc oxide, Antimony, dialkyl dithiocarbamate)  
 Class : 9  
 Packing group : III  
 Labels : CLASS 9  
 ERG Code : 171  
 Marine pollutant : yes(Zinc oxide, Antimony, dialkyl dithiocarbamate)

# SAFETY DATA SHEET



## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
Date of first issue: 05/19/2015

Remarks : Above applies only to containers over 119 gallons or 450 liters., Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

|| This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Respiratory or skin sensitization  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Zinc oxide	1314-13-2	>= 20 - < 30 %
------------	-----------	----------------

### US State Regulations

#### Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Zinc oxide	1314-13-2
Polytetrafluoroethylene	9002-84-0
Talc	14807-96-6
Calcium oxide	1305-78-8
Antimony, dialkyl dithiocarbamate	15890-25-2

#### California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Zinc oxide	1314-13-2
Talc	14807-96-6
Calcium oxide	1305-78-8

#### California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Zinc oxide	1314-13-2
Talc	14807-96-6



# SAFETY DATA SHEET



## WHITE COLLAR

Version 8.0      Revision Date: 11/04/2020      SDS Number: 120076-00017      Date of last issue: 05/06/2020  
Date of first issue: 05/19/2015

Calcium oxide      1305-78-8

### California Regulated Carcinogens

|| Quartz      14808-60-7


### The ingredients of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
- AICS : All ingredients listed or exempt.

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH	/	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIH / STEL : Short-term exposure limit
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
- NIOSH REL / C : Ceiling value not be exceeded at any time.
- OSHA CARC / PEL : Permissible exposure limit (PEL)

# SAFETY DATA SHEET



## WHITE COLLAR

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
8.0	11/04/2020	120076-00017	Date of first issue: 05/19/2015

---

OSHA Z-1 / TWA : 8-hour time weighted average  
OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/04/2020

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

# SAFETY DATA SHEET



## WHITE COLLAR

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2020
8.0	11/04/2020	120076-00017	Date of first issue: 05/19/2015

---

US / Z8