

## DRILLING COMPOUND

## BESTOLIFE® ZN-50 &amp; ZN-60



5 Gallon Plastic Pail

## PRODUCT CHARACTERISTICS

<b>Color:</b>	Gray
<b>Penetration:</b> (ASTM D217)	265-295
<b>NLGI Grade:</b>	2
<b>Weight/Gallon:</b>	14-16 pounds/gallon
<b>Thickener:</b>	Lithium
<b>Fluid Type:</b>	Petroleum
<b>Dropping Point:</b> (ASTM D2265)	≥350°F (≥177°C)
<b>Flash Point:</b>	≥485°F (≥252°C)
<b>Brushable To:</b>	10°F (-12°C)
<b>Service Rating:</b>	350°F (177°C)
<b>Friction Factor:</b>	1.0*
<b>Shelf Life:</b> (Unopened container)	4 years
<b>Contains:</b>	Zinc and other nonmetallic additives

\*NOTE: Due to operation and equipment variables, this value may require adjustment based on field experience.

Note: All package sizes are not listed. Call your sales representative for a complete listing.

## DESCRIPTION

BESTOLIFE® ZN-50 and ZN-60 are zinc-based thread compounds recommended for all rotary shouldered connections.

## APPLICATIONS

Zinc-based thread compound recommended for drilling, tool joints, drill collars, and coring bits.

## TECHNICAL DATA

ZN-50 and ZN-60 contain finely powdered metallic zinc, H<sub>2</sub>S and oxidation inhibitors bound in a high quality, washout resistant grease. Both products combat galling, seizing, and downhole makeup.

## NOTES

A safety data sheet is available from the manufacturer. Do not use on oxygen lines or in oxygen enriched atmospheres.

## PACKAGING

PRODUCT ZN-50	CONTAINER SIZE	CONTAINER WEIGHT
622240	3 1/2 gallon	40 pounds plastic
622255	5 gallon	55 pounds plastic
622259	5 gallon	60 pounds metal

PRODUCT ZN-60	CONTAINER SIZE	CONTAINER WEIGHT
623340	3 1/2 gallon	40 pounds plastic
623370	5 gallon	70 pounds metal



**BESTOLIFE**  
PREMIUM COMPOUNDS

2126 Vanco Dr. • Irving, TX 75061 • (855) 243-9164

**BESTOLIFE.COM**