

BASIC GUIDE TO MAGNETIC DRILLS & ANNULAR CUTTERS

How to use a Magnetic Drill with Annular Cutters, what to look for, best practices and tips to extend tool life & achieve the best performance

www.hougen.com

Magnetic Drills	
What is a Magnetic Drill?	3
When Do I Use a Mag Drill?	3
Where is a Mag Drill Used?	
Parts to a Mag Drill	
Which Mag Drill Do I Select?	5
Size of a Mag Drill	
Mag Drill Options	. 5
Annular Cutters	
What is an Annular Cutter?	6
Why Use an Annular Cutter?	
What Annular Cutter Do I Use?	. 6
Types of Annular Cutters	
Parts to an Annular Cutter	. 8
Diameter & Depth	. 8
Cutter Geometry	
Standard vs. Stack-Cut Geometry	
Non-Coated vs. Coated	
What is a Pilot?	10
Other Types of Annular Cutters	
What Makes an Annular Cutter Turn?	11
Annular Cutter Accessories	11
Tips & Troubleshooting	
Mag Drill - Magnet Adhesion	
Mag Drill - Surface Requirements	
How Do I Keep My Mag Drill from Slipping?	
Do I Have to Use Coolant?	13
What Causes Dull or Broken Cutters?	
Why Does My Slug Stick?	14
Maintaining Your Mag Drill	14
Is a Safety Strap/Chain Necessary?	
Why is My Magnet Lifting Off the Material?	
What is Positive Slug Ejection?	14
What is the Proper Feed Rate for a Mag Drill?	15
Why Not use Quick Change Cutters?	15
Is a Carbide Cutter Better Than a HSS Cutter?	15
Aren't All Annular Cutters the Same?	15
Why Do I Have Trouble Drilling Stainless Steel?	16
Should I Use a Power Feed Drill?	16
Can I Drill on the Same Material They are Welding?	16
Can I Get a Custom Cutter Made?	16
Hougen History	
Portable Mag Drill Chart	
Annular Cutter Chart	19

What is a Magnetic Drill?

A magnetic drill is a specialized portable power tool used for drilling holes in steel and similar metals.

- They are used on the job site or in the shop
- Also referred to as a mag drill, portable base drills, portable drill press

When Do I Use a Mag Drill?

It can be time-consuming and cumbersome to try to maneuver large steel or pipe into position at a stationary drill press or work center. A portable magnetic drill allows you to take the drill to the work piece, instead of trying to bring the work piece to the drill.

 A portable magnetic drill may be used in any position—vertical, horizontal, or overhead (upside down)



Where is a Mag Drill Used?

- Steel Fabrication
- Building & Construction
- Bridge Rebuilding
- Mining
- Ship Building
- Truck, RV & Special Vehicle Build
- · Pipeline, Offshore & Oil Fields
- Welding Shops
- Power Utilities
- Railroad Industries
- Maintenance Facilities
- Mobile Repair Shops
- Machinery Riggers

Mag drills are used
everywhere from
everywhere from
one person shops
to large plants and
to large plants sites
construction sites
with 1,000's of
workers



Which Mag Drill Do I Select?

Use the chart on page 18 to determine which mag drill to use. The mag drill you select depends upon:

- Application
- · Diameter of hole
- Depth of hole to be drilled (D.O.C. Depth of Cut)
- Drilling speed requirements
- Number of holes
- Work environment
- Space / physical limitations
- . Type of material to be drilled

Size of a Mag Drill

Available in a variety of sizes. From ultra low profile to large multi-speed models.





Mag Drill Options

Mag Drills can also have many options/accessories to help increase the products versatility

- Coolant bottle system
- Swivel base magnet
- · Multi-speed gear box
- Power feed
- Drill chucks
- Pipe adapters
- Countersinking
- Tapping
- · Arbor adapters
- Vac-Pad™




What is an Annular Cutter?

An annular cutter is a specialized bit for drilling through steel. Like a hole saw for wood, an annular cutter only cuts the outside edge of a hole. It produces accurate burr-free holes to close tolerances without pre-drilling or step drilling. It can drill a much larger hole and requires less force and time than a standard twist drill bit. As it turns, the cutter produces chips from the outside cutting edges and after cutting the hole a 'slug' (round chunk of steel from the center of the cutter) falls out.



Annular Cutters offer superior holemaking capabilities. They cut faster, last longer, produce a better hole finish, a true round hole with very tight tolerances, can be re-sharpened and drills holes with less power and torque.



What Annular Cutter Do I Use?

Use the chart on page 19 to determine which annular cutter to use. The cutter you select depends on the diameter of the hole, the depth of cut and the type of material. A wide range of annular cutters are designed to cut through the following materials:

- Carbon Steel
- Hard Alloys ex: Titanium
- Stainless Steel
- Hastelloy
- Aluminum



Types of Annular Cutters

Rotabroach® M2 HSS (High Speed Steel)

Most popular and used for a wide variety of applications.

- Mild & Structural Steel
- Aluminum
- Stainless Steel (lower BHN)

Rotabroach® M2 HSS TiN Coated

Coatings offer better performance in harder steels.

- Structural Steel
- Stainless Steel

M42 Premium HSS Cutters (Cobalt)

Cobalt plus TiN coating offers even better performance in harder steels.

- Structural Steel
- Stainless Steel
- Cast Iron

Copperhead™ Carbide Tip

Carbide provides longer tool life in harder or abrasive materials. Use a higher RPM than HSS tools for best tool life.

- Corroded or Weathered Material
- Structural & Stainless Steel
- AR

Rotabroach® Industrial Cutters

Available in M2 with and without coatings. Used for:

- Special drilling applications
- Industrial machining
- HMD915







Parts to an Annular Cutter



Diameter & Depth

When determining cutter size, they are measured by depth and diameter. If you look at an actual cutter the depth is actually longer than what it is rated, (a 1" cutter is really 1-1/4") because this ensures the tool can drill all the way through the hole and allows extra length for resharpening.




Cutter Geometry

Angles on the cutting teeth make a big difference in how the tool performs. More precision angles increase the tool life and accuracy. Hougen tools have four different tooth geometries.

- 2 angle
- 2 & 3 angle Hougen-Edge®
- Stack-Cut
- Industrial

Different Angles on the Teeth



Standard vs. Stack-Cut Geometry

Most annular cutters come with Standard geometry. These cutters are designed to cut through one piece of steel. They offer the fastest, cleanest hole producing a slug that looks like a 'Top Hat'. When the job requires drilling two or more pieces of steel, cutters with stack-cut geometry *must* be used. The cutting teeth cut from the inside out producing a round cylinder slug.







Stack-Cut Geometry Slug



Non-Coated vs. Coated

For 80% of applications a standard HSS cutter works.

Using a coated or carbide cutter in these applications offers no additional benefit. Hard materials is where the benefit of using a coated or carbide cutter will pay off with increased tool life.



Standard Rotabroach® Cutter



TiN Coated Rotabroach® Cutter

What is a Pilot?

A Pilot is a large nail looking object that must be used when using an annular cutter. It serves three very important functions:

- 1. Locates the center of the hole
- 2. Allows coolant to flow down around the slug and to the cutting teeth
- 3. Ejects the slug at the end of the cut



Slot allows coolant to flow to the cutting teeth

Pilots go through the center of the cutter. They retract up into the mag drill arbor as the hole is made. Pilots last a very long time and can be used with multiple sizes of cutters.

Other Types of Annular Cutters

Hougen makes many different annular cutters even ones for sheet metal. Below are two styles of annular cutters for use in hand-held drills and drill presses. They offer many of the same advantages as the mag drill annular cutters such as speed, quality of hole and longer tool life.



What Makes an Annular Cutter Turn?



Magnetic Drills

Annular Cutters are most often used with mag drills but can also be used with machine tools such as mills and large drill presses with tool holders.

Industrial Machines




Annular Cutter Accessories



Chuck Arbors





Hole Enlarging Pilots



TIPS & TROUBLESHOOTING FOR USING MAG DRILLS & ANNULAR CUTTERS

READ YOUR OPERATOR'S MANUAL ALWAYS OBSERVE STANDARD AND SPECIFIC SAFETY INSTRUCTIONS

When in Doubt

VISIT WWW.HOUGEN.COM OR CALL HOUGEN TECHNICAL SERVICE 800-426-7818

Mag Drill - Magnet Adhesion

Mag drills must magnetize to a solid surface. Magnetic strength is related to steel thickness. Minimum thickness is 3/8". If the material is thinner, the magnet will not hold well. Clamp another piece of steel on top or below the thinner steel for stronger adhesion. Material that is clean and free from coatings will offer the best surface for the magnet. For non-ferrous materials use a Vac-pad™ (HMD904 only) or clamp a piece a steel on top of it.

Mag Drill - Surface Requirements

A clean smooth surface will allow the magnet to 'stick' better. Situations where the magnet will have **reduced** holding power...

- a) Material less than 3/8" thick
- b) Coatings or paint layers on material
- c) Chips, dirt, or grease between the magnet and the material
- d) Curved surface (Surface should be flat. For pipe applications, a pipe adapter should be used.)
- e) Magnet only partially on work surface

How Do I Keep My Mag Drill from Slipping?

Make sure the drill's magnetic base is clear of chips and debris and is securely attached to a clean surface. Uneven surfaces or large debris buildup prevents the magnet from obtaining optimal holding power, which can cause the drill to shift or lift during operation. A safety chain or strap also helps to prevent injury if the drill shifts. If it does shift or lift during the cut, it is very possible the cutter will break. Hougen mag drills have a built-in safety circuit that stops the motor when the drill lifts from the material. Always use a safety chain especially in horizontal & overhead positions.

Do I Have to Use Coolant?

No.... **BUT...** Coolant increases annular cutter tool life **dramatically**. Hougen offers a number of different kinds of lubricant depending on the application. RotaMagic[™] Concentrated Cutting Fluid is a biodegradable coolant that is mixed with water and used with a mag drills coolant system. Slick-Stik[™] is a waxy lubricant. The user applies a glob to the inside and cutting teeth. Slick-Stik melts as the hole is made. Good for horizontal and overhead holes. RotaFoam[™] is a foamy spray lubricant that is sprayed onto the cutter before each hole.

For best results use the mag drills coolant system. Spraying or squirting coolant at the cutter while it is turning does very little in helping tool life. Most of the coolant is pushed aside by the chips and flutes before it reaches the cutter.

*** Note: For Hougen drills without coolant bottles... fill the coolant reservoir through the slots in the arbor. This will hold enough coolant for one hole.

What Causes Dull or Broken Cutters?

The primary cause of broken or prematurely dull cutters is a feed rate that is too slow. Slow feed rates will reduce the life of your cutter. Using a firm, steady feed pressure throughout the cut will maximize performance and extend tool life. You want to hear the drill motor working & the cutter producing long stringy chips that are being pulled from the hole. Look for a bird's nest around the cutter.

Blue Chips = Big Problem

(Something obstructing the coolant system or you're pushing too hard)



The cause of cutters quickly cutters quickly dulling is too little dulling is too little feed pressure.

"Babying" the tool will only decrease tool life.

Make sure you have the correct cutter for the material. Stack-Cut for multiple layers.

Second reason why cutters break is movement of the drill or work piece. The cutter wall can easily be snapped if the drill and material is not held rigid.

Good Looking Chips!!

Why Does My Slug Stick?

Using lubricant or cutting fluid helps the slug to eject at the end of the cut. But when slug ejection becomes unreliable or the steel resists cutting, it probably means the cutter's cutting edges are becoming dull. Re-sharpen or replace your cutter. Also make sure there are no chips inside your cutter which can hold up a slug. Also periodically check your ejection springs to maintain proper spring life.

Maintaining Your Mag Drill

For the best performance, always maintain your drill as instructed in the operator's manual. A list of op manuals can be found at *Hougen.com* if the manual supplied with your drill can not be located. Many mag drills feature a slide/gib/way system that requires periodic adjustments to maintain rigidity and optimal performance. Worn or damaged parts should be replaced to reduce the possibility of injury. The mag drill should be spot checked for damage prior to use. This will prevent costly repairs from running a damaged drill.

Is a Safety Chain / Strap Necessary?

YES! Your mag drill should always be used with a safety strap or chain especially in horizontal or upside down positions. Not only for safety of the operator but protecting your investment.

True Story - Many many Hougen drills have been lost over the years from falling from bridges when the power cord was unplugged. They fell into the water because they weren't using the safety chain.

Why is My Magnet Lifting Off the Material?

Check your surface as outlined in surface requirements (See Page 12). Also be sure the bottom of the magnet is free from chips and debris. A dull cutter can also push the magnet off the work surface. When drilling upside down, push on the handle closest to the arbor.

What Should I Do After Drilling the Hole?

- Turn off motor
- · Ensure the slug has been ejected
- Clean away any chips from the cutting tool & around and under the magnet

What is Positive Slug Ejection?

It is an arbor system that when the feed handles are retracted requires the slug to be pushed out after drilling a hole. The handles will not fully retract until the slug comes out of the cutter. All Hougen drills include this feature. It is a much more reliable method than a spring ejection arbor.

What is the Proper Feed Rate for a Mag Drill?

A solid steady feed rate should be used to maximize cutter tool life. Listen to the motor. You want the sound of the motor to bog down a little. It should sound like its working. Do not over drive or under drive it as you can break or damage the drill. Also do not "peck" at the hole... meaning... feed the cutter down then let up, then feed the cutter down and let up. This can quickly destroy your tool.

Why Not Use Quick Change Cutters?

Quick change cutters are nice and convenient if you need to change sizes every hole or two. But using a mag drill with the **two set screws to hold the cutter** in place offers a couple of advantages:

- Holds the cutter more rigid and less opportunity for it to move and break
- Will give up to 2x the tool life

Is a Carbide Cutter Better than a HSS Cutter?

Not necessarily. Carbide cutters are great tools and work good in most types of materials. But where they really shine is when they are used in hard or abrasive materials. They can be used in mild and structural steel but to get the best performance, carbide tooling needs to be turned at a much higher RPM than HSS cutters.

Aren't All Annular Cutters Pretty Much the Same?

That would be like saying all meat tastes the same. Hougen was the inventor of the mag drill annular cutter technology. Rotabroach® Cutters include the most features for the widest range of materials and benefits for long tool life. It takes a lot of extra time to machine and quality check the tools to ensure the customer gets what they expect. When purchasing a Hougen annular cutter, you are buying the highest quality Rotabroach tool in the market.

Why Do I Have Trouble Drilling Stainless Steel?

Stainless steel is a beautiful material but it can easily work harden. Meaning... if you let off your feed pressure and allow heat to build up, the material can harden up to the point that it becomes almost impossible to continue. Use solid steady feed pressure, plenty of coolant and **DO NOT** let up to adjust your position.

Should I Use a Power Feed Drill?

Power feed drills offer a nice option for increased productivity. Many shops set up multiple drills for one operator to run.

Can I Drill on the Same Material They are Welding?

No. Drilling on the same material as they are welding can cause the magnet and circuit board to short out.

Can I Get a Custom Cutter Made?

Absolutely! Hougen can solve your holemaking problems with creative solutions to help you get the job done, complete it faster and at a lower cost. We have helped thousands of customers with unique holemaking solutions. Give us a call or send us an email with your holemaking challenge.



For Technical Support & Warranty Service
Contact Hougen Mfg

www.hougen.com
15

North & South America 800-426-7818 22,23 tech@hougen.com

Australia 03 5277 2611 ausales@hougen.com

Hougen Manufacturing, Inc.



Hougen Manufacturing is a family owned business with our world headquarters and manufacturing facility located in Swartz Creek Michigan. The company was started by the late Dr. E Douglas Hougen who held over 400 worldwide patents including many for the Rotabroach® Annular Cutter. For over 50 years Hougen has been the world leader in portable magnetic drills and annular cutters. Hougen proudly manufactures all of our magnetic drills, Rotabroach Cutters and most of our other products in Michigan.

Customers who demand reliability and performance from their tools choose Hougen. From engineering, to manufacturing, to customer service, Hougen produces the best product in the market. Period. With our three principles in mind "Service, Integrity, Reliability", Hougen ensures you will be happy with our product and will work to continually solve your holemaking problems.

- Over 400 patents worldwide
- Invented spotweld cutter 1959
- Patented Rotabroach Cutter 1973
- First lightweight magnetic drill 1974
- First mag drill to use annular cutters
- First mag drill to drill over 1-1/2" dia.
- First mag drill to drill 3" deep
- First mag drill with positive slug ejection
- First mag drill with safety switch
- First mag drill with thru the tool coolant system
- First mag drill with quill feed spindle
- Quality American Made Products

PORTABLE MAGNETIC DRILLS


		HMD115	HMD150	HMD904	HMD925	HMD914	HMD505 / HMD508	HMD915
M		Low F	Profile		Fabricating		Heavy Du	ty Drilling
	RotaLoc™	/	/	With Adapter	With Adapter	With Adapter	With Adapter	
ıtters	RotaLoc Plus™		V	With Adapter	With Adapter	With Adapter	With Adapter	
Annular Cutters	Rotabroach® "12,000-Series"				<u>/</u>			With Adapter (5/8" & Larger)
Annu	Copperhead™ Carbide Tipped				/			
	Rotabroach® "42/43,000-Series"							/
S	Diameter Min./ Max.	1/2" to 1-1/16" (12 - 27mm)	7/16" to 1-3/8" (12 - 35mm)	7/16" to 1-1/2" (12 - 38mm)	7/16" to 1-1/2" (1-1/4" Pwr. Fd.) (12 - 38mm) (32mm Pwr Fd.)	7/16" to 2-1/16" (12 - 52mm)	7/16" to 2-3/8" (12 - 60mm)	5/8" to 3-1/16" (16 - 77mm)
ation	Depth Max.	3/4" (19mm)	1" (25mm)	2" (50mm)	2" (50mm)	3" (76mm)	3" (76mm)	3" (76mm)
ecific	Cutter Mounting	Bayonet Style	Bayonet Style	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" Double Flat	3/4" or 1-1/4" Weldon Shank
Model Specifications	No-Load R.P.M.	450	450	450	450	350	250 / 450 450 / 750	120 / 332 (w/ gear swap)
Mo	Model Weight	21.3 lbs (9.7 kg)	22.7 lbs (10.3 kg)	27.5 lbs (12.5 kg)	37 lbs (16.8 kg)	41 lbs (18.6 kg)	45 lbs (20.4 kg)	69 lbs (31.3 kg)
	Thru-the-Tool Coolant					/		
	Carrying Case Included	/	V		Optional			
	Swivel Base			Optional	Optional	Optional		
	Pipe Adapter			/	Manual Mode			Bracket Mount
(0	Tap Attachment			/	Manual Mode			
sories	Vac-Pad™							
cces	Coolant Bottle			Optional	Included	Included	Included	Included
ple 4	Countersink Kit				Manual Mode			With Adapter
Available Accessories	Twist Drill Adapter			<u>/</u>	Manual Mode		V	With Adapter
	Ratchet Drive							
	Arbor Extender				Manual Mode			With Adapter
	Drill Chuck			/	Manual Mode			
	RotaLoc™ Spindle Adapter			/	Manual Mode	/	/	

HOUGEN® CUTTER COMPARISON CHART

	4						(<
Hougen									
Tool Series:	RotaCut"	Extended Reach	Holcutter"	Carbide Holcutter"	RotaLoc™	RotaLoc Plus"	Rotabroach[®]	Copperhead""	"42/43,000"
Diameter Range Min. / Max.	1/4" to 1-1/2" (6mm - 25mm)	3/8" to 9/16"	11/16" to 3"	11/16" to 3"	1/2" to 1-1/16" (12mm - 27mm)	7/16" to 1-3/8" (12mm - 35mm)	7/16" to 2-3/8" (12mm - 60mm)	9/16" to 2" (14mm - 60mm)	3/4" to 3-1/16"
Max. Depth of Cut	1/4" to 1/2" (6.4mm - 12.7mm)	1/4" (6.4mm)	1/8" (3.2mm)	1/8" (3.2mm)	3/4" - (19mm) Stack Geometry	1" - (25mm)	1" to 6" (25mm to 152mm)	1" to 4" (25mm to 102mm)	2" or 3" (50mm or 76mm)
Mounting	3/8" or 1/2" Triple Flat Shank	3/8" Triple Flat Shank	3/8" Triple Flat Shank	3/8" or 1/2" Triple Flat Shank	Bayonet Style	Bayonet Style	3/4" Double Flat or Fusion" Shank	3/4" Double Flat or Fusion" Shank	3/4" Weldon or 1-1/4" Weldon
Cutter Material(s) Available	M2 HSS	M2 HSS	M2 HSS	Carbide Tip	M42 HSS	M2 HSS	M2 HSS, M2 TiN Coat, or M42 TiN	Carbide Tip	M2 HSS or M2 TiN Coat
Can be Resharpened		====== Dispo	======= Disposable ========		<u>\</u>	<u>\</u>	<u>\</u>		<u>\</u>
Available Grind Down (Within Limits)	/				/	<u> </u>	/		<u>\</u>
Max. Application Hardness Rating	275 BHN (28.5 HRC)	275 BHN (28.5 HRC)	275 BHN (28.5 HRC)	450 BHN (47.2 HRC)	350 BHN (37.7 HRC)	275 BHN (28.5 HRC)	275 BHN 325 BHN (TiN)	450 BHN (47.2 HRC)	275 BHN 325 BHN (TiN)
Recommended Lubrication	Slick-Stik™	Slick-Stik™	Slick-Stik™	Slick-Stik™	Slick-Stik™	Slick-Stik™	RotaMagic™	RotaMagic™	RotaMagic™
Aluminum					High RPM & Fast Feed Rates Suggested				
Mild Steel	_	<u>></u>	<u>></u>	<u>\</u>	<u>\</u>	<u>\</u>	<u>\</u>		_
Harder Steel		Good		<u>\</u>	Better	Good	Standard - Good TiN - Better	<u>\</u>	Standard - Good TiN - Better
Stainless Steel	99	Good	Recommend Speed Reducer	<u>\</u>	99	Good	TiN Coat or Premium Recommended	<u>\</u>	TiN Coat Recommended

Hougen Regional Sales Agencies

Your Link to Field Service, Sales Support and Training



B & B Industrial Inc.

15532 S.W. Pacific Hwy C1B #413 Tigard, Oregon 97224 Phone: (503) 639-7106 m.bullard2010@hotmail.com Alaska, Idaho, Oregon, Montana, Washington

Bohlman & Associates

7976 Clyo Rd Suite A
Centerville, OH 45459
Phone: (937) 435-1786
gbohlman@aol.com
Kentucky, Southern Indiana, Southern
Ohio, Western Pennsylvania & Western
New York

Cowles & Son, Inc

P.O. Box 1099 Princeton, MA 01541 Phone: (978) 464-0607 robkcowles@aol.com Connecticut, Maine, Massachusetts, New Hampshire, Vermont, Rhode Island

Fuller & Associates

587 Marilee Rd Gunter, TX 75058 Phone: 800-722-7078 tfuller@fullerrep.com Texas, Arkansas, Louisiana, Oklahoma

Canada

309 Nash Rd N Hamilton, Ontario L8H 7P4 Phone: 800-426-7818 m.tobola@hougen.com

Gardner & Meredith

P.O. Box 4837 Chattanooga, TN 37405 Phone: (423) 756-4722 dgard80421@aol.com Alabama, Florida, Georgia, Mississippi, North Carolina, South Carolina, Tennessee, Virginia, West Virginia

Hougen Manufacturing

3001 Hougen Drive Swartz Creek, MI 48473 Phone: (810) 635-7111 b.otero@hougen.com Michigan, North East Indiana, North Ohio

Impact Sales

2450 Pendleton Place Waukesha, WI 53188 Phone: (262) 366-1170 mschimel@tds.net Chicago Area, Eastern Wisconsin, NW Indiana, Parts of Iowa

Kenbil Engineering

2900 Adams C-18 Riverside, CA 92504 Phone: (951) 689-6633 dave@kenbil.com California, Nevada, Arizona

Australia

2/9 Shepherd Court North Geelong, VIC, 3215 1800 HOUGEN 03 5277 2611 ausales@hougen.com

KB Sales

104 Cain Drive Brentwood, NY 11717 Phone: (631) 269-7260 kbsales@optimum.net Eastern New York and Northern New Jersey

P.G. Tool Company

537 Mantua Ave, Suite 201 Woodbury, NJ 08096 Phone: (856) 848-2288 sales@pgtool.com Eastern Pennsylvania, Maryland, Delaware, Washington DC, Southern New Jersey

Pro Tool & Machine Sales

7000 N Broadway Street
Building 2, Unit 205
Denver, CO 80221
Phone: (303) 887-6551
jvancoevern@comcast.net
Colorado, Wyoming, New Mexico, Utah,
Western Nebraska

Weinacht & Associates

400 N. Bluff Road Collinsville, IL 62234 Phone: (618) 345-6565 kweinacht@weinacht.com Kansas, Missouri, North Dakota, South Dakota, Minnesota, Iowa, Parts of Illinois, Nebraska, and Western Wisconsin



HOUGEN MANUFACTURING, INC.

3001 Hougen Drive • Swartz Creek, MI 48473 USA Ph: (810) 635-7111 • Fax: (810) 635-8277 info@hougen.com • www.hougen.com