

HELVETIA

Dakota

Description:

Dakota is an oil-based leather with a pull-up effect with a smooth appearance on the finest European hides.

SPECIFICATIONS

Average Hide Size	54 sqft (+/-)
Thickness	0.9 - 1.1 mm

PERFORMANCE CHARACTERISTICS

Light Fastness (AATCC Method 16)	3-4
Tear Strength (ASTM D4705)	25 lbs.
Flexing Endurance (ASTM D2097)	Pass
Abrasion (ASTM D3884)	N/A
Elongation (ASTM D2211)	30% - 60% at 50 lbs.
Crocking (ASTM D5053)	Wet:4 Dry:4-5
Breaking Force (ASTM D2208)	150 lbs.

FLAMMABILITY

Boston Fire Dept. Code (BFD 1x1) w/Fire Blocker and or Fire Barrier Cloth	Pass
California Technical Bulletin 117	Pass
Cigarette Ignition Resistanc (NFPA 260)	Class 1
California Technical Bulletin 133 w/Fire Blocker and/or Fire Barrier Cloth	Pass

CLEANING INSTRUCTIONS

Natural, aniline leathers have little surface protection. If your aniline leather does become soiled, immediately blot excess liquid with a soft, clean cloth. Then clean the entire area (i.e. the entire seat cushion, arm rest, etc.) with a clean, damp cloth and clear luke warm water, starting from the outside of the spill to the center.

Do not use: Any saddle soaps, oils, abrasives, cleaners, soaps, furniture polish, varnish or ammonia water.

Please note: Due to the natural characteristics of this leather, scratches and marks may appear over time. This appearance is the "character" of the natural leather.