

# Cadence

## PROPERTIES

### Description

Italian enhanced grain, semi-aniline leather. Available in 12 in-stock FiberDye® colors.

### Attributes

Durable, anti-bacterial finish. Flame resistant. UV protected. Water and stain repellent dyed into the leather.

### Average Hide Size

50.00 sq. ft.

### Thickness

1.1mm +/- 0.1mm

### Weight

2.75oz +/- 0.25oz per sq. ft.

### Grain Characteristics

Uniform

### Finish Characteristics

Durable

## TEST PERFORMANCE

### ABRASION

#### CS-10

#### Taber Abrasion Resistance

1000 cycles

### ANTI-BACTERIAL

#### AATCC 100

#### Assessment of Anti-Bacterial Finishes on Textile Materials (Quantitative)

Meets Requirements

#### AATCC 147

#### Assessment of Anti-Bacterial Activity of Textile Materials (Qualitative)

Meets Requirements

### ENVIRONMENTAL

#### GREENGUARD

#### Indoor Air Quality

Certified

### FLAMMABILITY

#### California Technical Bulletin

#### 117 Section E Flammability Test

Certified

#### FMVSS 302

#### Federal Motor Vehicle Safety Standards Flammability of Interior Materials

Certified

#### FAR 25.853 (a) Am. 25-116, App. F, Part I (a)(1)(ii)

#### Federal Aviation Regulation for Flammability Resistance

Passes with flame treatment

#### IMO A.652(16)8.2

#### International Marine Organization Smoldering Cigarette Test

Passed

### NFPA 260

#### National Fire Protection Association

#### Cigarette Ignition Resistance

Certified

#### BS 5852:2006:Source 5

#### British Standard Flammability Test

Certified

### ASTM E84

#### Surface Burning Characteristics of Building Materials

Class A

### LIGHT FASTNESS

#### AATCC 16-2004, Opt 3

#### Colorfastness to Light

Class 5 at 72 hours

Cadence may be used in California TB 133 applications with suitable fire backers.

## DURABILITY

Excellant. Recommended for all upholstery applications, especially high traffic areas.



Available Worldwide  
Visit [garrettleather.com](http://garrettleather.com) for a showroom in your area.



800.342.7738  
[www.garrettleather.com](http://www.garrettleather.com)