

Garrett Glazed®

PROPERTIES

Description

Italian full grain, semi-aniline leather.
Available in 10 in-stock FiberDye® colors.

Attributes

Hand-antiqued with high gloss finish.
Flame resistant. UV protected. Water and stain repellent dyed into the leather.

Average Hide Size

55.00 sq. ft.

Thickness

1.1mm +/- 0.1mm

Weight

2.75oz +/- 0.25oz per sq. ft.

Grain Characteristics

Smooth

Finish Characteristics

High gloss

TEST PERFORMANCE

ABRASION

CS-10

Taber Abrasion Resistance
5600 cycles

ANTI-BACTERIAL

AATCC 100

Assessment of Anti-Bacterial Finishes on
Textile Materials (Quantitative)
Meets Requirements

AATCC 147

Assessment of Anti-Bacterial Activity of
Textile Materials (Qualitative)
Meets Requirements

ENVIRONMENTAL

GREENGUARD

Indoor Air Quality
Certified

FLAMMABILITY

California Technical Bulletin
117 Section E Flammability Test
Certified

FAR 25.853 (a) Am. 25-116,
App. F, Part I (a)(1)(ii)
Federal Aviation Regulation
for Flammability Resistance
Passes with flame treatment

FMVSS 302

Federal Motor Vehicle Safety Standards
Flammability of Interior Materials
Certified

IMO A.652(16)8.2

International Marine Organization
Smoldering Cigarette Test
Passed

IMO.A652(16)8.3

International Marine Organization
20 Second Butane Flame Test
Passed

NFPA 260

National Fire Protection Association
Cigarette Ignition Resistance
Certified
ASTM E84

Surface Burning Characteristics
of Building Materials
Class B on MDF backer

BS 5852:2006:Source 5

British Standard Flammability Test
Certified

LIGHT FASTNESS

AATCC 16-2004, Opt 3

Colorfastness to Light
Class 3.5 at 72 hours

Glazed maybe used in California TB 133
applications with suitable fire backers.

DURABILITY

| Excellent. Recommended for all upholstery applications, especially high traffic areas.



Available Worldwide
Visit garrettleather.com for a showroom in your area.

Garrett
Leather

800.342.7738
www.garrettleather.com