

# Resilience

## PROPERTIES

### Description

Italian full grain, pure aniline leather.  
Available in 10 in-stock FiberDye® colors.

### Attributes

Paraffin wax and scratch resistant finish.  
Unique variations and natural markings.

### Average Hide Size

60.00 sq. ft.

### Thickness

1.1 mm +/- 0.1 mm

### Weight

2.75oz +/- 0.25oz per sq. ft.

### Grain Characteristics

Natural variations

### Finish Characteristics

Paraffin wax and scratch resistant finish.

## TEST PERFORMANCE

### ABRASION

ASTM D-4157  
Wyzenbeek Abrasion Resistance  
Class 5 at 100,000 cycles

### ANTI-BACTERIAL

AATCC 100  
Assessment of Anti-Bacterial Finishes on  
Textile Materials (Quantitative)  
Meets Requirements

### AATCC 147

Assessment of Anti-Bacterial Activity of  
Textile Materials (Qualitative)  
Meets Requirements

### LIGHT FASTNESS

AATCC 16-2004, Opt 3  
Colorfastness to Light  
Class 3.5 at 72 hours

### ENVIRONMENTAL

GREENGUARD  
Indoor Air Quality  
Certified

### FLAMMABILITY

California Technical Bulletin  
117 Section E Flammability Test  
Certified

FAR 25.853 (a) Am. 25-116,  
App. F, Part I (a)(1)(ii)  
Federal Aviation Regulation  
for Flammability Resistance  
Passes with flame treatment

### FMVSS 302

Federal Motor Vehicle Safety Standards  
Flammability of Interior Materials  
Certified

### IMO A.652(16)8.2

International Marine Organization  
Smouldering Cigarette Test  
Passed

### IMO.A652(16)8.3

International Marine Organization 20  
Second Butane Flame Test  
Passed

### NFPA 260

National Fire Protection Association  
Cigarette Ignition Resistance  
Certified

### BS 5852:2006:Source 5

British Standard Flammability Test  
Certified

Resilience may be used in California TB 133  
applications with suitable fire backers.

## DURABILITY

| Recommended for all upholstery applications.