



Material Safety Data Sheet

EXPERT PLATINUM SUPWH 874620

1. Product and company identification

Product name : EXPERT PLATINUM SUPWH 874620
Synonym : Not available.
Trade name : Not available.
Material uses : Not available.
Manufacturer : Akzo Nobel Canada Inc.
2505 De la Métropole,
Longueuil, QC, J4G 1E5
Validation date : 2011-11-18.
Print date : 2011-11-18.
Responsible name : Regulatory Department
In case of emergency : 514 495-5710
8:00 - 17:00
Product use : Water based coating

2. Hazards identification

Emergency overview :



MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER, BASED ON ANIMAL DATA.

Slightly irritating to the eyes, skin and respiratory system. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Contains material that may cause target organ damage, based on animal data. Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Medical conditions aggravated by over-exposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (section 11)

3. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
titanium dioxide	13463-67-7	10 - 30
sodium potassium aluminum silicate	37244-96-5	5 - 10
aluminum silicate hydrate (pig white 19)	1332-58-7	1 - 5
propylene glycol	57-55-6	1 - 5

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4 . First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5 . Fire-fighting measures

- Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Special remarks on fire hazards** : Not available.
- Special remarks on explosion hazards** : Not available.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

6 . Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8 . Exposure controls/personal protection

Product name

titanium dioxide

Exposure limits

ACGIH TLV (United States, 1/2009). Notes: Substance identified by other sources as a suspected or confirmed human carcinogen. 1996 Adoption Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124) :36338-33351, June 30, 1993, for revised OSHA PEL. Refers to Appendix A - - Carcinogens.

TWA: 10 mg/m³ 8 hour(s).

OSHA PEL (United States, 11/2006).

TWA: 15 mg/m³ 8 hour(s). Form: Total dust

OSHA PEL 1989 (United States, 3/1989).

TWA: 10 mg/m³ 8 hour(s). Form: Total dust

aluminum silicate hydrate (pig white 19)

ACGIH TLV (United States, 1/2009). Notes: 1996 Adoption Refers to Appendix A -- Carcinogens. Respirable fraction; see Appendix C, paragraph C.

TWA: 2 mg/m³ 8 hour(s). Form: Respirable fraction

NIOSH REL (United States, 6/2009).

TWA: 5 mg/m³ 10 hour(s). Form: Respirable fraction

TWA: 10 mg/m³ 10 hour(s). Form: Total

OSHA PEL (United States, 11/2006).

TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction

TWA: 15 mg/m³ 8 hour(s). Form: Total dust

OSHA PEL 1989 (United States, 3/1989).

TWA: 5 mg/m³ 8 hour(s). Form: Respirable fraction

TWA: 10 mg/m³ 8 hour(s). Form: Total dust

8 . Exposure controls/personal protection

propylene glycol

AIHA WEEL (United States, 1/2009). Notes: 2004 Revised Document

TWA: 10 mg/m³ 8 hour(s).

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Other protection : Not available.

Personal protective equipment (Pictograms) : Not available.

9 . Physical and chemical properties

Physical state : Liquid.

Flash point : Not applicable.

Auto-ignition temperature : Not available.

Color : Various

Odor : Characteristic

pH : 9

Boiling/condensation point : 100°C (212°F)

Melting/freezing point : -5°C (23°F)

Specific gravity : 1,28

Vapor pressure : 3,3 kPa (25 mm Hg)

Vapor density : >1 [Air = 1]

Volatility : 62.34% (v/v), 48.4% (w/w)

Odor threshold : Not available.

Evaporation rate : 0,05 (butyl acetate = 1)

VOC : 85,2 g/l [Method 24]

Dispersibility properties : Easily dispersible in the following materials: cold water.

9 . Physical and chemical properties

- Octanol/water partition coefficient** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Dynamic: 1400 mPa·s (1400 cP)

10 . Stability and reactivity

- Stability** : The product is stable.
- Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.
- Conditions to avoid** : No specific data.
- Materials to avoid** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Conditions of reactivity** : Not available.
Not available.

11 . Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
propylene glycol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rabbit	18500 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
	LDLo Oral	Rabbit	20000 mg/kg	-

Chronic toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Not available.					

Sensitizer

Product/ingredient name	Route of exposure	Species	Result
Not available.			

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
titanium dioxide	A4	2B	-	-	-	-
Kaolin	A4	-	-	-	-	-
propane-1,2-diol	-	-	-	None.	-	-

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Not available.			

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Not available.						

Synergistic products : Not available.

11 . Toxicological information

Potential acute health effects

- Inhalation** : Slightly irritating to the respiratory system.
Ingestion : No known significant effects or critical hazards.
Skin : Slightly irritating to the skin.
Eyes : Slightly irritating to the eyes.

Potential chronic health effects

- Chronic effects** : Contains material that may cause target organ damage, based on animal data.
Carcinogenicity : Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.
Target organs : Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, stomach.

Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:
 respiratory tract irritation
 coughing
Ingestion : No specific data.
Skin : Adverse symptoms may include the following:
 irritation
 redness
Eyes : Adverse symptoms may include the following:
 irritation
 watering
 redness

12 . Ecological information

- Environmental effects** : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
titanium dioxide	-	Acute EC50 >1000000 ug/L Fresh water	Daphnia - Water flea - Daphnia magna - <24 hours	48 hours
	-	Acute LC50 5,5 ppm Fresh water	Daphnia - Water flea - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) - <24 hours	48 hours
	-	Acute LC50 >1000000 ug/L Marine water	Fish - Mummichog - Fundulus heteroclitus	96 hours
	-	Chronic NOEC 500 ppm Fresh water	Daphnia - Water flea - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) - <24 hours	48 hours
	-	Chronic NOEC 1	Daphnia - Water	48 hours

12 . Ecological information

		ppm Fresh water	flea - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) - <24 hours	
propylene glycol	-	Acute EC50 >1000 mg/L Fresh water	Daphnia - Water flea - Daphnia magna - <24 hours	48 hours
	-	Acute EC50 >10000000 ug/L Fresh water	Daphnia - Water flea - Daphnia magna - 6 to 24 hours	48 hours
	-	Acute LC50 5122 to 6011 mg/L Fresh water	Daphnia - Water flea - Ceriodaphnia dubia - <24 hours	48 hours
	-	Acute LC50 4919 mg/L Fresh water	Daphnia - Water flea - Ceriodaphnia dubia - <24 hours	48 hours
	-	Acute LC50 34060 to 39339 mg/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <=7 days	96 hours
	-	Acute LC50 >1000 mg/L Marine water	Crustaceans - Amphipod - Chaetogammarus marinus - Young - 5 mm	48 hours
	-	Acute LC50 44 to 47 ml/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss - 0,8 g	96 hours
	-	Acute LC50 >62000000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <=7 days	96 hours
	-	Acute LC50 55770000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <=7 days	96 hours
	-	Acute LC50 18340000 ug/L Fresh water	Daphnia - Water flea - Ceriodaphnia dubia - <=24 hours	48 hours
	-	Acute LC50 15052 to 17561 mg/L Fresh water	Daphnia - Water flea - Ceriodaphnia dubia - <24 hours	48 hours
	-	Acute LC50 1020000 ug/L Fresh water	Daphnia - Water flea - Ceriodaphnia dubia - <=24 hours	48 hours
	-	Acute LC50	Fish - Fathead	96 hours

12 . Ecological information

	710000 ug/L Fresh water	minnow - Pimephales promelas - <=7 days	
-	Chronic NOEC 600000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <=7 days	96 hours
-	Chronic NOEC 13020000 ug/L Fresh water	Daphnia - Water flea - Ceriodaphnia dubia - <=24 hours	48 hours
-	Chronic NOEC 1000 mg/L Fresh water	Daphnia - Water flea - Daphnia magna - <24 hours	48 hours
-	Chronic NOEC 660000 ug/L Fresh water	Daphnia - Water flea - Ceriodaphnia dubia - <=24 hours	48 hours
-	Chronic NOEC 52930000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <=7 days	96 hours

- Conclusion/Summary** : Not available.
- Bioconcentration factor** : Not available.
- Mobility** : Not available.
- Toxicity of the products of biodegradation** : Not available.
- Other adverse effects** : No known significant effects or critical hazards.

13 . Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Waste stream : Not available.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14 . Transport information

TDG Classification Not regulated.

IMDG Class Not regulated.

IATA-DGR Class Not regulated.

15 . Regulatory information

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Label requirements : MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. POSSIBLE CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.) :

Health	*	2
Flammability		1
Physical hazards		0

The customer is responsible for determining the PPE code for this material.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

16 . Other information

Version : 4

Notice to reader

The manufacturer hereby declares that the information disclosed herein have been based on our raw material suppliers' data, information and notification. Such raw materials are being used as components in the manufacturing of the product. The manufacturer has no control over the nature and content of such information. The manufacturer fully reproduces all the information it holds on the constituent of the product, at the time it is manufactured. The manufacturer does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. By this data sheet, the manufacturer hereby discloses all the potential dangers it has knowledge of and which might be related to the using or manipulation of the product in order to allow the proper care to be brought and use with regard to the product. Materials used may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist and notification is hereby given to the user. The product must be handled with care and it is recommended to use all the required measures in order to ensure the protection and safety of any person using or handling the product. Notice is hereby given that injury can derive therefrom if the foregoing is not respected. The manufacturer assumes no responsibility for personal and/or material damage, lost or injury of whichever nature caused or which may occur following the wrongful, inappropriate, negligent or abusive use or handling of the product or from not having read the herein contained information.