

### Technical data sheet

#### Water based Stain for floors and interior wood finishing

##### PHYSICAL PROPERTIES

Color	10 base colors available
Solid content	8 % (weight)
pH	8.0 ± 1.0
VOC	452 g/L
Flash point	N. A.
Freeze / thaw stability	Keep from freezing
Drying time (depending on conditions)	To touch: 1 hour To recoat: 3 hours for wood tones and 6 hours for white tones
Viscosity	16 to 18 seconds (Zahn #2)
Density	N.A.

##### TECHNICAL DATA

Coverage	Up to 125 sq.ft. (11.5 m <sup>2</sup> ) / liter (depending on conditions)
Available size	940 mL
Shelflife	12 months (when kept in its original container)
Tool	Absorbent lint-free cloth
Tools clean-up	Warm soapy water
Storage	Between 10 and 30 °C (50 and 85 °F)
Waste disposal	Recycle if possible (Consult local authorities)



##### FIRST AID AND WARNING

In case of eye or skin contact, rinse well with water for 15 minutes. In case of inhalation, allow the victim to rest in a well-ventilated area. If swallowed, seek medical attention. Do not induce vomiting. Have conscious person drink several glasses of water. **KEEP OUT OF REACH OF CHILDREN**

##### APPLICATION

To read about the method of application, refer to Finitec's "Water based stain instructions".