

Mallia™

push-buttons, dimmers, automatic switches and other lighting functions - customisable colours



2 830 84



2 834 90



2 832 81



2 812 75

Plate selection charts p. 547

Conform to BS EN 60669 – 1
Painted polycarbonate front cover
Compact mechanism for a larger wiring space
Supplied with 2 screws M 3.5 for BS boxes
To be equipped with plates - Dim.: 86 x 86 mm

Pack Cat.Nos Push-buttons 10 A - 250 V~

Pack	Cat.Nos	Push-buttons 10 A - 250 V~
5	2 830 41	N/O contact (push to make) ● Silver ● Pearl ● Dark Silver
5	2 832 41	
5	2 834 41	
5	2 830 40	N/O contact with bell symbol ● Silver ● Pearl ● Dark Silver
5	2 832 40	
5	2 834 40	

RCD + LED dimmers

Pack	Cat.Nos	RCD + LED dimmers
1	2 830 86	Rotary dimmer 100-240 V~ without neutral, for all types of dimmable bulbs: - dimmable LED: 5 to 75 W (10 bulbs max.) - dimmable compact fluorescent bulbs: 5 to 75 W (10 bulbs max.) - fluorescent tube with ballast: 5 to 300 VA - halogen and incandescent: 5 to 300 W - electronic or ferromagnetic transformers: 5 to 300 VA When switched on, gradually (2 seconds) lights up at the level set before last switch off ● Silver ● Pearl ● Dark Silver
1	2 832 86	
1	2 834 86	

Leading edge dimmers

Pack	Cat.Nos	Leading edge dimmers
1	2 830 80	Rotary control dimmer 60-500 W for incandescent and halogen lamps 230 V~ 60-500 VA ELV halogen lamps with ferromagnetic transformer and compensator Cat.No 0 401 39 ● Silver ● Pearl ● Dark Silver
1	2 832 80	
1	2 834 80	
1	2 830 84	Rotary control dimmer + switch 60-500 W for incandescent and halogen lamps 230 V~ 60-200 VA ELV halogen lamps with ferromagnetic transformer and compensator Cat.No 0 401 39 ● Silver ● Pearl ● Dark Silver
1	2 832 84	
1	2 834 84	
1	2 830 85	Rotary dimmer 60-1000 W (230 V) - 60-500 W (127 V) for incandescent and halogen lamps 60-600 VA (230 V) 60-300 VA (127 V) for halogen lamps with electronic transformer with leading edge behaviour 60-1000 VA (230 V) 60-500 W (127 V) for halogen lamps with ferromagnetic transformers ● Silver ● Pearl ● Dark Silver
1	2 832 85	
1	2 834 85	

Pack Cat.Nos Programmable switches

Pack	Cat.Nos	Programmable switches
1	2 830 92	Power supply: 230 V~ - 50/60 Hz Maximum load: 2300 W Weekly programme Capacity: max. 28 programmes Output: 1 changeover contact ● Silver ● Pearl ● Dark Silver
1	2 832 92	
1	2 834 92	

Time delay switches

Pack	Cat.Nos	Time delay switches
1	2 830 91	Adjustable time from 5 min to 12 h Maximum load: 500 W incandescent and halogen lamps 230 V~ 250 W fluorescent lamps without capacitor ● Silver ● Pearl ● Dark Silver
1	2 832 91	
1	2 834 91	

Fan speed controls

Pack	Cat.Nos	Fan speed controls
1	2 830 81	400 VA rotary fan controls ● Silver ● Pearl ● Dark Silver
1	2 832 81	
1	2 834 81	
1	2 830 82	5-speed fan controls 100 W for fan with overall diameter 48" ● Silver ● Pearl ● Dark Silver
1	2 832 82	
1	2 834 82	

Cooker control units 45 A - 250 V~

Pack	Cat.Nos	Cooker control units 45 A - 250 V~
5	2 812 75	Supplied complete with plate Conform to BS 4177 45 A DP switch + 13 A switched socket outlet with red indicator Dim.: 146 x 86 mm ● Silver ● Pearl ● Dark Silver
5	2 832 75	
5	2 834 75	

Automatic switches

Pack	Cat.Nos	Automatic switches
1	2 830 90	IR movement detector Horizontal detection angle 180° Luminosity threshold: 43 to 1614 lux Temporization: 20 s - 15 min Detection range: max. 12 m Compatible load: 25 - 200 W for incandescent and halogen lamps 230 V~ ● Silver ● Pearl ● Dark Silver
1	2 832 90	
1	2 834 90	