



Colour: White T084
 Material: Thermoplastic
 Dimensions: 86 x 86 x 9.5 mm (1 gang) / 86 x 146 x 9.5 mm (2 gang)
 Supplied with 2 screws M3.5 for BS boxes

| Pack | Cat.Nos | Television sockets |
|--------------------------|----------|--|
| 10 | 6 171 21 | Single TV socket, female |
| 10 | 6 171 20 | Single TV socket, "F" type |
| 10 | 6 171 23 | Double TV socket, female + "F" type |
| 10 | 6 171 27 | Double female TV socket |
| Telephone sockets | | |
| 10 | 6 170 99 | Telephone connection block 10 connections |
| 10 | 6 170 95 | BT master |
| 10 | 6 170 96 | BT secondary |
| 10 | 6 170 97 | RJ 11 socket |
| 10 | 6 170 98 | Double RJ 11 socket |
| Telephone + data sockets | | |
| 10 | 6 170 94 | RJ 11 + RJ 45 Cat.5e UTP socket |
| 10 | 6 170 93 | RJ 11 + RJ 45 Cat.6 UTP socket |
| Data sockets | | |
| 10 | 6 170 90 | RJ 45 Cat.5e UTP |
| 10 | 6 170 91 | RJ 45 Cat.6 UTP |
| 10 | 6 170 92 | Double RJ 45 Cat.6 UTP |

| Pack | Cat.Nos | Key card switch |
|--------------------------------|----------|--|
| 1 | 6 170 12 | 16 A - 230 V - 50 Hz Time delay of approx. 30 s after card removal |
| Hotel bedrooms call indicators | | |
| 10 | 6 170 13 | 2 settings : - Do not disturb - Please clean the room Indicator lamp + bell push Installed in the corridor, display calls |
| 10 | 6 170 14 | Internal control unit Installed in the room, allows the user to select the desired setting |
| Shaver socket | | |
| 1 | 6 170 68 | Conform to BS 61558 115/230 V - 20 VA - 50/60 Hz Surface or flush-mounting, back box to be min. 47 mm deep - 2 gang |
| Security switch | | |
| 1 | 6 170 19 | 1 A resistive - 250 V~ Panic button |