

Synergy™

single pole switches, single pole push and key switches, rotary dimmers - white



7 300 00



7 300 06



7 311 51



7 301 56

Front plates: white thermoset. Terminal screws captive and backed off ready for cabling - large angled terminal entries
Compact mechanism for maximised wiring space. Supplied with faceplate screw caps

Pack	Cat.Nos	Single pole plate switches 10 AX - 250 V~	Pack	Cat.Nos	3 pole fan switch 10 A - 250 V~
10	7 300 00	Conform to BS EN 60669-1 For flush-mounting, back box to be min. 16 mm deep ASTA licence Nominal plate dimensions: 86 x 86 mm 1 gang - 1 way	10	7 300 09	Conform to BS EN 60669-1: 2000 With integrated padlockable safety block in OFF position. Flush-mounting back box: min 25 mm deep Nominal plate dimensions: 86 x 86 mm 3 pole fan switch
10	7 300 01	1 gang - 2 way			
10	7 300 05	1 gang - intermediate			
10	7 300 24	2 gang - 1 way			
10	7 300 02	2 gang - 2 way			
10	7 301 24	3 gang - 1 way			
10	7 300 03	3 gang - 2 way			
5	7 300 04	Nominal plate dimensions: 86 x 146 mm 4 gang - 2 way			
5	7 300 06	6 gang - 2 way	1	7 311 51	Push on/off rotary universal dimmer 5 W/300 W 100 - 240 V~ - 50/60 Hz Conform to IEC 60669-2-1 For flush-mounting back box to be min. 40 mm deep Equipped with overvoltage and short-circuit protection Screw terminals. For all types of lamps: - dimmable LEDs: 5 W to 75 W - dimmable compact fluorescent lamps: 5 W to 75 W - halogen with ferromagnetic or electronic transformer: 5 VA to 300 VA - fluorescent tube - ballast: 5 VA to 300 VA - halogen and incandescent 230 V: 5 W to 300 W When switched on, gradually (2 seconds) lights up at the level set before last switch-off Nominal plate dimensions: 86 x 86 mm 1 gang
10	7 301 30	Single pole plate switches 20 AX - 250 V~ Conform to BS EN 60669-1 For flush-mounting, back box to be min. 16 mm deep Nominal plate dimensions: 86 x 86 mm 1 gang - 1 way			
10	7 301 31	1 gang - 2 way			
10	7 301 34	2 gang - 1 way			
10	7 301 32	2 gang - 2 way	1	7 301 56	Push on/off rotary dimmers 400 W 100 - 240 V~ - 50/60 Hz Conform to BS EN 60669-1 For flush-mounting, back box to be min. 25 mm deep Nominal plate dimensions: 86 x 86 mm 1 gang - 2 way
10	7 301 35	3 gang - 1 way	1	7 301 57	2 gang - 2 way
10	7 301 33	3 gang - 2 way	1	7 300 49	Nominal plate dimensions: 86 x 146 mm 4 gang - 2 way
5	7 300 07	Single pole push switches 10 A - 250 V~ Conform to BS EN 60669-1 For flush-mounting, back box to be min. 16 mm deep ASTA licence Nominal plate dimensions: 86 x 86 mm 1 gang - 2 way push switch			
5	7 300 11	1 gang - 2 way push switch marked "PRESS"			
5	7 301 07	1 gang - 2 way push switch with bell symbol			
10	7 300 08	Single pole key switch 10 AX - 250 V~ Conform to BS EN 60669-1: 2000 Key supplied. For flush-mounting, back box to be min. 16 mm deep. Nominal plate dimensions: 86 x 86 mm 1 gang - 2 way	1	7 301 50	1 gang

Surface mounting boxes, p. 554

